

UNIVERSITI MALAYSIA PAHANG

DECLARATION OF THESIS / UNDERGRADUATE PROJECT PAPER AND COPYRIGHT

Author's full name: **NORHIDAYAH BINTI HAMIDON**

Date of birth : **17 FEBRAURY 1987**

Title : **THE EFFECTIVENESS OF RECTANGULAR AND
CYLINDRICAL CONCRETE BLOCKS AS ENERGY
DISSIPATION STRUCTURES IN SPILLWAY AND
STILLING BASIN**

Academic Session : **2009/2010**

I declare that this Final Year Project Report is classified as:

- CONFIDENTIAL** (Contains confidential information under the Official Secret Act 1972)*
- RESTRICTED** (Contains restricted information as specified by the organization where research was done)
- OPEN ACCESS** I agree that my thesis to be published as online open access (full text)

I acknowledged that Universiti Malaysia Pahang reserves the right as follows:

1. The Final Year Project Report is the property of Universiti Malaysia Pahang.
2. The Library of Universiti Malaysia Pahang has the right to make copies for the purpose of research only.
3. The Library has the right to make copies of the thesis for academic exchange.

Certified by:

SIGNATURE

870217-14-5024

(NEW IC NO./PASSPORT NO.)

Date: 23 NOVEMBER 2009

SIGNATURE OF SUPERVISOR

NORASMAN B IN OTHMAN

NAME OF SUPERVISOR

Date: 23 NOVEMBER 2009

NOTES: * If the Final Year Project Report is CONFIDENTIAL or RESTRICTED, please attach with the letter from the organization with period and reasons for condentially or restriction.

**THE EFFECTIVENESS OF RECTANGULAR AND CYLINDRICAL
CONCRETE BLOCKS AS ENERGY DISSIPATION STRUCTURES IN
SPILLWAY AND STILLING BASIN**

NORHIDAYAH BINTI HAMIDON

**A final year project report submitted in fulfillment of the requirements for the
award of the degree of Bachelor in Civil Engineering**

Faculty of Civil Engineering and Earth Resources

Universiti Malaysia Pahang

NOVEMBER 2009

“I hereby declare that this final year project report, submitted to Universiti Malaysia Pahang as a partial fulfillment of the requirements for the degree of Bachelor of Civil Engineering. I also certify that the work described here is entirely my own except for excerpts and summaries whose sources are appropriately cited in the references.”

Signature :

Name : NORHIDAYAH BINTI HAMIDON

Date : 9 NOVEMBER 2009

“Specially dedicated to my beloved late father, mother, brothers and sister, lecturers
and friends....”

ACKNOWLEDGEMENT

In the name of Allah S.W.T the Most Gracious and the Most Merciful. Praise and blessings be upon the Holy Prophet Muhammad S.A.W. It is with Grace and Blessings of Allah S.W.T, *Alhamdulillah* this project have been completed finally.

My utmost gratitude goes to my supervisor, Mr. Norasman Bin Othman, lecturer of Faculty of Civil Engineering and Earth Resources for his precious guidance and patience that helped me a lot in completing this final year project.

Here I would also like to acknowledge Hydraulic and Hydrology Laboratory and Construction Laboratory lab technicians especially Mr. Muhammad Nurul Fakhri, Mr. Ahmad Shuhaimi and Mr. Mohd Qari for their contributions that helped me to accomplish my study. My special thank goes to my friend, Chew Chai Siah for her support and helps in constructing the open channel model structure at the laboratory. Last but not least I would like to give my special gratitude to my friends, lecturers and family for being with me to put this thesis through.

ABSTRACT

Velocity of flow water in a channel will increase when there are different between water level at upstream and downstream of a channel. High velocity of flow water can be possessed by water flow in a spillway which the flow is caused by the gravitational force. A high velocity of flow water could possibly cause bad impacts such as erosion and scouring of riverbed and bank. Besides, this problem could also cause some destruction to the hydraulic structure like spillway and stilling basin. Regarding to this matter, the suitable precaution method need to be considered in order to control the high velocity of flow water. Therefore, a rectangular open channel model structure (40 cm x 60 cm) consists of spillway and stilling basin parts is constructed and used to conduct an experiment to study the performances and effectiveness of rectangular and cylindrical concrete blocks as energy dissipation structures. In this study, concrete blocks are arranged in row arrangement and various pattern of arrangements in spillway and stilling basin of a channel. The water flow depth and flow velocity are recorded and analyzed before and after locating energy dissipaters. For row arrangements, the increase in number of row and number of blocks can reduced the velocity of flow water more effectively and alternate arrangement of concrete blocks give the best result in reduction of flow velocity for various pattern of arrangements. In this study, the rectangular concrete block is proved to be more effective in reducing the flow velocity compared to the cylindrical concrete block with percentage of reduction of 73.68% for row arrangement and 75.41% for alternate pattern of arrangement.

ABSTRAK

Halaju air yang mengalir di dalam saluran akan bertambah apabila adanya perbezaan aras air di antara kawasan hilir dan hulu saluran. Aliran air berhalaju tinggi boleh berlaku apabila air mengalir melalui struktur alur limbah di mana aliran air adalah disebabkan oleh daya tarikan graviti bumi. Aliran air berhalaju tinggi bukan sahaja boleh memberi kesan negatif terhadap alam sekitar seperti hakisan dan kerukan di dasar dan tebing sungai, malah turut menyebabkan berlakunya kerosakan terhadap struktur hidraulik seperti struktur alur limbah dan lembangan penenang. Oleh yang demikian, satu langkah pengawalan yang berkesan perlu diambil kira bagi mengawal aliran air yang berhalaju tinggi. Dalam kajian ini, sebuah model saluran terbuka berbentuk segi empat tepat (40 cm x 60 cm) yang terdiri daripada bahagian alur limbah dan lembangan penenang telah dibina di makmal untuk menjalankan ujikaji bagi mengkaji penggunaan serta keberkesanan blok konkrit berbentuk segiempat tepat dan silinder sebagai struktur pengurangan halaju. Blok-blok konkrit yang diuji disusun mengikut corak susunan berbaris dan pelbagai corak susunan rawak di bahagian alur limbah dan lembangan penenang. Ukur dalam air dan halaju air akan diambil dan dianalisis sebelum dan selepas struktur pengurangan halaju diletakkan di kawasan uji kaji. Bagi susunan berbaris, penambahan jumlah baris blok serta penambahan kuantiti blok memberi kesan pengurangan halaju yang lebih baik dan corak susunan selang seli didapati paling efektif dalam mengurangkan halaju air bagi pelbagai corak susunan rawak. Blok konkrit berbentuk segiempat tepat memberi kesan pengurangan halaju yang lebih baik berbanding blok konkrit berbentuk silinder iaitu sebanyak 73.68% untuk susunan berbaris dan 75.41% bagi corak susunan selang seli.

TABLES OF CONTENTS

CHAPTER	TITLE	PAGE
	STATUS VALIDATION	i
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xi
	LIST OF FIGURES	xiii
	LIST OF SYMBOLS	xv
	LIST OF APPENDICES	xvii
1	INTRODUCTION	
	1.1 Background of Study	1
	1.2 Problem Statement	4
	1.3 Objectives	4
	1.4 Scope of Study	5
	1.5 Significant of Study	5

2 LITERATURE REVIEW

2.1	Spillways	6
2.2	Froude Number (Fr)	9
2.3	Specific Energy (E)	10
2.4	Hydraulic Jump	12
2.4.1	Types of Hydraulic Jump	13
2.4.2	Hydraulic Jump in Sloping Channels	16
2.5	Types of Energy Dissipater	17
2.5.1	Hydraulic Jump Stilling Basin	18
2.5.1.1	The Saint Anthony Falls (SAF) Stilling Basin	18
2.5.1.2	United States Bureau of Reclamation (USBR) Stilling Basin	19
2.5.2	Stepped Spillways	23
2.5.3	Trajectory Buckets	25
2.5.4	Baffled Apron Drops	28

3 METHODOLOGY

3.1	Introduction	30
3.2	Flow Chart of Project Methodology	30
3.3	Open Channel Model Structure Selection	32
3.4	Research parameter selection	33
3.5	Energy Dissipater Model Structure	34
3.6	Discharge and Velocity Measurement	35
3.7	Water Depth Measurement	37

3.8	Arrangement and Position of the Energy Dissipater Structure	37
3.9	Procedure of the Experiment	42
3.10	Assumptions in the Experiment	43
4	RESULT AND DISCUSSION	
4.1	Introduction	44
4.2	Measurement of Flow Depth, y and Flow Velocity, v	45
4.3	Experimental Data Recorded	46
4.4	Results for Rectangular Concrete Blocks Energy Dissipaters	48
4.5	Results for Cylindrical Concrete Blocks Energy Dissipaters	53
4.6	Discussion	58
4.6.1	Discussion on Results after Locating Energy Dissipation Structures in Row Arrangement at Stilling Basin	58
4.6.2	Discussion on Results after Locating Energy Dissipation Structures in Row Arrangement at Spillway	60
4.6.3	Discussion on Results after Locating Energy Dissipation Structures In Various Arrangements at Stilling Basin	61

5 CONCLUSION AND RECOMMENDATION

5.1	Introduction	62
5.2	Conclusion	63
5.3	Problems Encountered	64
5.4	Recommendations	65

REFERENCES	66
-------------------	----

APPENDIX	69
-----------------	----

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Classification of Hydraulic Jump According to Froude Number	15
4.1	Initial Flow Depth and Velocity at Spillway and Stilling Basin	45
4.2	Example of Recorded Data for Flow Velocity after Locating 3 Rectangular Concrete Blocks in Row Arrangement with $d = 300$ mm at Stilling Basin	49
4.3	Example of Recorded Data for Flow Velocity after Locating 6 Rectangular Concrete Blocks in Row Arrangement with $d = 360$ mm at Spillways	51
4.4	Comparison of Percentage of Reduction in Flow Velocity after Locating Rectangular Concrete Blocks in Various Arrangements at Stilling Basin	52
4.5	Example of Recorded Data for Flow Velocity after Locating 3 Cylindrical Concrete Blocks in Row Arrangement with $d = 300$ mm at Stilling Basin	54

4.6	Example of Recorded Data for Flow Velocity after Locating 5 Cylindrical Concrete Blocks in Row Arrangement with $d = 300$ mm at Spillways	56
4.7	Comparison of Percentage of Reduction in Flow Velocity after Locating Cylindrical Concrete Blocks in Various Arrangements at Stilling Basin	57

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Main Spillway of Oldman Dam, Alberta	7
2.2	B.Everett Jordan Dam and Shaft Spillway, Haw River Chatham Country, N.C	8
2.3	A spillway bucket of Anderson Dam, California	8
2.4	Specific Energy Diagram	11
2.5	Phenomenon of Hydraulic Jump at Bottom of the Spillway	12
2.6	Jump Forms Related to Froude Number	13
2.7	Hydraulic Jump Types Sloping Channels	16
2.8	SAF Stilling Basin	19
2.9	Stilling Basin Structure Type II	20
2.10	Stilling Basin Structure Type III	21
2.11	Stilling Basin IV	22
2.12	The Skimming Flow Regime	23
2.13	Close Up View of RCC Steps	24
2.14	Ski Jump Buckets	25
2.15	Flip Buckets	26
2.16	Free Jet Spillway	26
2.17	Flip Bucket at Glen Canyon Dam, Arizona	27
2.18	Baffled Apron Drop	28
2.19	Baffle Apron Drop Energy Dissipater	29

3.1	Methodology of Study	31
3.2	Layout of Rectangular Open Channel	33
3.3	Rectangular Concrete Block	34
3.4	Cylindrical Concrete Block	34
3.5	Measurement Of Cross Sectional Area, A	36
3.6	Row Arrangement of Concrete Blocks	38
3.7	Arrangement of Pattern 1 of Concrete Blocks	39
3.8	Arrangement of Pattern 2 of Concrete Blocks	39
3.9	Arrangement of Pattern 3 of Concrete Blocks	40
3.10	Arrangement of Pattern 4 of Concrete Blocks	40
4.1	Location of the Data Taken From Conducted Experiment	47

LIST OF SYMBOLS

Symbol	Item
v	- Measured velocity
v_0	- Initial velocity
y	- Measured flow depth
y_0	- Initial flow depth
Q	- Flow rate
A	- Area of hydraulic section
m	- Meter
mm	- Millimeter
m^3/s	- Meter cubic per second
m/s	- Meter per second
m^2	- Meter squared
E	- Specific energy
h	- Height of channel's wall
L_1	- Length of spillway
L_2	- Length of stilling basin
B	- Width of channel
Fr	- Froude number
Δv	- Reduction in flow velocity
d	- Distance between rows of concrete blocks
s_1	- Distance between concrete block and channel's wall
$s_2/s_3/s_4/s_5/s_6$	- Distance between concrete blocks

γ	-	Unit weight of water
ϕ	-	Angle of channel with the horizontal
w	-	Weight of water in jump control volume
USBR	-	United States Bureau of Reclamation
MASMA	-	Manual Saliran Mesra Alam Malaysia

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A1	Design of Row Arrangement for Rectangular Concrete Blocks at Spillway and Stilling Basin	70
A2	Design of Row Arrangement for Cylindrical Concrete Blocks at Spillway and Stilling Basin	72
A3	Design of Various Arrangements for Rectangular Concrete Blocks at Stilling Basin	74
A4	Design of Various Arrangements for Cylindrical Concrete Blocks at Stilling Basin	77
B1	Recorded Data for Flow Velocity after Locating 3 Rectangular Concrete Blocks in Row Arrangement with $d = 300$ mm at Stilling Basin	79
B2	Recorded Data for Flow Velocity after Locating 4 Rectangular Concrete Blocks in Row Arrangement with $d = 300$ mm at Stilling Basin	80
B3	Recorded Data for Flow Velocity after Locating 5 Rectangular Concrete Blocks in Row Arrangement with $d = 300$ mm at Stilling Basin	80
B4	Recorded Data for Flow Velocity after Locating 6 Rectangular Concrete Blocks in Row Arrangement with $d = 300$ mm at Stilling Basin	81

B5	Recorded Data for Flow Velocity after Locating 3 Rectangular Concrete Blocks in Row Arrangement with d = 320 mm at Stilling Basin	81
B6	Recorded Data for Flow Velocity after Locating 4 Rectangular Concrete Blocks in Row Arrangement with d = 320 mm at Stilling Basin	82
B7	Recorded Data for Flow Velocity after Locating 5 Rectangular Concrete Blocks in Row Arrangement with d = 320 mm at Stilling Basin	82
B8	Recorded Data for Flow Velocity after Locating 6 Rectangular Concrete Blocks in Row Arrangement with d = 320 mm at Stilling Basin	83
B9	Recorded Data for Flow Velocity after Locating 3 Rectangular Concrete Blocks in Row Arrangement with d = 340 mm at Stilling Basin	83
B10	Recorded Data for Flow Velocity after Locating 4 Rectangular Concrete Blocks in Row Arrangement with d = 340 mm at Stilling Basin	84
B11	Recorded Data for Flow Velocity after Locating 5 Rectangular Concrete Blocks in Row Arrangement with d = 340 mm at Stilling Basin	84
B12	Recorded Data for Flow Velocity after Locating 6 Rectangular Concrete Blocks in Row Arrangement with d = 340 mm at Stilling Basin	85
B13	Recorded Data for Flow Velocity after Locating 3 Rectangular Concrete Blocks in Row Arrangement with d = 360 mm at Stilling Basin	85
B14	Recorded Data for Flow Velocity after Locating 4 Rectangular Concrete Blocks in Row Arrangement with d = 360 mm at Stilling Basin	86

B15	Recorded Data for Flow Velocity after Locating 5 Rectangular Concrete Blocks in Row Arrangement with d = 360 mm at Stilling Basin	86
B16	Recorded Data for Flow Velocity after Locating 6 Rectangular Concrete Blocks in Row Arrangement with d = 360 mm at Stilling Basin	87
B17	Recorded Data for Flow Velocity after Locating 3 Cylindrical Concrete Blocks in Row Arrangement with d = 300 mm at Stilling Basin	88
B18	Recorded Data for Flow Velocity after Locating 4 Cylindrical Concrete Blocks in Row Arrangement with d = 300 mm at Stilling Basin	89
B19	Recorded Data for Flow Velocity after Locating 5 Cylindrical Concrete Blocks in Row Arrangement with d = 300 mm at Stilling Basin	89
B20	Recorded Data for Flow Velocity after Locating 6 Cylindrical Concrete Blocks in Row Arrangement with d = 300 mm at Stilling Basin	90
B21	Recorded Data for Flow Velocity after Locating 3 Cylindrical Concrete Blocks in Row Arrangement with d = 320 mm at Stilling Basin	90
B22	Recorded Data for Flow Velocity after Locating 4 Cylindrical Concrete Blocks in Row Arrangement with d = 320 mm at Stilling Basin	91
B23	Recorded Data for Flow Velocity after Locating 5 Cylindrical Concrete Blocks in Row Arrangement with d = 320 mm at Stilling Basin	91
B24	Recorded Data for Flow Velocity after Locating 6 Cylindrical Concrete Blocks in Row Arrangement with d = 320 mm at Stilling Basin	92

B25	Recorded Data for Flow Velocity after Locating 3 Cylindrical Concrete Blocks in Row Arrangement with $d = 340$ mm at Stilling Basin	92
B26	Recorded Data for Flow Velocity after Locating 4 Cylindrical Concrete Blocks in Row Arrangement with $d = 340$ mm at Stilling Basin	93
B27	Recorded Data for Flow Velocity after Locating 5 Cylindrical Concrete Blocks in Row Arrangement with $d = 340$ mm at Stilling Basin	93
B28	Recorded Data for Flow Velocity after Locating 6 Cylindrical Concrete Blocks in Row Arrangement with $d = 340$ mm at Stilling Basin	94
B29	Recorded Data for Flow Velocity after Locating 3 Cylindrical Concrete Blocks in Row Arrangement with $d = 360$ mm at Stilling Basin	94
B30	Recorded Data for Flow Velocity after Locating 4 Cylindrical Concrete Blocks in Row Arrangement with $d = 360$ mm at Stilling Basin	95
B31	Recorded Data for Flow Velocity after Locating 5 Cylindrical Concrete Blocks in Row Arrangement with $d = 360$ mm at Stilling Basin	95
B32	Recorded Data for Flow Velocity after Locating 6 Cylindrical Concrete Blocks in Row Arrangement with $d = 360$ mm at Stilling Basin	96
C1	Recorded Data for Flow Velocity after Locating 3 Rectangular Concrete Blocks in Row Arrangement with $d = 300$ mm at Spillway	97
C2	Recorded Data for Flow Velocity after Locating 4 Rectangular Concrete Blocks in Row Arrangement with $d = 300$ mm at Spillway	98

C3	Recorded Data for Flow Velocity after Locating 5 Rectangular Concrete Blocks in Row Arrangement with d = 300 mm at Spillway	98
C4	Recorded Data for Flow Velocity after Locating 6 Rectangular Concrete Blocks in Row Arrangement with d = 300 mm at Spillway	99
C5	Recorded Data for Flow Velocity after Locating 3 Rectangular Concrete Blocks in Row Arrangement with d = 320 mm at Spillway	99
C6	Recorded Data for Flow Velocity after Locating 4 Rectangular Concrete Blocks in Row Arrangement with d = 320 mm at Spillway	100
C7	Recorded Data for Flow Velocity after Locating 5 Rectangular Concrete Blocks in Row Arrangement with d = 320 mm at Spillway	100
C8	Recorded Data for Flow Velocity after Locating 6 Rectangular Concrete Blocks in Row Arrangement with d = 320 mm at Spillway	101
C9	Recorded Data for Flow Velocity after Locating 3 Rectangular Concrete Blocks in Row Arrangement with d = 340 mm at Spillway	101
C10	Recorded Data for Flow Velocity after Locating 4 Rectangular Concrete Blocks in Row Arrangement with d = 340 mm at Spillway	102
C11	Recorded Data for Flow Velocity after Locating 5 Rectangular Concrete Blocks in Row Arrangement with d = 340 mm at Spillway	102
C12	Recorded Data for Flow Velocity after Locating 6 Rectangular Concrete Blocks in Row Arrangement with d = 340 mm at Spillway	103

C13	Recorded Data for Flow Velocity after Locating 3 Rectangular Concrete Blocks in Row Arrangement with d = 360 mm at Spillway	103
C14	Recorded Data for Flow Velocity after Locating 4 Rectangular Concrete Blocks in Row Arrangement with d = 360 mm at Spillway	104
C15	Recorded Data for Flow Velocity after Locating 5 Rectangular Concrete Blocks in Row Arrangement with d = 360 mm at Spillway	104
C16	Recorded Data for Flow Velocity after Locating 6 Rectangular Concrete Blocks in Row Arrangement with d = 360 mm at Spillway	105
C17	Recorded Data for Flow Velocity after Locating 3 Cylindrical Concrete Blocks in Row Arrangement with d = 300 mm at Spillway	106
C18	Recorded Data for Flow Velocity after Locating 4 Cylindrical Concrete Blocks in Row Arrangement with d = 300 mm at Spillway	107
C19	Recorded Data for Flow Velocity after Locating 5 Cylindrical Concrete Blocks in Row Arrangement with d = 300 mm at Spillway	107
C20	Recorded Data for Flow Velocity after Locating 6 Cylindrical Concrete Blocks in Row Arrangement with d = 300 mm at Spillway	108
C21	Recorded Data for Flow Velocity after Locating 3 Cylindrical Concrete Blocks in Row Arrangement with d = 320 mm at Spillway	108
C22	Recorded Data for Flow Velocity after Locating 4 Cylindrical Concrete Blocks in Row Arrangement with d = 300 mm at Spillway	109

C23	Recorded Data for Flow Velocity after Locating 5 Cylindrical Concrete Blocks in Row Arrangement with $d = 320$ mm at Spillway	109
C24	Recorded Data for Flow Velocity after Locating 6 Cylindrical Concrete Blocks in Row Arrangement with $d = 320$ mm at Spillway	110
C25	Recorded Data for Flow Velocity after Locating 3 Cylindrical Concrete Blocks in Row Arrangement with $d = 340$ mm at Spillway	110
C26	Recorded Data for Flow Velocity after Locating 4 Cylindrical Concrete Blocks in Row Arrangement with $d = 340$ mm at Spillway	111
C27	Recorded Data for Flow Velocity after Locating 5 Cylindrical Concrete Blocks in Row Arrangement with $d = 340$ mm at Spillway	111
C28	Recorded Data for Flow Velocity after Locating 6 Cylindrical Concrete Blocks in Row Arrangement with $d = 340$ mm at Spillway	112
C29	Recorded Data for Flow Velocity after Locating 3 Cylindrical Concrete Blocks in Row Arrangement with $d = 360$ mm at Spillway	112
C30	Recorded Data for Flow Velocity after Locating 4 Cylindrical Concrete Blocks in Row Arrangement with $d = 360$ mm at Spillway	113
C31	Recorded Data for Flow Velocity after Locating 5 Cylindrical Concrete Blocks in Row Arrangement with $d = 360$ mm at Spillway	113
C32	Recorded Data for Flow Velocity after Locating 6 Cylindrical Concrete Blocks in Row Arrangement with $d = 360$ mm at Spillway	114