

DESIGN AND ANALYSIS BATTERY
PACKAGING FOR ELECTRIC VEHICLE

SIBRA MALLISI BIN YUSSOF

BACHELOR OF ENGINEERING
UNIVERSITI MALAYSIA PAHANG

DESIGN AND ANALYSIS BATTERY PACKAGING FOR ELECTRIC VEHICLE
(EV)

SIBRA MALLISI YUSSOF

Thesis submitted in fulfillment of the requirements
for the award of the degree of
Bachelor of Mechanical Engineering with Automotive Engineering

Faculty of Mechanical Engineering
UNIVERSITI MALAYSIA PAHANG

NOVEMBER 2009

SUPERVISOR'S DECLARATION

I hereby declare that I have checked this project and in my opinion, this project is adequate in terms of scope and quality for the award of the degree of Bachelor of Mechanical Engineering with Automotive Engineering.

Signature :

Name of Supervisor : DR. YUSNITA RAHAYU

Position : Senior Lecturer

Date : 25 November 2009

STUDENT'S DECLARATION

I hereby declare that the work in this report is my own research except for quotations and summaries which have been duly acknowledged. The report has not been accepted for any degree and is not concurrently submitted for award of other degree.

Signature :

Name of Candidate : SIBRA MALLISI BIN YUSSOF

ID Number : MH06011

Date : 25 November 2009

UNIVERSITI MALAYSIA PAHANG
FACULTY OF MECHANICAL ENGINEERING

We certify that the project entitled “*(Design and analysis battery packaging for Electric Vehicle)*” Is written by *(Sibra Mallisi Bin Yussof.)* We have examined the final copy of this project and in our opinion; it is fully adequate in terms of scope and quality for the award of the degree of Bachelor of Engineering. We herewith recommend that it be accepted in partial fulfillment of the requirements for the degree of Bachelor of Mechanical Engineering with Automotive Engineering.

(Zamri Mohamed)

Examiner

Signature

To my beloved mother and father,

Mrs. Rubiah Binti Ghazali

Mr. Wan Khairudin Bin Wan Mohamad

ACKNOWLEDGEMENTS

Praise to Allah S.W.T, the most Merciful and the most Compassionate. Peace upon him Muhammad S.A.W, the messenger of Allah.

First and foremost, I would like to express my gratitude to my supervisor; Dr. Yusnita Rahayu for her invaluable guidance, suggestions and continuous encouragements in making this research possible. I appreciate her consistent support from the first day I applied to graduate program to these concluding moments. I am truly grateful for her progressive vision about my training in science, her tolerance of my naïve mistakes, and her commitment to my future career. This acknowledgment also goes to Dr. Sugeng Ariyono and for all lecturers and associates in Faculty of Mechanical Engineering, Universiti Malaysia Pahang. Their contribution and cooperation during my research was really helpful.

Finally, I wish to convey my heartfelt thanks to my parent, Wan khairudin Bin Wan Mohamad and Rubiah Binti Ghazali for their love, dream and sacrifice throughout my life. I cannot find the appropriate words that could properly describe my appreciation for their devotion, support and faith in my ability to obtain my goals.

ABSTRACT

Battery packaging is the packaging where the batteries Lead-acid or Lithium-Ion are kept safe. Battery packaging is installed in car such as electric vehicle, hybrid electric vehicle or the car that needs to convert to the electric vehicle. Batteries selection is made depend on the motor specification that install in the car. The battery packaging are important to make the performance of batteries are stable. The cooling system of battery packaging is used to make the heat flow in battery packaging not exceeding the operating temperature of the batteries. The proposed design is made to reach the design specification of battery packaging. Some of battery packaging is made without cooling system. More criteria needs to consider in order choosing the battery packaging such as cost, weight, available space, compact, maintenances and more. The selection of battery packaging must have all the criteria needed by battery packaging, therefore the analysis are made for selection material and heat transfer from battery packaging to outside of the car. The cooling system is effect most on the performance, weight, cost, and maintenances. For example, the liquid cooling system most effective than air cooling system, but liquid cooling have more deficiency in leakage problem, need more mass to complete the circulate of the cooling system and also higher cost of maintenances. The air cooling system less effective, but the cost is low than liquid, easy maintenance and also less mass. So that, this project is focus on cooling system type air to find most effective cooling system by three proposed design of air cooling system. At the end of this project, a new design of proposed battery packaging has been choose by using Solid Work software. There are some improvements have been made in order to reach the design criteria. As the result of this battery packaging design and analysis, the objective to design battery packaging and select the suitable battery packaging, analysis on the faster type design heat transfer from battery packaging to outside of the car can be achieved.

ABSTRAK

Kotak bateri adalah kotak dimana bateri seperti Lead-acid atau Lithium-ion disimpan. Kebiasaannya kotak bateri digunakan untuk kenderaan yang menggunakan tenaga elektrik. Projek ini fokus kepada kereta Proton Iswara dimana kereta ini ingin ditukar daripada menggunakan bahan api petrol kepada elektrik. Elektrik motor telah dipasang dalam kereta proton iswara, oleh itu pemilihan bateri adalah penting supaya jumlah voltan, kuasa dan arus yang sesuai dengan spesifikasi motor tercapai. Sistem penyejukan kotak bateri penting dalam memastikan suhu bateri adalah tidak melebihi suhu operasi bateri. Ini kerana, jika suhu yang berkumpul dalam kotak bateri melebihi suhu operasi bateri, bateri akan rosak dan melibatkan kos yang tinggi untuk menyelenggara bateri yang rosak. Projek ini menghasilkan tiga rekaan kotak bateri untuk mencapai rekaan yang sesuai sebagai kotak bateri kenderaan elektrik. Antara kriteria yang perlu ada pada kotak bateri ialah kos yang murah, berat yang sesuai, kekosongan tempat dalam kereta proton iswara dan kos penyelenggara kerosakan bateri dan kotak bateri. Contoh pada sistem penyejukan, kesan pada berat, kos dan penyelenggaraan adalah tinggi. Terdapat dua jenis sistem penyejukan, pertama menggunakan cecair penyejuk dan jenis kedua menggunakan udara sebagai bahan penyejuk. Sistem penyejuk cecair lebih member kesan pada kawalan suhu di dalam kotak bateri, tetapi jenis penyejukan cecair mempunyai banyak kekurangan seperti memerlukan banyak alat untuk siap, kos yang tinggi dalam pemasangan dan juga penyelenggaraan. Sistem ini juga boleh menyebabkan kebocoran pada cecair dan boleh merosakkan kotak bateri jika cecair bertindak balas dengan bahan membuat kotak bateri. Sistem penyejukan yang menggunakan angin kurang keberkesanan berbanding cecair penyejuk, tetapi mempunyai banyak kelebihan seperti kos yang rendah, kurang berat dan juga mudah untuk diselenggara. Oleh itu, projek ini fokus pada sistem penyejukan jenis angin, untuk memilih susunan kipas sedut angin dan kipas bebas angin yang paling memberi kesan pada penurunan dan kawalan suhu di dalam kotak bateri supaya kedua – dua jenis sistem penyejukan memberikan perbezaan yang kecil. Hasil daripada rekaan tiga jenis kotak bateri dan pemilihan kotak bateri yang paling cepat mengeluarkan haba daripada kotak bateri dapat dicapai.

TABLE OF CONTENTS

	Page
SUPERVISOR’S DECLARATION	ii
STUDENT’S DECLARATION	iii
PANEL DECLARATION	iv
DEDICATION	v
ACKNOWLEDGEMENTS	iv
ABSTRACT	vii
ABSTRAK	viii
TABLE OF CONTENTS	ix
LIST OF TABLES	xii
LIST OF FIGURES	xiii
LIST OF SYMBOLS	xvi
LIST OF ABBREVIATION	xvii
CHAPTER 1 INTRODUCTION	
1.1 Introduction	1
1.2 Project Background	2
1.3 Project Problem Statement	3
1.4 Project Objectives	4
1.5 Project Scope	4
1.6 Overview of the thesis	4
CHAPTER 2 OVERVIEW OF ELECTRIC VEHICLES BATTERY PACKAGING	
2.1 Introduction	5
2.2 History of Electric Vehicle	5
2.3 Electric Vehicle Batteries	7
2.3.1 Lead-acid Battery	7
2.3.2 Lithium-Ion and Nickel Metal Hybrid	8
2.4 Battery Packaging	11
2.5 Conclusion	15

CHAPTER 3 DESIGN CONSIDERATION OF BATTERY PACKAGING

3.1	Introduction	16
3.2	Design Requirement	18
	3.2.1 Available Space	18
	3.2.2 Specification of Motor in Proton Iswara	22
	3.2.3 Types of Material Specification	23
	3.2.4 Material Selection	24
	3.2.4.1 Steel and other material	24
	3.2.4.2 Aluminium Properties	24
3.3	Cooling System	27
	3.3.1 Liquid Cooling System	27
	3.3.2 Air Cooling System	28
3.4	Conclusion	29

CHAPTER 4 FINAL DESIGN OF PROTON ISWARA BATTERY PACKAGING

4.1	Introduction	30
4.2	Lead-acid Connection	31
	4.2.1 Series	31
	4.2.2 Parallel	33
4.3	Lithium-Ion Connection	34
	4.3.1 Series	34
	4.3.2 Parallel	36
4.4	Batteries Arrangement	38
4.5	Design Specification	40
	4.5.1 Installing Location	40
	4.5.2 Design One	41
	4.5.3 Design Two	43
	4.5.4 Design Three	45

4.6	Performance Analysis	47
	4.6.1 Stress Analysis	47
	4.6.2 Thermal Analysis	49
4.7	Design Dimensions	53
4.8	Conclusions	61

CHAPTER 5 CONCLUSION AND RECOMMENDATIONS

5.1	Introduction	62
5.2	Conclusions	63
5.3	Recommendations for Future Research	63

REFERENCES	65
-------------------	----

APPENDICES

A1	Gantt Chart Final Year Project 1	67
A2	Gantt Chart Final Year Project 2	68

LIST OF TABLES

Table No.	Title	Page
3.1	Motor Specification that already install in Proton Iswara	21
3.2	Aluminium detail properties	24
4.1	Lead-acid Battery	29
4.2	Lithium-Ion Specification	32
4.3	Total Batteries dimension in battery packaging	35

LIST OF FIGURES

Figure No.	Title	Page
2.1	Some of the newer EV's that made early 1902 by wood	6
2.2	Example of Lead-acid battery	7
2.3	Lithium-Ion Battery (LiFeP04)	8
2.4	Nickel Metal Hybrid (Ni-MH)	9
2.5	Comparison lifespan between Ni-MH and Li-Ion	10
2.6	Tesla Roadster Battery Packaging	12
2.7	Battery Packaging System of Chevrolet Volt	13
2.8	Front side of the Battery Packaging in Savy	14
2.9	Rear side of the Battery Packaging in Savy	14
3.1	Flow Chart for Overall of the Project	16
3.2	Front view of Proton Iswara	17
3.3	Available space at front Proton Iswara	18
3.4	Rear view Proton Iswara	18
3.5	Available Space at rear side of Proton Iswara	19

3.6	Dimensions of Rear side Proton Iswara	20
3.7	Example of Air cooling system	27
4.1	Arrangements of batteries in Battery Packaging	35
4.2	Schematic of Liquid cooling system	36
4.3	Schematic of Air cooling system	37
4.4	Rear view of Proton Iswara where the Battery Packaging installed	38
4.5	Isometric view of design one	39
4.6	Transparent view of design one	40
4.7	Back and side view of design one	40
4.8	Isometric view of design two	41
4.9	Transparent view of design two	42
4.10	Side, bottom and back view of design two	42
4.11	Isometric view of design three	43
4.12	Transparent view of design three	44
4.13	Side and back view of design three	44
4.14	Stress analysis on steel	45

4.15	Stress analysis on Aluminium	46
4.16	Temperature of design one and two	47
4.17	Heat flux of design one and two	48
4.18	Temperature of design three	49
4.19	Heat flux of design three	50
4.20	Battery packaging without drawer dimensions for design three	51
4.21	Battery packaging without cooling system dimension for design three	52
4.22	Dimension of exhaust pipe for design one, two and design three	53
4.23	Dimensions of suction pipe for design three	54
4.24	Dimension of suction fan pipe for design two	55
4.25	Design one proposed battery packaging sketching paper view	56
4.26	Design two proposed battery packaging sketching paper view	57
4.27	Design three proposed battery packaging sketching paper view	58

LIST OF SYMBOLS

P	Power
V	Voltage
I	Current

LIST OF ABBREVIATION

EV	Electric vehicle
FEA	Finite Element Analysis
ZEV	Zero Emission Vehicle

CHAPTER 1

INTRODUCTION

1.1 INTRODUCTION

Today, as human being transportation become an important role for getting a comfortable life. But, human not realize that next 50 years, global population will increase from 6 billion to 10 million and in order aspects, the number of vehicles will increase from 700 million to 2.5 billion [Husain, 1964]. If all these vehicles are propelled or get their sources energy by internal combustion engines (ICEs), then the fuel are out of source. The gloomy answer to these hard questions compel human to strive for sustainable road transportation for 21st century [Husain, 1964].

An electric vehicle (EV) is a vehicle with one or more electric motors for propulsion. This is also referred to as an electric drive vehicle. The motion may be provided either by wheels or propellers driven by rotary motors, or in the case of tracked vehicles, by linear motors. Unlike an internal combustion engine (ICE) that is tuned to specifically operate with a particular fuel such as gasoline or diesel, an electric drive vehicle needs electricity, which comes from sources such as batteries or a generator. This flexibility allows the drive train of the vehicle to remain the same, while the fuel source can be changed [Husain, 1964].

The idea of hybrid vehicles is not a recent development, early 1960s, several companies attempted to develop bipolar lead (acid batteries) for hybrid-electric vehicles [Husain, 1964]. Hybrid vehicles have the potential to increase fuel economy by using a primary engine operating at a constant power to supply average power requirements and a surge power unit for peak power demands and to recover braking energy. But until

now, there have no detailed system optimization analysis has been performed for hybrid electric vehicles.

Transportation becomes the major contributor to multiple global environmental problems such as greenhouse effect-gas emissions and urban pollution. The hybrid vehicle typically achieves greater fuel economy and lower emissions than conventional internal combustion engine vehicles (ICEVs), in terms of fewer emissions being generated. These savings are primarily achieved by four elements of a typical hybrid design. First, recapturing energy normally wasted during braking. Second, having significant battery storage capacity to store and reuse recaptured energy. Third, shutting down the gasoline or diesel engine during traffic stops or while coasting or other idle periods and last one is relying on both the gasoline (or diesel engine) and the electric motors for peak power needs resulting in a smaller gasoline or diesel engine sized more for average usage rather than peak power usage.

These features make a hybrid vehicle particularly efficient for city traffic where there are frequent stops, coasting and idling periods. In addition noise emissions are reduced, particularly at idling and low operating speeds, in comparison to conventional gasoline or diesel powered engine vehicles [M.H., Johns, 1996]. For continuous high speed highway use these features are much less useful in reducing emissions. Vehicles which have significant idle periods and only occasional needs of peak power like railroad switching locomotives or repeated lifting and lowering cycles like Rubber Tire Gantry's are also good candidates for hybrid systems resulting in potentially significant fuel and emission savings. The detail of electric vehicle packaging is discussed in the 1.2 Project background.

1.2 PROJECT BACKGROUND

This project is focus on battery packaging for electric vehicle. Some of the battery packaging is referring to the TESLA car and CHEVROLET VOLT that is the electric vehicle that already available in market.

1.3 PROJECT PROBLEM STATEMENT

The performance of the EV depends on the performance of its high-voltage battery pack. Battery temperatures influences are availability of discharge power (for startup and acceleration), energy, and charge acceptance during energy recovery from regenerative braking. These affect vehicle drivability. Temperature also affects the life of the battery and its replacements frequency. Therefore, batteries should operate within temperature range that is optimum for performance and life.

The optimum operating temperature range varies with battery type. The batteries that could be used for EV's are lead acid, nickel metal hybrid (NiMH), and lithium ion (Li-Ion). Today, Li-Ion is the leading choice because the batteries perform well, are safe, and are durable. Usually, the optimum battery temperature range (according to the battery manufacturer) is much narrower than the vehicle manufacturer's specified operating range. For example, the operating temperature for a lead acid battery should be 25°C–45°C, however, the specified vehicle operating range could be -30°C– 60°C. The goal of a thermal management system in an EV is to maintain an acceptable temperature range in a battery packaging with even temperature distribution. However, the pack thermal management system has to meet the vehicle manufacturer's requirement, it must compact, light weight, low cost, easily packaged, and compatible with location.

A thermal management system may use air for heating, cooling, liquid for cooling/heating, insulation, thermal storage such as phase change materials, or a combination of these methods. The material selection are also important in order to make the battery packaging are meet the requirement of the total heat. Therefore, EV must be thermally managed for hot and cold climates and seasons. They must be cooled (by air or liquid) to maintain an acceptable lifespan [Ahmad Pesaran, 2003].

1.4 PROJECT OBJECTIVES

- i. To design the battery packaging of Proton Iswara.

1.5 PROJECT SCOPE

- i. Measure the available space in Proton Iswara at the University Malaysia Pahang mechanical lab.
- ii. Design the battery packaging by using Solid works.
- iii. Identify the type of material selection suitable for battery packaging.
- iv. Identify the best design of a battery packaging.

1.6 OVERVIEW OF THE THESIS

This thesis is about battery packaging system for electric vehicle. In chapter 1, the project background, problem statement of battery packaging, objectives and project scopes will discuss. In chapter 2, overview of electric vehicle battery packaging are detail in the history of electric vehicle and also the type of the battery that will use in electric vehicle. The battery packagings that already exist in industry are also explained in chapter 2. The design criteria are explain in chapter 3, the available space of Proton Iswara car are, material selection for battery packaging and also cooling system type are discuss in chapter 3. For result and discussions of battery packaging is in chapter 4. This chapter 4 is concluding the type of connection between batteries, comparison of the design and also analysis performance. The last chapter is chapter 5, this chapter is conclusion for overall project and also recommendations for future research.