

High Surface Area Activated Carbon From Rice Husk As A High Performance Supercapacitor Electrode

Ellie Yi Lih Teo^a, Lingeswarran Muniandy^b, Eng-Poh Ng^b, Farook Adam^b, Abdul Rahman Mohamed^c,
Rajan Jose^a, Kwok Feng Chong^a

^a Faculty of Industrial Sciences & Technology, Universiti Malaysia Pahang, 26300 Gambang, Kuantan, Malaysia

^b School of Chemical Sciences, Universiti Sains Malaysia, 11800 Pulau Pinang, Malaysia

^c School of Chemical Engineering, Universiti Sains Malaysia, Engineering Campus, 14300 Nibong Tebal, Pulau Pinang, Malaysia

ABSTRACT

In this study, we report on the application of high surface area activated carbon (AC) derived from rice husks as a supercapacitor electrode. The prepared AC was free from Brønsted or Lewis acid sites, thus making the electrical double layer capacitance as the main charge storage mechanism. Three samples of AC with different surface areas were prepared at different activation temperatures and studied electrochemically using cyclic voltammetry, galvanostatic charge-discharge and electrochemical impedance spectroscopy. All AC samples exhibited good electrochemical performance as supercapacitor electrode. The maximum specific capacitance (147 F g^{-1}) was obtained by the AC sample (surface area of $2696 \text{ m}^2 \text{ g}^{-1}$) which was prepared at an activation temperature of $850 \text{ }^\circ\text{C}$. Detailed impedance studies revealed the low resistivity ($0.23 \text{ } \Omega$) of AC sample and the fast frequency response (0.11 s) of the supercapacitor electrode.

KEYWORDS: Biowaste; energy storage; supercapacitors; electrochemistry; activated carbon

DOI: [10.1016/j.electacta.2016.01.140](https://doi.org/10.1016/j.electacta.2016.01.140)