

Development of DEM–CFD Simulation of Combustion Flow in Incinerator with the Representative Particle Model

Kenya Kuwagi¹, Toshihiro Takami¹, Azri Bin Alias², Degang Rong³, Hiroshi Takeda³, Shinichiro Yanase⁴, Toshinori Kouchi⁴, Toru Hyakutake⁵, Kaoru Yokoyama⁶, Yoshiyuki Ohara⁶, Nobuo Takahashi⁶ and Noritake Sugitsue⁶

¹*Department of Mechanical Systems Engineering, Okayama University of Science, 1-1 Ridai-cho, Kita-ku, Okayama-shi, Okayama 700-0005, Japan*

²*Faculty of Mechanical Engineering, University Malaysia Pahang, Pekan Campus, 26600 Pahang, Malaysia*

³*R-flow Corporation Ltd., Takanashi Building, 1-10-45 Takasago, Soka-shi, Saitama 340-0015, Japan* ⁴*(graduate School of Natural Science and Technology, Okayama University, 3-1-1 Tsushima-Naka, Kita-ku, Okayama-shi, Okayama 700-8530, Japan*

⁵*(graduate School of Engineering, Yokohama National University, 79-5 Tokiwadai, Hodogaya-ku, Yokohama-shi, Kanagawa 240-8501, Japan*

⁶*Japan Atomic Energy Agency, 1550, Kagamino-cho, Tomata-gun, Okayama 708-0698, Japan*

Keywords: Incinerator, DEM–CFD Simulation, Combustion, Waste

ABSTRACT

A simulation code based on the discrete element method (DEM) and computational fluid dynamics (CFD) coupling model was developed to simulate the behavior of radioactive cesium in waste incinerators. The waste lump was represented by particles in the simulation. The energy equation for a mixed gas, diffusion equation for each gas component, as well as the energy, drying, pyrolysis, and combustion equations for each particle were solved in the simulation by adding a combustion model to the standard DEM–CFD coupling model. The particle size of the waste changed as drying, pyrolysis, and combustion progressed. At the end of the combustion process, particle waste became ash, and the number of ash particles was enormous. To avoid an excessive computational load due to the high particle number, a similar assembly model was adopted to reduce the particle number in the calculation. There was a good agreement between the simulation and experimental results for the temperature at the outlet of the furnace and the flue gas composition.