

**STRENGTH STABILIZATION OF PEAT SOIL  
USING  
ORDINARY PORTLAND CEMENT (OPC)**

**MARLENE INSIN ANAK JACK**

**B. ENG (HONS.) CIVIL ENGINEERING  
UNIVERSITI MALAYSIA PAHANG**

**UNIVERSITI MALAYSIA PAHANG**

**DECLARATION OF THESIS/ UNDERGRADUATE PROJECT PAPER AND COPYRIGHT**

Author's full name : MARLENE INSIN ANAK JACK  
Date of birth : 26<sup>th</sup> JANUARY 1993  
Title : STRENGTH STABILIZATION OF PEAT SOIL USING  
ORDINARY PORTLAND CEMENT (OPC)  
Academic Session : 2015/2016

I declare that this thesis is classified as:

- CONFIDENTIAL** (Contains confidential information under the Official Secret Act 1972)\*
- RESTRICTED** (Contains restricted information as specified by the organization where research was done)\*
- OPEN ACCESS** I agree that my thesis to be published as online open access (Full text)

I acknowledge that Universiti Malaysia Pahang reserve the right as follows:

1. The Thesis is the Property of University Malaysia Pahang
2. The Library of University Malaysia Pahang has the right to make copies for the purpose of research only.
3. The Library has the right to make copies of the thesis for academic exchange.

Certified By:

\_\_\_\_\_  
(Student's Signature)

930126 - 13 - 5172

New IC / Passport Number

Date : 20 JUNE 2016

\_\_\_\_\_  
(Signature of Supervisor)

MR. YOUVENTHARAN A/L DURAISAMY

Name of Supervisor

Date : 20 JUNE 2016

**NOTES:** \*If the thesis is CONFIDENTIAL or RESTRICTED, please attach with the letter from the organization with period and reasons for confidentiality or restriction.

“I hereby declare that I have read this project report and in my opinion, this project report is sufficient in terms of scope and quality for the award of the degree of Bachelor in Civil Engineering”

Signature : .....

Supervisor : MR. YOUVENTHARAN A/L DURAISAMY

Date : JUNE 2016

STRENGTH STABILIZATION OF PEAT SOIL USING  
ORDINARY PORTLAND CEMENT (OPC)

MARLENE INSIN ANAK JACK

A report submitted in partial fulfilment of the  
requirements for the award of the degree of  
B. Eng (Hons.) Civil Engineering

Faculty of Civil Engineering and Earth Resources  
UNIVERSITI MALAYSIA PAHANG

JUNE 2016

## DECLARATION

I declare that this thesis entitled “Strength Stabilization of Peat Soil Using Ordinary Portland Cement (OPC)” is the result of my own research as cited in the references. The thesis has not been accepted for any degree and is not concurrently submitted in candidature of any other degree.

Signature : .....

Supervisor : MARLENE INSIN ANAK JACK

Date : JUNE 2016

## TABLE OF CONTENTS

<b>CHAPTER</b>	<b>TITLE</b>	<b>PAGE</b>
	<b>STUDENT DECLARATION</b>	i
	<b>DEDICATION</b>	ii
	<b>ACKNOWLEDGEMENTS</b>	iii
	<b>ABSTRACT</b>	iv
	<b>ABSTRAK</b>	iv
	<b>TABLE OF CONTENTS</b>	vi
	<b>LIST OF TABLES</b>	ix
	<b>LIST OF FIGURES</b>	x
	<b>LIST OF SYMBOLS</b>	xi
	<b>LIST OF APPENDICES</b>	xii
<b>1</b>	<b>INTRODUCTION</b>	1
	1.1 Background of the Problem	1
	1.2 Statement of Problem	2
	1.3 Objectives and aims	3
	1.4 Scope of the Study	3
	1.5 Significance of the Study	4
<b>2</b>	<b>LITERATURE REVIEW</b>	5
	2.1 Introduction	5
	2.2 Classification of peat	7
	2.2.1 Types of peat	7
	2.2.2 Characteristic of peat soil	10
	2.2.2.1. Physical characteristic	10
	2.2.2.2. Chemical characteristic	11
	2.3 Shear strength	12

2.4	Types of soil stabilizer	13
2.4.1.	Ordinary Portland Cement (OPC)	13
2.4.2.	Fly ash	17
2.4.3.	Gypsum	18
2.4.4.	Lime	18
2.4.5.	Blast furnace slag	20
2.5	Shear strength result found with different types of stabilizer	22
2.5.1.	Ordinary Portland Cement (OPC) as a stabilizer and polypropylene fiber as additive	22
2.5.2.	Gypsum and fly ash	25
<b>3</b>	<b>RESEARCH METHODOLOGY</b>	<b>27</b>
3.1	Introduction	27
3.2	Project flowchart	29
3.3	Identification of peat	30
3.3.1.	Physical and chemical properties	30
3.3.2.	Classification of peat soil	30
3.4	Preparation of peat soil sample	31
3.5	Unconfined Compressive Strength (UCS) test	32
3.6	Curing procedure (Air Curing Technique)	33
3.7	Research planning and schedule	34
<b>4</b>	<b>RESULTS</b>	<b>36</b>
4.1	Physical and chemical properties	36
4.2	Shear strength obtained from Unconfined Compressive Strength	38
<b>5</b>	<b>CONCLUSIONS AND RECOMMENDATION</b>	<b>43</b>
5.1	Introduction	43
5.2	Conclusion	43
5.3	Recommendation	44

**REFERENCES**

45

**APPENDICES A – B**

47



**LIST OF TABLE**

<b>TABLE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
2.1	Organic soils and peat section of Malaysia Soil Classification System	8
2.2	Classification of peat soil from Von Post (Huat,2004)	9
2.3	General features of the main types of Portland Cement	15
3.1	Research planning and schedule (Gantt Chart)	35
4.1	Physical and chemical properties behavior of unstabilized peat	37
4.2	The summary of shear strength improved peat at 28 days.	42

## LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Effect of the addition of the line on plasticity properties of London Clay (Sherwood,1993)	20
2.2	Different percentages of fiber and cement mixed with peat soil versus percent strength increase of UCS after 90 days of curing	23
2.3	Curing time versus unconfined compressive strength values for the stabilized peat soil with different percent of ordinary Portland cement (15,30,50%) and 0.15% of polypropylene fibers	24
2.4	UCS test result for sample with respect to various percentage of gypsum added and curing period.	26
2.5	UCS test result for sample with respect to various percentage of fly ash added and curing period.	26
3.1	Site location at Inderasempurna Pekan, Pahang	28
3.2	Research flowchart	29
3.3	Fresh peat soil during Von Post degree of decomposition	30
3.5	The sample was collected at the depth of 0.3 to 0.5m depth	31
3.5	The peat soil was dried in the oven for at least for 24 hours	31
3.6	The mixture were placed inside the split mould	32
3.7	The Unconfined Compressive Strength machine	33
4.1	UCS test result for samples with respect to various of percentage of OPC added	39
4.2	UCS test result for samples with respect to period of curing	40

**LIST OF SYMBOLS**

$S_u$	Shear strength
$K_o$	Pressure coefficient
$q_u$	Unconfined Compressive Strength
$G_s$	Specific gravity
$e_o$	Initial void ratio
$E$	Strain
$\Sigma$	Stress

**LIST OF APPENDIXES**

<b>APPENDIX</b>	<b>TITLE</b>	<b>PAGE</b>
A	Soil sample preparation	47
B	Unconfined Compressive Strength test result	48

STRENGTH STABILIZATION OF PEAT SOIL USING  
ORDINARY PORTLAND CEMENT (OPC)

MARLENE INSIN ANAK JACK

A report submitted in partial fulfilment of the  
requirements for the award of the degree of  
B. Eng (Hons.) Civil Engineering

Faculty of Civil Engineering and Earth Resources  
UNIVERSITI MALAYSIA PAHANG

JUNE 2016

## **ABSTRACT**

This article describes a laboratory study on stabilizing peat soil using Ordinary Portland Cement (OPC) to improve its strength. Peat soil commonly occur as extremely soft, wet, unconsolidated surficial deposits that are the major parts of the wetland systems. These problematic soils are well known for its high compressibility and low in shear strength. Therefore this soil were stabilized in order to solve the major problem that always encountered by the civil engineer in Malaysia. Various percentages of OPC which is 4, 6, and 8% were added to peat soil at optimum moisture content and the sample was cured for 7, 14 and 28 days before conducting Unconfined Compressive Strength test. The Unconfined Compressive Strength test show that the strength of the peat soil will increase as the percentage of the stabilizer increases.

## **ABSTRAK**

Thesis ini adalah mengenai kajian makmal untuk menguatkan tanah gambut dengan menggunakan Portland Simen Biasa (PSB) bagi meningkatkan kekuatan tanah gambut. Pada kebiasaannya tanah gambut merupakan tanah yang sangat lembut, basah, dan selalu didapati di permukaan tanah tak terkukuh adalah merupakan bahagian terbesar di system kawasan 'wetland'. Tanah yang mempunyai banyak masalah ini telah distabilkan supaya dapat menyelesaikan masalah yang sering dihadapi oleh jurutera awam di Malaysia. Pelbagai peratusan PSB akan digunakan iaitu 4,6 dan 8% untuk dicampurkan ke dalam tanah gambut pada kandungan lembapan yang optimum dan sampel juga telah dimatangkan selama 7,14 dan 28 hari sebelum menjalankan eksperimen Kekuatan Mampatan Takterkurung. Eksperimen Kekuatan Mampatan Takterkurung akan menunjukkan kekuatan tanah gambut akan meningkat sekiranya peratusan penstabil juga meningkat.

## CHAPTER 1

### INTRODUCTION

#### 1.1 Background of the Problem

Soil may contain organic matters which are essential remains of plants. These soils called organic soil once their organic content exceeds 20% of their dry mass. Organic soils would turn be termed 'peat', once their organic content exceeds 75%. In Malaysia, the area that covered with peat soil is about 3 million hectares or 8% of the total land in Malaysia. Peat and organic soils were extremely soft and unconsolidated surficial deposits constituting the subsurface of wetland systems. The peat soil also can be found stratified in other surficial deposits in areas that have undergone paleo-environmental changes. General construction problems in this deposit were insufficient bearing capacity, excessive post construction settlement and instability on excavation and embankment forming.

Peat soil also well known to deform and fail under a light surcharge load and it was characterized with low shear strength. Generally any ground that subjected to additional loads which exceed its previous load condition or level, geotechnical requirements for design on that ground are to be established. These requirements included a set of standard laboratory tests and also some foundation design calculations in order to find the allowable bearing capacity.

Different approaches were used for the improvement of peat soil. Soil stabilization such as compaction and soil mixing with the addition of chemicals was



to modify the soil condition so that construction can be done easily without any risk. Most common way for soft or peat soil treatment was by excavating the soft or peat soil and replacing it with good granular or sandy soil but this way of soil treatment was not encouraged because of the uneconomical design. If the construction of the heavy loaded buildings was made on a soft peat soil layers, piled foundations can be used to transfer the loading to the rock. But if lightly loaded buildings or a road are to be constructed, it is not economical to construct the structures on a piled foundation. The method of pre-consolidation by preloading was the most widely used method by the engineers to improve the soil. But the one of the disadvantage of preloading method was it required a long period of time to done.

Soil stabilization was very important to strengthen the peat soil. Therefore, it was more economical to improve the strength and stiffness of the soil so that the structures can be built on top of soft soil. Soil stabilization by using chemical admixtures involves the treatment of the structures and fabric of the soil. The chemical reaction that occurs within the soil will results in changes in moisture content, shear strength, compressibility, pH values and other physical, chemical and engineering properties of the soil. The chemical stabilizer could accelerate the bonding in the soil but the bonding and the rate of the bonding depends on the type of stabilizer used.

## **1.2 Statement of Problem**

These problematic soils were well known for their high compressibility and low shear strength (Huat, 2004). Normally, the construction and buildings were avoided on these soils. Usually it was very hard to access to the peat soils as the water table was often at, near or above the ground surface. From the perspective of engineering, the choices to construct on this type of soil normally had been avoided due to its consolidation settlement.

Challenges faced by those responsible for construction on peat and organic soils include:

- Limited accessibility and difficult traffic ability
- Expectation of very large settlements over an extended time period

- Possibility of stability problems

As the peat soil was easily to deform and fail under a light surcharge load, and also commonly known low shear strength, low compressibility, and high water content. Thus, it was not suitable for construction area due to its consolidation settlement.

### **1.3 Objectives and aims**

Based on the high strength characteristic of peat in the evaluation of the soil when it applies with load, the objectives set for this study were as followed:

#### **Overall Objective**

This study was aimed to evaluate the strength of Pekan, Pahang Peat Soil which was stabilized with Ordinary Portland Cement (OPC) as an admixtures.

#### **Specific Aims**

1. To determine the physical and chemical behavior of unstabilized peat soil at Pekan.
2. To evaluate the strength and the effectiveness of the stabilizers (OPC) mixed with peat soil.

### **1.4 Scope of the Study**

This research was carried out according to the scope of study that was specified. The scope focuses on the effectiveness towards the peat soil used different percentages of OPC which were 4, 6 and 8%. The curing period used were different which were 7, 14 and 28 days. Several laboratory tests had been carried out to determine the physical and chemical properties of soil.

The Unconfined Compression Strength (UCS) method was used to test the strength of the peat soil with different amount of OPC. If the UCS value is increasing by adding the OPC to the soil there is effectiveness in increasing the soil strength and