ORIGINAL PAPER



Toughening effect of liquid natural rubber on the morphology and thermo-mechanical properties of the poly(lactic acid) ternary blend

Mohd Bijarimi¹ · Sahrim Ahmad² · A. K. M. Moshiul Alam^{1,3}

Received: 31 August 2016/Revised: 21 November 2016/Accepted: 16 December 2016/ Published online: 28 December 2016 © Springer-Verlag Berlin Heidelberg 2016

Abstract In this work, poly(lactic acid) (PLA) was melt blended with liquid natural rubber (LNR) and linear low-density polyethylene (LLDPE) to fabricate a PLA–LNR–LLDPE ternary blend. The torque rheology demonstrates the melt mixing behavior of PLA–LLDPE binary and PLA–LNR–LLDPE ternary blends. Mechanical properties of ternary blend illustrate the highest toughness as compared to neat PLA and PLA–LLDPE binary blend. Fracture morphology reveals the plastic deformation behavior in the ternary blend which is illustrated in TEM micrograph. The cold crystallization temperature of the ternary blend appears at a lower temperature as compared to the binary blend. The thermal stability of PLA is improved due to blending with LLDPE and LNR. The ternary blend exhibits greater storage modulus in the glassy state as well as in the rubbery state as compared to neat PLA and LLDPE.

Keywords Blend \cdot Mechanical properties \cdot Rheology \cdot Morphology \cdot Thermal properties

Mohd Bijarimi bijarimi@ump.edu.my

A. K. M. Moshiul Alam akmmalam@gmail.com

- ¹ Faculty of Chemical and Natural Resources Engineering, Universiti Malaysia Pahang, Gambang, 26300 Kuantan, Malaysia
- ² Faculty of Science and Technology, School of Applied Physics, Universiti Kebangsaan Malaysia, Bangi, Selangor, Malaysia
- ³ Institute of Radiation and Polymer Technology, Bangladesh Atomic Energy Commission, Dhaka, Bangladesh

outstanding enhancement of elongation at break and impact strength of the ternary blend. Therefore, the toughness of the ternary blend obviously improved which was the key aim of this work. Morphology of ternary blend revealed apparent compatibility of PLA and LLDPE in the presence of LNR compatibilizer. Besides, the polyolefin long chains inhibited the molecular motion of PLA in the binary blend as a consequence enhanced the cold crystallization temperature of blends. Short chain of LNR performed as a nucleating and plasticizing agent which influenced the mobility PLA molecules retrieving the cold crystallization temperature in the ternary blend. Polyolefin and LNR jointly enhanced the thermal stability of PLA blends as was observed from TGA and DTG thermograms. In DMA thermograms, the ternary blend illustrated the highest storage modulus and the lower δ peak temperature as compared to binary blend. So, it can be concluded that LNR played a key role in developing good interaction between PLA and LLDPE polyolefin besides enhancing the thermo-mechanical properties of the ternary blend.

Acknowledgements Authors would like to acknowledge Universiti Malaysia Pahang, Malaysia for providing financial support to project RDU140331.

References

- Zeng X, Wu B, Wu L, Hu J, Bu Z, Li B (2014) Poly(l-lactic acid)-block-poly(butylene succinate-cobutylene adipate) multiblock copolymers: from synthesis to thermo-mechanical properties. Ind Eng Chem Res 53(9):3550–3558
- Moshiul Alam AKM, Shubhra QTH (2015) Surface modified thin film from silk and gelatin for sustained drug release to heal wound. J Mater Chem B 3(31):6473–6479
- Moshiul Alam AKM, Beg MDH, Mina MF, Mamun AA, Bledzki AK (2014) Degradation and stability of green composites fabricated from oil palm empty fruit bunch fiber and poly lactic acid: effect of fiber length. J Compos Mater. doi:10.1177/0123456789123456
- Williams CK, Hillmyer MA (2008) Polymers from renewable resources: a perspective for a special issue of polymer reviews. Polym Rev 48:1–10
- Li J, Song Z, Gao L, Shan H (2016) Preparation of carbon nanotubes/polylactic acid nanocomposites using a non-covalent method. Polym Bull 73:2121–2128
- Alam AKMM, Beg MDH, Mina MF, Khan MR, Prasad DRM (2012) Structures and performances of simultaneous ultrasound and alkali treated oil palm empty fruit bunch fiber reinforced poly(lactic acid) composites. Compos A 43:1921–1929
- Moshiul Alam AKM, Mina MF, Beg MDH, Mamun AA, Bledzki AK, Shubhra QTH (2014) Thermomechanical and morphological properties of short natural fiber reinforced poly (lactic acid) biocomposite: effect of fiber treatment. Fibers Polym 15(6):1303–1309
- Ishida S, Nagasaki R, Chino K, Dong T, Inoue Y (2009) Toughening of poly(L-lactide) by melt blending with rubbers. J Appl Polym Sci 113:558–566
- Bitinis N, Verdejo R, Cassagnau P, Lopez-Manchado MA (2011) Structure and properties of polylactide/natural rubber blends. Mater Chem Phys 129(3):823–831
- 10. Bijarimi M, Ahmad S, Rasid R (2014) Mechanical, thermal and morphological properties of poly(lactic acid)/epoxidized natural rubber blends. J Elastomers Plast 46(4):338–354
- Dahlan HM, Khairul Zaman MD, Ibrahim A (2000) Liquid natural rubber (LNR) as a compatibilizer in NR/LLDPE blends. J Appl Polym Sci 78(10):1776–1782
- Dahlan HM, Khairul Zaman MD, Ibrahim A (2002) The morphology and thermal properties of liquid natural rubber (LNR)-compatibilized 60/40 NR/LLDPE blends. Polym Test 21(8):905–911
- Dahlan HM, Zaman MDK, Ibrahim A (2002) Liquid natural rubber (LNR) as a compatibiliser in NR/ LLDPE blends–II: the effects of electron-beam (EB) irradiation. Radiat Phys Chem 64(5–6):429–436

- Lee Hyun Jae, Won Jong Sung, Lim Sung Chan, Lee Seung Goo (2016) Preparation and characterization of the PVDF/LDPE thermoplastic composite having piezoelectric property. Polym Bull 73:2639–2647
- Yang K, Zhang T, Zhu C, Zhang P, Zhao S, Guo L (2016) The reinforcing mechanism study of carbon nanotube in the NR matrix. Polym Bull. doi:10.1007/s00289-016-1755-7
- Fischer EW, Sterzel HJ, Wegner G (1973) Investigation of the structure of solution grown crystals of lactide copolymers by means of chemical reaction. Colloid Polym Sci 251:980–990
- 17. Brandrup J, Immergut EH (1975) Polymer handbook V-16
- Moly KA, Radusch HJ, Androsh R, Bhagawan SS, Thomas S (2005) Nonisothermal crystallisation, melting behavior and wide angle X-ray scattering investigations on linear low density polyethylene (LLDPE)/ethylene vinyl acetate (EVA) blends: effects of compatibilisation and dynamic crosslinking. Eur Polym J 41:1410–1419
- Maity AK, Xavier SF (1999) Rheological properties of ethylene-propylene block copolymer and EPDM rubber blends using a torque rheometer. Eur Polym J 35:173–181
- Cheng B, Zhou C, Yu W, Sun X (2001) Evaluation of rheological parameters of polymer melts in torque rheometers. Polym Test 20:811–818
- Ahmad A, Mohd Dahlan Hj, Ibrahim A (2004) Mechanical properties of filled NR/LLDPE blends. Iran Polym J 13(3):173–178
- 22. Liu H, Song W, Chen F, Guo L, Zhang J (2011) Interaction of Microstructure and interfacial adhesion on impact performance of polylactide (PLA) ternary blends. Macromolecules 44:1513–1522
- Zhang H, Huang J, Yang L, Chen R, Zou W, Lin X, Qu J (2015) Preparation, characterization and properties of PLA/TiO₂ nanocomposites based on a novel vane extruder. RSC Adv. 5:4639–4647
- Shubhra QTH, Alam AKMM, Quaiyyum MA (2011) Mechanical properties of polypropylene composites: a review. J Thermoplast Compos Mater 26(3):362–391
- Calafel MI, Remiro PM, Cortázar MM, Calahorra ME (2010) Cold crystallization and multiple melting behavior of poly(L-lactide) in homogeneous and in multiphasic epoxy blends. Colloid Polym Sci 288:283–296
- Yuryev Y, Wood-Adams PJ (2010) Rheological properties of crystallizing polylactide: detection of induction time and modeling the evolving structure and properties. Polym Sci Polym Phys 48:812–822
- Visakh PM, Thomas S, Oksman K, Mathew AP (2012) Crosslinked natural rubber nanocomposites reinforced with cellulose whiskers isolated from bamboo waste: processing and mechanical/thermal properties. Compos A 43:735–741