

REFERENCES

- Abidin, I., Umar, M., & Yusof, M. (2000). Advantages and Applications of Eddy Current Thermography Testing for Comprehensive and Reliable Defect Assessment. *Proceedings of 18th World Conference on Nondestructive Testing*, 16–20.
- Acherjee, B., Kuar, A. S., Mitra, S., & Misra, D. (2012). Modeling and analysis of simultaneous laser transmission welding of polycarbonates using an FEM and RSM combined approach. *Optics and Laser Technology*, 44(4):995–1006.
- Adoko, A. C., & Wu, L. (2011). Fuzzy inference systems-based approaches in geotechnical engineering- a review. *Electronic Journal of Geotechnical Engineering*, 16:1543–1558.
- Aguila-Munoz, J., Espina-Hernandez, J. H., Perez-Benitez, J. a., Caleyó, F., & Hallen, J. M. (2013). Crack detection in steel using a GMR-based MFL probe with radial magnetization. *CONIELECOMP 2013, 23rd International Conference on Electronics, Communications and Computing*, 104–108.
- Ai, Q., Liu, C. X., Chen, X. R., He, P., & Wang, Y. (2010). Acoustic emission of fatigue crack in pressure pipe under cyclic pressure. In *Nuclear Engineering and Design*, 240,:3616–3620.
- Al-Sarkhi, A., & Hanratty, T. J. (2002). Effect of pipe diameter on the drop size in a horizontal annular gas-liquid flow. *International Journal of Multiphase Flow*, 28(10):1617–1629.
- Alper, M., Attenborough, K., Hart, R., Lane, S. J., Lashmore, D. S., Younes, C., & Schwarzacher, W. (1993). Giant magnetoresistance in electrodeposited superlattices. *Applied Physics Letters*, 63(15):2144.
- Amineh, R. K., Sadeghi, S. H. H., & Moini, R. (2003). Suppressing sensor lift-off effects on cracks signals in surface magnetic field measurement technique. *IEEE International Conference on Industrial Technology*, 360–363.
- Angani, C. S., Park, D. G., Kim, C. G., Leela, P., Kollu, P., & Cheong, Y. M. (2010). The Pulsed Eddy Current Differential Probe to Detect a Thickness Variation in an Insulated Stainless Steel. *Journal of Nondestructive Evaluation*, 29(4):248–252.
- Arjomandi, K., & Taheri, F. (2011). Stability and post-buckling response of sandwich pipes under hydrostatic external pressure. *International Journal of Pressure Vessels and Piping*, 88(4), 138–148.
- Arjun, V., Sasi, B., Chandra Rao, B. P., Mukhopadhyay, C. K., & Jayakumar, T. (2015). Optimisation of pulsed eddy current probe for detection of sub-surface defects in stainless steel plates. *Sensors and Actuators A: Physical*, 226: 69–75.
- Azizi, A. (2015). Investigating the controllable factors influencing the weight loss of

- grinding ball using SEM/EDX analysis and RSM model. *Engineering Science and Technology, an International Journal*, 18(2):278–285.
- Baibich, M. N., Broto, J. M., Fert, A., & Van Dau, F. N. (1988). Giant magnetoresistance of (001) Fe/(001) Cr magnetic superlattices. *Physical Review Letters*, 61(21):2472–2475.
- Bernieri, A., Betta, G., Member, S., Ferrigno, L., & Laracca, M. (2004). An Automated Self-Calibrated Instrument for Nondestructive Testing on Conductive Materials, 53(4): 955–962.
- Bernieri, A., Betta, G., Member, S., Ferrigno, L., & Laracca, M. (2013). Improving Performance of GMR Sensors. *IEEE Sensors Journal*, 13(11), 4513-4521.
- Bhatti, M. S., Kapoor, D., Kalia, R. K., Reddy, A. S., & Thukral, A. K. (2011). RSM and ANN modeling for electrocoagulation of copper from simulated wastewater: Multi objective optimization using genetic algorithm approach. *Desalination*, 274(1–3):74–80.
- Biju, N., Ganesan, N., Krishnamurthy, C. V, & Balasubramaniam, K. (2013). Optimum frequency variations with coil geometry and defects in tone burst eddy current thermography (TBET). *Insight: Non-Destructive Testing and Condition Monitoring*, 55(9), 504–509.
- Birring, A. S. (1999). Selection of NDT Techniques for Inspection of Heat Exchanger Tubing Conventional Eddy Current. In *ASNT International Conference on Petroleum Industry Inspection*, 6:1–14.
- Bouchalkha, A., Hamad, M. S., Al-Beloushi, K., Al-Qayedi, M., & Al-Hammadi, K. (2011). Design of an oil pipe inner surface inspection system. *2011 IEEE GCC Conference and Exhibition (GCC)*, 29–32.
- Boyacioglu, M. A., & Avci, D. (2010). An adaptive network-based fuzzy inference system (ANFIS) for the prediction of stock market return: The case of the Istanbul stock exchange. *Expert Systems with Applications*, 37(12):7908–7912.
- Bubar, B. G. (2011). Welding and NDT. In *Pipeline Planning and Construction Field Manual* (pp. 357–378).
- Cacciola, M., Megali, G., Pellicanó, D., & Morabito, F. C. (2011). A GMR–ECT based embedded solution for applications on PCB inspections. *Sensors and Actuators A: Physical*, 167(1):25–33.
- Cardoso, F. A., Rosado, L. S., Franco, F., Ferreira, R., Paz, E., Cardoso, S. F., ... Freitas, P. J. P. (2014). Improved magnetic tunnel junctions design for the detection of superficial defects by eddy currents testing. *IEEE Transactions on Magnetics*, 50(11), 2–5.
- Chao, W., Ya, Z., & Peng, G. (2013). GMR Based Eddy Current System for Defect Detection. *International Conference on Electronic Measurement & Instruments*

- (*ICEMI*), 2:1052-1056.
- Chen, B., Matthews, P. C., & Tavner, P. J. (2013). Wind turbine pitch faults prognosis using a-priori knowledge-based ANFIS. *Expert Systems with Applications*, 40(17):6863–6876.
- Chen, D.-W. C. D.-W., & Zhang, J.-P. Z. J.-P. (2005). Time series prediction based on ensemble ANFIS. *2005 International Conference on Machine Learning and Cybernetics*, 6:18–21.
- Chen, X., & Lei, Y. (2014a). Excitation current waveform for eddy current testing on the thickness of ferromagnetic plates. *NDT & E International*, 66:28–33.
- Chen, X., & Lei, Y. (2014b). Time-domain analytical solutions to pulsed eddy current field excited by a probe coil outside a conducting ferromagnetic pipe. *NDT & E International*, 68: 22–27.
- Chen, X., & Lei, Y. (2015). Electrical conductivity measurement of ferromagnetic metallic materials using pulsed eddy current method. *NDT & E International*, 75:33–38.
- Cordón, O. (2011). A historical review of evolutionary learning methods for Mamdani-type fuzzy rule-based systems: Designing interpretable genetic fuzzy systems. *International Journal of Approximate Reasoning*, 52(6), 894-913.
- Current, A. E., & Principle, T. (2012). Eddy Current Crack Extension Direction Evaluation based on Neural Network. *IEEE Sensors*, 1-4.
- Daughton, J., Brown, J., Chen, E., Beech, R., Pohm, a., & Kude, W. (1994). Magnetic field sensors using GMR multilayer. *IEEE Transactions on Magnetics*, 30(6):4608–4610.
- Davoust, M.-È., Le Brusquet, L., & Fleury, G. (2010). Robust Estimation of Hidden Corrosion Parameters Using an Eddy Current Technique. *Journal of Nondestructive Evaluation*, 29(3):155–167.
- Dieny, B., Speriosu, V. S., & Metin, S. (1991). Thermal variation of the magnetoresistance of soft spin-valve multilayers. *Europhys. Lett.*, 15, 227.
- Diercks, D. (1996). Steam generator tube integrity program. *Nuclear Engineering and Design*, 165(1–2): 143–149.
- Dogaru, T., & Smith, S. T. (2001). Giant magnetoresistance-based eddy-current sensor. *IEEE Transactions on Magnetics*, 37(5): 3831–3838.
- Du, W., Dutt, A., & Scallion, K. (2010). Design of a GMR sensor array system for robotic pipe inspection. *IEEE Sensors*, 2551–2554.
- Edalati, K., Rastkhah, N., Kermani, A., Seiedi, M., & Movafeghi, A. (2006). The use of radiography for thickness measurement and corrosion monitoring in pipes.

- International Journal of Pressure Vessels and Piping*, 83(10):736–741.
- Elshafiey, I., & Mohra, A. (2007). Evaluation Of Printed Circuit Board. *Journal of Circuits, Systems, and Computers*, 16(6): 847–857.
- Enokizono, M., Todaka, T., & Akita, M. (1993). Rotational Magnetic Flux Sensor with Neural Network for Non-destructive Testing, 29(6):3195–3197.
- Expert, D. (2005). Multifactor RSM Tutorial (Part 1 – The Basics) Response Surface Design and Analysis. *Design Expert 9: User's Guide*, 1–53.
- Fan, M., Huang, P., Ye, B., Hou, D., Zhang, G., & Zhou, Z. (2009). Analytical modeling for transient probe response in pulsed eddy current testing. *NDT and E International*, 42(5):376–383.
- Foong, K. C., Chee, C. T., & Wei, L. S. (2009). Adaptive network fuzzy inference system (ANFIS) handoff algorithm. In *Proceedings - 2009 International Conference on Future Computer and Communication*, 195–198.
- Freitas, P. P., Silva, F., Oliveira, N. J., Melo, L. V., Costa, L., & Almeida, N. (2000). Spin valve sensors. *Sensors and Actuators, A: Physical*, 81(1):2–8.
- Fukutomi, H., Takagi, T., & Nishikawa, M. (2001). Remote field eddy current technique applied to non-magnetic steam generator tubes. *NDT and E International*, 34:17–23.
- Gao, P., Wang, C., Li, Y., Li, F., & Yan, Y. (2014). Defect Evaluation Using the Phase Information of an EC-GMR Sensor. In *IEEE International Instrumentation and Measurement Technology Conference*, 25-29.
- García-Martín, J., Gómez-Gil, J., & Vázquez-Sánchez, E. (2011). Non-destructive techniques based on eddy current testing. *Sensors (Basel, Switzerland)*, 11(3): 2525–65.
- George, J., Pereira, L., Barthélémy, A., Petroff, F., Steren, L., Duvail, J., ... Schroeder, P. (1994). Inverse spin-valve-type magnetoresistance in spin engineered multilayered structures. *Physical Review Letters*, 72(3):408–411.
- Ghafari, E., Costa, H., & Júlio, E. (2014). RSM-based model to predict the performance of self-compacting UHPC reinforced with hybrid steel micro-fibers. *Construction and Building Materials*, 66:375–383.
- Ghafari, S., Aziz, H. A., Isa, M. H., & Zinatizadeh, A. A. (2009). Application of response surface methodology (RSM) to optimize coagulation-flocculation treatment of leachate using poly-aluminum chloride (PAC) and alum. *Journal of Hazardous Materials*, 163(2–3): 650–656.
- Ghoni, R., Dollah, M., Sulaiman, A., & Ibrahim, F. M. (2014). Defect Characterization Based on Eddy Current Technique : Technical Review. *Advances in Mechanical Engineering*, 6: 182496.

- Gotoh, Y., Matsuoka, A., & Takahashi, N. (2011). Electromagnetic Inspection Technique of Thickness of Nickel-Layer on Steel Plate Without Influence of Lift-Off Between Steel and Inspection Probe. *IEEE Transactions on Magnetics*, 47(5):950–953.
- Grimberg, R., Savin, a., Radu, E., & Chifan, S. M. (2000). Eddy current sensor for non-destructive evaluation of metallic wires, bars and pipes. *Sensors and Actuators A: Physical*, 81(1–3):224–226.
- Guillaume, S. (2001). Designing fuzzy inference systems from data: An interpretability-oriented review. *IEEE Transactions on Fuzzy Systems*, 9(3): 426–443.
- Güler, I., & Übeyli, E. D. (2005). Adaptive neuro-fuzzy inference system for classification of EEG signals using wavelet coefficients. *Journal of Neuroscience Methods*, 148(2): 113–121.
- Gunawan, E. R., Basri, M., Rahman, M. B. A., Salleh, A. B., & Rahman, R. N. Z. A. (2005). Study on response surface methodology (RSM) of lipase-catalyzed synthesis of palm-based wax ester. *Enzyme and Microbial Technology*, 37(7):739–744.
- Hamia, R., Cordier, C., & Dolabdjian, C. (2014). NDT & E International Eddy-current non-destructive testing system for the determination of crack orientation. *NDT and E International*, 61:24–28.
- Hamzaoui, A. H., Jamoussi, B., & M'nif, A. (2008). Lithium recovery from highly concentrated solutions: Response surface methodology (RSM) process parameters optimization. *Hydrometallurgy*, 90(1):1–7.
- He, Y., Pan, M., Luo, F., & Tian, G. (2011a). Pulsed eddy current imaging and frequency spectrum analysis for hidden defect nondestructive testing and evaluation. *NDT & E International*, 44(4):344–352.
- He, Y., Pan, M., Luo, F., & Tian, G. (2011b). Reduction of Lift-Off Effects in Pulsed Eddy Current for Defect Classification. *IEEE Transactions on Magnetics*, 47(12): 4753–4760.
- Hellier, C. J. (2012). *Hanbook of nondestructive evaluation*. United States of America.
- Hewidy, M. S., El-Taweel, T. A., & El-Safty, M. F. (2005). Modelling the machining parameters of wire electrical discharge machining of Inconel 601 using RSM. *Journal of Materials Processing Technology*, 169(2):328–336.
- Horan, P., Underhill, P. R., & Krause, T. W. (2013). Pulsed eddy current detection of cracks in F/A-18 inner wing spar without wing skin removal using Modified Principal Component Analysis. *NDT & E International*, 55: 21–27.
- Hossain, A., Pirkle, H., & Parker, R. (1996). Design and fabrication of GMR multilayers with enhanced thermal stability, 156: 303–305.

- Huang, C. (2014). Probe Lift-off Compensation Method for Pulsed Eddy Current Thickness Measurement. *3rd Asia-Pacific Conference on Antennas and Propagation*, 937–939.
- Huang, H., Sakurai, N., Takagi, T., & Uchimoto, T. (2003). Design of an eddy-current array probe for crack sizing in steam generator tubes. *NDT and E International*, 36(7), 515–522.
- Huo, S., Wang, C., Cheng, S., & Song, X. (2011). Impedance analyzing for planar eddy current probe array. *International Conference on Information Science and Technology*, 995–999.
- Jang, J.-S. R. (1996). Input selection for ANFIS learning. *Proceedings of IEEE 5th International Fuzzy Systems*, 2:1493–1499.
- Jarvis, R., Cawley, P., & Nagy, P. B. (2016). Current deflection NDE for the inspection and monitoring of pipes. *NDT and E International*, 81, 46–59.
- Jedlicska, I., Weiss, R., & Weigel, R. (2008). Increasing the measurement accuracy of GMR current sensors through hysteresis modeling. *IEEE International Symposium on Industrial Electronics*, 884–889.
- Jiang, H., Kwong, C. K., Law, M. C., & Ip, W. H. (2013). Development of customer satisfaction models for affective design using rough set and ANFIS approaches. In *Procedia Computer Science*, 22:104–112.
- Jogschies, L., Klaas, D., Kruppe, R., Rittinger, J., Taptimthong, P., Wienecke, A., ... Wurz, M. (2015). Recent Developments of Magnetoresistive Sensors for Industrial Applications. *Sensors*, 15(11):28665–28689.
- Jun, J., & Lee, J. (2009). Nondestructive evaluation of a crack on austenitic stainless steel using a sheet type induced current and a Hall sensor array. *Journal of Mechanical Science and Technology*, 22(9):1684–1691.
- Junior, F. R. L., Osiro, L., & Carpinetti, L. C. R. (2013). A fuzzy inference and categorization approach for supplier selection using compensatory and non-compensatory decision rules. *Applied Soft Computing Journal*, 13(10):4133–4147.
- Junjun, X., Naiguang, L., Udpa, L., & Udpa, S. S. (2011). Nondestructive Inspection Using Rotating Magnetic Field Eddy-Current Probe. *IEEE Transactions on Magnetics*, 47(5):1070–1073.
- Kaur, A., & Kaur, A. (2012). Comparison of Mamdani-Type and Sugeno-Type Fuzzy Inference Systems for Air Conditioning System. *International Journal of Soft Computing & Engineering*, 2(2):323–325.
- Khuri, A. I., & Mukhopadhyay, S. (2010). Response surface methodology. *Wiley Interdisciplinary Reviews: Computational Statistics*, 2(2):128–149.
- Kim, J., Yang, G., Udpa, L., & Udpa, S. (2010). Classification of pulsed eddy current

- GMR data on aircraft structures. *NDT & E International*, 43(2):141–144.
- Kim, Y.-J., & Lee, S.-S. (2012). Eddy current probes of inclined coils for increased detectability of circumferential cracks in tubing. *NDT & E International*, 49:77–82.
- Kools, J. C. S. (1996). Exchange-biased spin-valves for magnetic storage. *IEEE Transactions on Magnetics*, 32(4 PART 2):3165–3184.
- Koshy, C. P., Rajendrakumar, P. K., & Thottackkad, M. V. (2015). Evaluation of the tribological and thermo-physical properties of coconut oil added with MoS₂ nanoparticles at elevated temperatures. *Wear*, 330–331, 288–308. <http://doi.org/10.1016/j.wear.2014.12.044>
- Král, J., & Smid, R. (2011). Thickness Measurement Using Transient Eddy Current Techniques. *Instrumentation and Measurement Technology Conference (I2MTC)*, 1-6.
- Kral, J., Smid, R., Ramos, H. M. G., & Ribeiro, a. L. (2013). The lift-off effect in Eddy currents on thickness modeling and measurement. *IEEE Transactions on Instrumentation and Measurement*, 62(7):2043–2049.
- Krampfner, Y.D.; Johnson, D.D. (1990). Flexible substrate eddy current coil arrays. *Review of Progress in Quantitative Nondestructive Evaluation*, 7, 471-478.
- Kuhnt, S., & Rudak, N. (2013). Simultaneous Optimization of Multiple Responses with the R Package JOP. *Journal of Statistical Software*, 54(9), 1-23.
- Le, M., Kim, J., Sik Do, H., & Lee, J. (2014). 2-D vector field visualization of corrosion in a small-bore piping system using bobbin-type integrated Hall and GMR sensors arrays. *2014 IEEE Sensors Applications Symposium (SAS)*,38–41.
- Lee, J., Jun, J., Kim, J., Choi, H., & Le, M. (2012). Bobbin-Type Solid-State Hall Sensor Array With High Spatial Resolution for Cracks Inspection in Small-Bore Piping Systems. *IEEE Transactions on Magnetics*, 48(11): 3704–3707.
- Lei, N., Udpa, L., Udpa, S., Zhiwei, Z., & Zeng, Z. (2010). Rotating field eddy current (RoFEC)-probe for steam generator inspection. *International Journal of Applied Electromagnetics & Mechanics*, 32(3/4):1279–1285.
- Lenssen, K. M. H., Adelerhof, D. J., Gassen, H. J., Kuiper, a. E. T., Somers, G. H. J., & Van Zon, J. B. a D. (2000). Robust giant magnetoresistance sensors. *Sensors and Actuators, A: Physical*, 85:1–8.
- Lenth, R. V. (2012). Response-surface methods in R , using RSM. *Journal of Statistical Software*, 32(7): 1–17.
- Li, D. Q., Jia, X., Wei, Z., & Liu, Z. Y. (2012). Box-Behnken experimental design for investigation of microwave-assisted extracted sugar beet pulp pectin. *Carbohydrate Polymers*, 88(1):342–346.

- Lopes Ribeiro, a., Ramos, H. G., & Couto Arez, J. (2012). Liftoff insensitive thickness measurement of aluminum plates using harmonic eddy current excitation and a GMR sensor. *Measurement*, 45(9):2246–2253.
- Lopez, L. a N. M., Ting, D. K. S., & Upadhyaya, B. R. (2008). Removing Eddy-Current probe wobble noise from steam generator tubes testing using Wavelet Transform. *Progress in Nuclear Energy*, 50(7):828–835.
- Lu, J., Huang, S., Pan, K., Qian, Z., & Chen, N. (2012). Development of characteristic test system for GMR sensor. *8th IEEE International Symposium on Instrumentation and Control Technology (ISICT) Proceedings*, 20–23.
- Lu, T., Liu, S. M., & Attinger, D. (2013). Large-eddy simulations of structure effects of an upstream elbow main pipe on hot and cold fluids mixing in a vertical tee junction. *Annals of Nuclear Energy*, 60, 420–431.
- Mahmoodi, N. M., Soltani-Gordefaramarzi, S., & Sadeghi-Kiakhani, M. (2013). Dye removal using modified copper ferrite nanoparticle and RSM analysis. *Environmental Monitoring and Assessment*, 185(12):10235–10248.
- Maji, K., & Pratihari, D. K. (2010). Forward and reverse mappings of electrical discharge machining process using adaptive network-based fuzzy inference system. *Expert Systems with Applications*, 37(12): 8566–8574.
- Mook, G., Hesse, O., & Uchanin, V. (2007). Typical Depths of penetration. *Materialpruefung/Materials Testing*, 49(5):258–264.
- Morris, A. S., & Langari, R. (2012). *Measurement and instrumentation : theory and application*. US Patent 4,039,260.
- Mott, N. F. (1936). The Electrical Conductivity of Transition Metals. *Proceedings of the Royal Society of London Series A Mathematical and Physical Sciences*, 153(880):699–717.
- Myers, R., Khuri, A., & Vining, G. (1992). Response surface alternatives to the Taguchi robust parameter design approach. *The American Statistician*, 46(2):131–139.
- Nestleroth, J. B. (2006). Pipeline in-line inspection - Challenges to NDT. *Insight: Non-Destructive Testing and Condition Monitoring*, 48(9), 524-524.
- Nogués, J., & Schuller, I. K. (1999). Exchange bias. *Journal of Magnetism and Magnetic Materials*, 192(2):203–232.
- Nolting, F., Scholl, a, Stohr, J., Seo, J., Fompeyrine, J., Siegwart, H., Padmore, H. (2000). Direct observation of the alignment of ferromagnetic spins by antiferromagnetic spins. *Nature*, 405:767–9.
- Oka, M., & Enokizono, M. (1996). A detection of backside crack using rotational magnetic flux sensor with search coils. *IEEE Transactions on Magnetics*, 32(5 PART 2):4968–4970.

- Park, D.-G., Angani, C. S., Rao, B. P. C., Vértesy, G., Lee, D.-H., & Kim, K.-H. (2013). Detection of the Subsurface Cracks in a Stainless Steel Plate Using Pulsed Eddy Current. *Journal of Nondestructive Evaluation*, 32(4): 350–353.
- Parkin, S. S. P. (1995). Giant Magnetoresistance in Magnetic Nanostructures. *Annual Review of Materials Science*, 25(1): 357–388.
- Parkin, S. S. P., More, N., & Roche, K. P. (1990). Oscillations in Exchange Coupling and Magnetoresistance in Metallic Superlattice Structures: Co/Ru, Co/Cr, Fe/Cr. *Physical Review Letters*, 64(19): 2304–2307.
- Pasadas, D. J., Ribeiro, A. L., Rocha, T. J., & Ramos, H. G. (2014). Open Crack Depth Evaluation Using Eddy Current Methods and GMR Detection. *Metrology for Aerospace (MetroAeroSpace)*, 117–121.
- Pasadas, D. J., Ribeiro, A. L., Rocha, T. J., & Ramos, H. M. G. (2014). Remote field eddy current tube inspection using giant magneto-resistance sensors. *International Journal of Industrial Electronics and Drives* 12(3):167–173.
- Pasadas, D., Rocha, T. J., Ramos, H. G., & Ribeiro, a. L. (2012). Evaluation of portable ECT instruments with positioning capability. *Measurement*, 45(3): 393–404.
- Pelkner, M., Neubauer, A., Reimund, V., Kreutzbruck, M., & Schütze, A. (2012). Routes for GMR-Sensor Design in Non-Destructive Testing. *Sensors*, 12(12): 12169–12183.
- Peluso, C. B. G., Iorio, M. V. A. De, & Penta, F. (2009). Detection of Magnetomechanical Effect in Structural Steel Using SQUIDs and Flux-gate Sensors. *Journal of superconductivity and novel magnetism*, 22(8): 833–839.
- Petit, F., Juraszek, J., Youssef, J. Ben, Teillet, J., Dekadjevi, D. T., & Gall, H. Le. (2005). Effect of annealing on the structural and magnetic properties of giant magnetostrictive multilayers. *Journal of Magnetism and Magnetic Materials*, 290–291 PA, 839–842.
- Poon, T. Y., Tse, N. C. F., & Lau, R. W. H. (2013). Extending the GMR current measurement range with a counteracting magnetic field. *Sensors (Basel, Switzerland)*, 13(6):8042–59.
- Porto, R. W., Brusamarello, V. J., & Azambuja, R. (2013). Design and Analysis of a GMR Eddy Current probe for NDT. *Seventh International Conference on Sensing Technology (ICST)*, 424-429.
- Porwal, A., Carranza, E. J. M., & Hale, M. (2004). A hybrid neuro-fuzzy model for mineral potential mapping. *Mathematical Geology*, 36(7):803-826.
- Postolache, O. (2012). Uniform Eddy Current Probe based on GMR Sensor Array and Image Processing for NDT. *IEEE International Instrumentation and Measurement Technology Conference (I2MTC)*, 458-463.

- Postolache, O., Lopes, A., & Ramos, H. G. (2013). GMR array uniform eddy current probe for defect detection in conductive specimens. *Measurement*, 46(10):4369–4378.
- Postolache, O., Ramos, H. G., & Ribeiro, A. L. (2008). Characterization of Defects in Aluminum Plates Using GMR Probes and Neural Network Signal Processing. *XVI-IMEKO TC4 Symposium, Florence-Italy*.
- Postolache, O., Ramos, H. G., & Ribeiro, A. L. (2011). Computer Standards & Interfaces Detection and characterization of defects using GMR probes and artificial neural networks. *Computer Standards & Interfaces*, 33(2):191–200.
- Prinz, G. a. (1998). Magnetolectronics. *Science*, 282:1660–1663.
- Pu, J., Moore, P. R., & Wong, C. B. (2000). Smart components-based servo pneumatic actuation systems. *Microprocessors and Microsystems*, 24(2):113–119.
- Qiu, Z. C., Wang, B., Zhang, X. M., & Han, J. Da. (2013). Direct adaptive fuzzy control of a translating piezoelectric flexible manipulator driven by a pneumatic rodless cylinder. *Mechanical Systems and Signal Processing*, 36(2):290–316.
- Ramírez, E., Espina, J. H., Pérez, J. A., Caleyó, F., & Hallen, J. M. (2015). Some Particularities of EC Crack Detection in Aluminum Using an Asymmetrical GMR-Coil Configuration. *IEEE Latin America Transactions*, 13(5):1331–1339.
- Ramos, H. G., Ribeiro, A. L., Alegria, F., Postolache, O., & Diagram, A. B. (2006). Virtual Instrument to Detect Defects in Conductive Materials. *7th Conference on Telecommunications*, 137-140.
- Ramos, H. G., Rocha, T., Král, J., Pasadas, D., & Ribeiro, A. L. (2014). An SVM approach with electromagnetic methods to assess metal plate thickness. *Measurement*, 54:201–206.
- Ramos, H. G., Rocha, T., Ribeiro, A. L., & Pasadas, D. (2014). GMR Versus Differential Coils in Velocity Induced Eddy Current Testing. *Proceedings IEEE International Instrumentation and Measurement Technology Conference*, 915-918.
- Ribeiro, a. L., Ramos, H. G., Pasadas, D. J., & Rocha, T. J. (2012). Current around a crack in an aluminum plate under nondestructive evaluation inspection. *2012 IEEE International Instrumentation and Measurement Technology Conference Proceedings*, 1635–1639.
- Rifai, D., Abdalla, A., Ali, K., & Razali, R. (2016). Giant Magnetoresistance Sensors: A Review on Structures and Non-Destructive Eddy Current Testing Applications. *Sensors*, 16(3): 298.
- Rocha, T. J., Ramos, H. G., Lopes Ribeiro, a., & Pasadas, D. J. (2015). Magnetic sensors assessment in velocity induced eddy current testing. *Sensors and Actuators A: Physical*, 228:55–61.

- Rocha, T. J., Ramos, H. G., Lopes Ribeiro, a., Pasadas, D. J., & Angani, C. S. (2015). Studies to optimize the probe response for velocity induced eddy current testing in aluminium. *Measurement*, 67:108–115.
- Romano, D., Varetto, M., & Vicario, G. (2004). Multiresponse robust design: a general framework based on combined array. *Journal of Quality Technology*, 36(1), 27.
- Rosado, L. S., Cardoso, F. A., Cardoso, S., Ramos, P. M., Freitas, P. P., & Piedade, M. (2014). Sensors and Actuators A: Physical Eddy currents testing probe with magneto-resistive sensors and differential measurement. *Sensors & Actuators: A. Physical*, 212:58–67.
- Sabri, N., Aljunid, S. A., Salim, M. S., Badlishah, R. B., Kamaruddin, R., & Abd Malek, M. F. (2013). Fuzzy inference system: Short review and design. *International Review of Automatic Control*, 6(4): 441–449.
- Safizadeh, S., & Hasanian, M. (2011). Gas Pipeline Corrosion Mapping Using Pulsed Eddy Current Technique. *International Journal of Advanced Design and Manufacturing Technology*, 5(1):11–19.
- Sharma, N., Khanna, R., & Gupta, R. (2013). Multi quality characteristics of WEDM process parameters with RSM. In *Procedia Engineering* ,64:710–719.
- Sharma, S., Malik, A., & Satya, S. (2009). Application of response surface methodology (RSM) for optimization of nutrient supplementation for Cr (VI) removal by *Aspergillus lentulus* AML05. *Journal of Hazardous Materials*, 164(2–3): 1198–1204.
- Singh, W. S., Rao, B. P. C., Thirunavukkarasu, S., & Jayakumar, T. (2012). Flexible GMR Sensor Array for Magnetic Flux Leakage Testing of Steel Track Ropes. *Journal of Sensors*, 2012.
- Sinha, K., Saha, P. Das, & Datta, S. (2012). Extraction of natural dye from petals of Flame of forest (*Butea monosperma*) flower: Process optimization using response surface methodology (RSM). *Dyes and Pigments*, 94(2): 212–216.
- Siritaratiwat, A., Hill, E. ., Stutt, I., Fallon, J. ., & Grundy, P. . (2000). Annealing effects on GMR multilayer films. *Sensors and Actuators A: Physical*, 81(1–3): 40–43.
- Smetana, M., & Strapacova, T. (2013). Detection capabilities evaluation of the advanced sensor types in Eddy Current Testing, (3): 247–249.
- Sued, M. K., Pons, D., Lavroff, J., & Wong, E. H. (2014). Design features for bobbin friction stir welding tools: Development of a conceptual model linking the underlying physics to the production process. *Materials & Design*, 54: 632–643.
- Sullivan, S. P., Cecco, V. S., Obrutsky, L., & Lakhan, R. (1997). Validating Eddy Current Array Probes for Inspecting Steam Generator Tubes. *NDTnet*, 3:29-35.

- Sundararaghavan, V., & Balasubramaniam, K. (2005). A multi-frequency eddy current inversion method for characterizing conductivity gradients on water jet peened components. *NDT & E International*, 38(7):541-547.
- Tamburrino, a., Udpa, L., & Udpa, S. S. (2010). Pulsed Eddy-Current Based Giant Magnetoresistive System for the Inspection of Aircraft Structures. *IEEE Transactions on Magnetics*, 46(3): 910–917.
- Tavana, M., Azizi, F., Azizi, F., & Behzadian, M. (2013). A fuzzy inference system with application to player selection and team formation in multi-player sports. *Sport Management Review*, 16(1): 97–110.
- Theodoulidis, T., & Bowler, J. R. (2010). Interaction of an eddy-current coil with a right-angled conductive wedge. *IEEE Transactions on Magnetics*, 46(4): 1034–1042.
- Thirunavukkarasu, S., Rao, B. P. C., Jayakumar, T., & Raj, B. (2011). Techniques for processing remote field eddy current signals from bend regions of steam generator tubes of prototype fast breeder reactor. *Annals of Nuclear Energy*, 38(4): 817–824.
- Tian, G. Y., Li, Y., & Mandache, C. (2009). Study of lift-off invariance for pulsed eddy-current signals. *IEEE Transactions on Magnetics*, 45(1): 184–191.
- Tian, G. Y., & Sophian, A. (2005a). Defect classification using a new feature for pulsed eddy current sensors. *NDT & E International*, 38(1):77–82.
- Tian, G. Y., & Sophian, A. (2005b). Reduction of Lift-Off Effects for Pulsed Eddy Current NDT. *NDT and E International*, 38(4): 319–324.
- Translation, I., On, J., & In, M. (1992). Non-Destructive Testing with Magnetic Sensor Using Rotational Magnetic Flux. *IEEE translation journal on magnetics in Japan*, 7(3):241-249.
- Tsymbal, E. Y., & Pettifor, D. G. (2001). Perspectives of giant magnetoresistance. *Solid State Physics - Advances in Research and Applications*, 56(3): 113–237.
- Type, T. M., Mbt, I., & Briggs, I. (1985). Myers-Briggs Type Indicator (MBTI). *New York*, 60, 2–5.
- Vacher, F., Alves, F., & Gilles-Pascaud, C. (2007). Eddy current nondestructive testing with giant magneto-impedance sensor. *NDT & E International*, 40(6), 439-442.
- Vieux-Rochaz, L. (2000). A new GMR sensor based on NiFe/Ag multilayers. *Sensors and Actuators A: Physical*, 81(1–3):53–56.
- Wan, J., Huang, M., Ma, Y., Guo, W., Wang, Y., Zhang, H., ... Sun, X. (2011). Prediction of effluent quality of a paper mill wastewater treatment using an adaptive network-based fuzzy inference system. *Applied Soft Computing Journal*, 11(3): 3238–3246.

- Wei, L., Guoming, C., Xiaokang, Y., Chuanrong, Z., & Tao, L. (2013). Analysis of the lift-off effect of a U-shaped ACFM system. *NDT & E International*, 53: 31–35.
- Wong, H., Bajaj, V., Moan, G., Huterer, M., & Poidevin, C. (1990). The role of leak-before-break in assessments of flaws detected in CANDU pressure tubes. *International Journal of Pressure Vessels and Piping*, 43(1–3):23–37.
- Wu, Y., Cao, Z., & Xu, L. (2011). A simplified model for non-destructive thickness measurement immune to the lift-off effect. *Instrumentation and Measurement Technology Conference (I2MTC)*, 1-4.
- Xie, R., Chen, D., Pan, M., Tian, W., Wu, X., Zhou, W., & Tang, Y. (2015). Fatigue Crack Length Sizing Using a Novel Flexible Eddy Current Sensor Array. *Sensors*, 15(12):32138–32151.
- Xu, X., Liu, M., Zhang, Z., & Jia, Y. (2014). A Novel High Sensitivity Sensor for Remote Field Eddy Current Non-Destructive Testing Based on Orthogonal Magnetic Field. *Sensors (Basel, Switzerland)*, 14(12): 24098–24115.
- Xu, Z., Wu, X., Li, J., & Kang, Y. (2012). Assessment of wall thinning in insulated ferromagnetic pipes using the time-to-peak of differential pulsed eddy-current testing signals. *NDT & E International*, 51:24–29.
- Yadegari, a. M., Moini, R., Sadeghi, S. H. H., & Mazlumi, F. (2010). Output signal prediction of an open-ended rectangular waveguide probe when scanning cracks at a non-zero lift-off. *NDT & E International*, 43(1):1–7.
- Yamanaka, A., Kashima, T., Nago, S., Hosoyama, K., Takao, T., Sato, S., & Takeo, M. (2002). Coil bobbin composed of high strength polyethylene fiber reinforced plastics for a stable high field superconducting magnet. *Physica C: Superconductivity and Its Applications*, 372–376(PART 3), 1447–1450.
- Yang, G., Dib, G., Udpa, L., Tamburrino, A., Udpa, S. S., & Eddy, A. (2015). Rotating Field EC-GMR Sensor for Crack Detection at Fastener Site in Layered Structures. *IEEE Sensors Journal*, 15(1):463–470.
- Yang, G., Zeng, Z., Deng, Y., Liu, X., Udpa, L., & Dib, G. (2012). Sensor-tilt invariance analysis for eddy current signals. *NDT & E International*, 52:1–8.
- Yang, S., Tian, G. Y., Abidin, I. Z., & Wilson, J. (2011). Simulation of Edge Cracks Using Pulsed Eddy Current Stimulated Thermography. *Journal of Dynamic Systems, Measurement, and Control*, 133(1): 011008,
- Ye, C., Huang, Y., Udpa, L., & Udpa, S. S. (2016). Novel Rotating Current Probe With GMR Array Sensors for Steam Generate Tube Inspection. *IEEE Sensors Journal*, 16(12), 4995-5002.
- Yin, W., Binns, R., Dickinson, S. J., Davis, C., & Peyton, A. J. (2007). Analysis of the Liftoff Effect of Phase Spectra for Eddy Current Sensors. *IEEE Transactions on Instrumentation and Measurement*, 56(6):2775–2781.

- Yin, W., Member, S., & Xu, K. (2015). A Novel Triple-Coil Electromagnetic Sensor for Thickness Measurement Immune to Lift-Off Variations. *IEEE Transactions on Instrumentation and Measurement*, 65(1), 164-169.
- Yin, W., Withers, P. J., Sharma, U., & Peyton, A. J. (2009). Noncontact characterization of carbon-fiber-reinforced plastics using multifrequency eddy current sensors. *IEEE Transactions on Instrumentation and Measurement*, 58(3): 738–743.
- Yu, Y., Yan, Y., Wang, F., Tian, G., & Zhang, D. (2014). An approach to reduce lift-off noise in pulsed eddy current nondestructive technology. *NDT & E International*, 63:1–6.
- Zaoui, A., Menana, H., Feliachi, M., & Berthiau, G. (2010). Inverse problem in nondestructive testing using arrayed eddy current sensors. *Sensors (Basel, Switzerland)*, 10(9):8696–704.
- Zemalache, K. M., & Maaref, H. (2009). Controlling a drone: Comparison between a based model method and a fuzzy inference system. *Applied Soft Computing*, 9(2): 553–562.
- Zeng, Z., Deng, Y., Liu, X., Udpa, L., Udpa, S. S., Koltenbah, B. E. C., Steffes, G. (2011). EC-GMR Data Analysis for Inspection of Multilayer Airframe Structures. *IEEE Transactions On Magnetics*, 47(12):4745–4752.
- Zhang, Y., Li, Q., Zhang, Y., Wang, D., & Xing, J. (2012). Optimization of succinic acid fermentation with *Actinobacillus succinogenes* by response surface methodology (RSM). *Journal of Zhejiang University SCIENCE B*, 13(2):103–110.
- Zhao, J., Tian, W., Zhang, Q., Pan, M., Hu, J., Chen, D., & Luo, F. (2013). Designs of Slope Magnetic Flux Guides for 3-Axis Magnetic Sensor. *IEEE Transactions on Magnetics*, 49(10): 5301–5303.
- Zhu, W., Shen, H., & Chen, W. (2009). New Method for Suppressing Lift-Off Effects Based on Hough Transform. *2009 International Conference on Measuring Technology and Mechatronics Automation*, 653–656.

PUBLICATIONS

1. Rifai, D., Abdalla, A., Ali, K., & Razali, R. (2016). Giant Magnetoresistance Sensors: A Review on Structures and Non-Destructive Eddy Current Testing Applications. *Sensors*, 16(3), 298.
2. Rifai, D., & Abdalla, A. N. (2015). Defect Signal Analysis for Nondestructive Testing. *ARPN Journal of Engineering and Applied Sciences*, 11(4), 1–14.
3. Rifai, D., Abdalla, A. N., Khamsah, N., & Aizat, M. (2016). Subsurface Defects Evaluation using Eddy Current Testing. *Indian Journal of Science and Technology*, 9(March).
4. Rifai, D., Abdalla, A., Ali, K., Razali R. Faraj, Moneer (2017). An Eddy Current Testing Platform System for Pipe Defect Inspection Based on an Optimized Eddy Current Technique Probe Design. *Sensors*, 17,579