

UNIVERSITI MALAYSIA PAHANG

BORANG PENGESAHAN STATUS TESIS*

JUDUL: **TEMPERATURE BASED DC MOTOR SPEED CONTROL**

SESI PENGAJIAN: 2010/2011

Saya GARY ROYSTON GEORGE (881101-13-5039)

mengaku membenarkan tesis (Sarjana Muda/Sarjana /Doktor Falsafah)* ini disimpan di Perpustakaan dengan syarat-syarat kegunaan seperti berikut:

1. Tesis adalah hakmilik Universiti Malaysia Pahang (UMP).
2. Perpustakaan dibenarkan membuat salinan untuk tujuan pengajian sahaja.
3. Perpustakaan dibenarkan membuat salinan tesis ini sebagai bahan pertukaran antara institusi pengajian tinggi.
4. **Sila tandakan (✓)

SULIT

(Mengandungi maklumat yang berdarjah keselamatan atau kepentingan Malaysia seperti yang termaktub di dalam AKTA RAHSIA RASMI 1972)

TERHAD

(Mengandungi maklumat TERHAD yang telah ditentukan oleh organisasi/badan di mana penyelidikan dijalankan)

TIDAK TERHAD

Disahkan oleh:

(TANDATANGAN PENULIS)

(TANDATANGAN PENYELIA)

Alamat Tetap:

KG SUNGAI PINANG
94000 BAU, KUCHING
SARAWAK

NOR LAILI BT ISMAIL
(Nama Penyelia)

Tarikh: _____

Tarikh: _____

- CATATAN: * Potong yang tidak berkenaan.
 ** Jika tesis ini SULIT atau TERHAD, sila lampirkan surat daripada pihak berkuasa/organisasi berkenaan dengan menyatakan sekali tempoh tesis ini perlu dikelaskan sebagai atau TERHAD.
 ♦ Tesis dimaksudkan sebagai tesis bagi Ijazah doktor Falsafah dan Sarjana secara Penyelidikan, atau disertasi bagi pengajian secara kerja kursus dan penyelidikan, atau Laporan Projek Sarjana Muda (PSM).

TEMPERATURE BASED DC MOTOR SPEED CONTROL

GARY ROYSTON GEORGE

This thesis is submitted as partial fulfillment of the requirements for the award of the
Bachelor of Electrical Engineering (Electronics)

Faculty of Electrical & Electronics Engineering
Universiti Malaysia Pahang

NOVEMBER, 2010

TABLE OF CONTENTS

CHAPTER	ELEMENTS	PAGE
DECLARATION		ii
DEDICATION		iii
ACKNOWLEDGEMENT		iv
ABSTRACT		v
TABLE OF CONTENTS		vii
LIST OF FIGURES		x
LIST OF APPENDICES		xii
LIST O LIST OF ABBREVIATION		xiii

CHAPTER 1	INTRODUCTION	
------------------	---------------------	--

1.1 Background of Study	1
1.2 Problem Statement	2
1.3 Project Objective	2
1.4 Project Scope	3
1.5 Thesis outline	4

CHAPTER 2 LITERATURE REVIEW

2.1 Analog to Digital Converter (ADC)	5
2.2 Pulse Width Modulation (PWM)	5
2.3 PIC 16F877 Microcontroller	7
2.4 MOSFET switching applications	8
2.4.1 Turn-On procedure	9
2.4.2 Turn-Off procedure	11
2.5 MOSFET Driver	14
2.6 LM35 precision centigrade temperature sensor	16
2.7 DC-DC boost converter	16

CHAPTER 3 METHODOLOGY

3.1 Theory of operation	19
3.2 System Operation Flowchart	21
3.3 Design hardware	22
3.4 Sensor and microcontroller interfacing	22
3.5 Principle of operation for controlling DC motor speed using PWM	27
3.6 DC motor speed control and LED signal behavior by PIC	27
3.7 DC motor speed control by a power MOSFET	33

3.8 PWM control using transistor at low side drive	33
3.9 DC-DC Boost Converter simulation	34
3.9.1 Pulse-width modulation simulation setting	36
3.9.2 Voltage output simulation setting	37

CHAPTER 4

RESULTS AND DISCUSSIONS

4.1 PROTEUS ISIS Professional v7.6 SP4	
simulation for PIC16F877 interfacing with	
LM35 temperature sensor and 14-pins LCD display	38
4.2 DC motor speed control and LED simulation	39
4.3 DC-DC Boost Converter simulation by	
PSpice OrCAD Capture v9.1	41
4.4 Hardware	44
4.4.1 Hardware overview	44
4.4.2 Oscillator result on output PWM signal	
for motor control	47

CHAPTER 5

CONCLUSION AND RECOMMENDATIONS

5.0 Conclusion	52
5.1 Future Recommendation	53

REFERENCES	54
-------------------	-----------

APPENDICES	A: INSTRUCTION SOURCE CODE	57
	B: DATASHEET	61

LIST OF FIGURES

FIGURE	TITLE	PAGE
1	Examples of PWM duty cycle square waves	6
2	Pin diagram for PIC16F877A microcontroller	8
3	Simplified clamped inductive switching model	9
4a	MOSFET turn-on diagram	9
4b	MOSFET turn-on time intervals	10
5a	MOSFET turn-off diagram	12
5b	MOSFET turn-off time intervals	12
6	Direct gate drive circuit	15
7	Typical DC-DC boost converter	17
8	Design flowchart	21
9	Circuit design for the hardware	22
10	Schematic circuit for sensor, lcd and microcontroller interface	23
11a	Source code	24
11b	Source code (continued)	24
12	LM35, PIC16F877 and external crystal, LCD display, LED, MOSFET and 12V DC motor interface simulation.	28
13	Definition and variables for PWM and LED	

	output program	29
14	PWM duty cycle and LED behavior program	30
15	Low side drive circuit	34
16	DC-DC boost converter schematic by PSpice OrCAD Capture v9.1 software	34
17	A running simulation with a voltage/level marker at the generated PWM signal	36
18	Simulation setting; Transient analysis, runtime until 1ms	36
19	A running simulation with a voltage/level marker at the output voltage	37
20	Simulation setting; Transient analysis, runtime until 0.1s	37
21	A running simulation at temperature of 28°C set on LM35	38
22	LM35, PIC16F877 and external crystal, LCD display, LED, MOSFET and 12V DC motor interface simulation	39
23	A running simulation at a temperature below 25°C. The output LED is low and DC motor is not running (duty cycle = 0)	40
24	Simulation at temperature between 25°C and 41°C. The motor is running at 65.5% motor speed and the LED is blinking.	40
25	Simulation at temperature higher than 41°C. Duty cycle is 100%, drive DC motor to a full speed. The output LED is high.	41
26	Graph of transient analysis for PWM simulation between 0s to 1ms (PWM duty cycle is 25%)	41
27	Graph of transient analysis between 50ms until 100ms	42
28	PW of VPULSE is reduced to 8μs	42
29	Graph of transient analysis between 50ms until 100ms	43

30	Simulation using a larger capacitor (2.2mF) and PW is adjusted to 8.5 μ s	43
31	Graph of transient analysis between 0s to 100ms	44
32	Hardware circuit	45
33	DC-DC boost converter circuit	46
34	LCD display 30°C temperature reading and the motor is running	46
35	PWM input into IRF 540N MOSFET at 26°C	47
36	PWM input into IRF 540N MOSFET at 28°C	47
37	PWM input into IRF 540N MOSFET at 30°C	48
38	PWM input into IRF 540N MOSFET at 32°C	48
39	PWM input into IRF 540N MOSFET at 34°C	49
40	PWM input into IRF 540N MOSFET at 36°C	49
41	PWM input into IRF 540N MOSFET at 38°C	50
42	PWM input into IRF 540N MOSFET at 40°C	50
43	PWM input into IRF 540N MOSFET at 42°C	51

LIST OF TABLES

TABLE	TITLE	PAGE
1	Temperature reading and calculated PWM duty cycle, DC motor speed and LED signal behavior.	32
2	Hardware label	45
3	Temperature reading with theoretical calculated PWM duty cycle and oscillator result on hardware testing duty cycle.	51

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Instruction Source Code	57
B1	Datasheet for PIC 16F877	62
B2	Datasheet for LM 35	66
B3	Datasheet for LM 7805	72
B4	Datasheet for TO-220 package	77
B5	Datasheet for IRF540N	78

LIST OF ABBREVIATION

DC	Direct Current
PIC	Programmable Interface Controller
PWM	Pulse Width Modulation
ADC	Analog to Digital Converter
RPM	Revolutions per Minute
LCD	Liquid Crystal Display

MOSFET	Metal–Oxide–Semiconductor Field-Effect Transistor
PCB	Printed Circuit Board
CICM	Continuous Inductor Current Mode
DICM	Discontinuous Inductor Current Mode
PFC	Power Factor Correction
EMI	Electromagnetic Interference