

## REFERENCES

- Ako, T. A., Onoduku, U. S., Oke, S. A., Essien, B. I., Idris, F. N., Umar, A. N., & Ahmed, A. A. (2014). Environmental Effects of Sand and Gravel Mining on Land and Soil in Luku, Minna, Niger State, North Central Nigeria. *Journal of Geosciences and Geomatics*, 2(2), 42–49. <https://doi.org/10.12691/jgg-2-2-1>
- Nisha, D. A. (2016). Study of Partial Replacement by Glass Powder and Crushed Spent Fire Bricks in Concrete, 5(3), 83–88.
- Kumar, D., Gupta, A., & Ram, Sri. (2014). Uses of Bottom ash in the Replacement of fine aggregate for Making Concrete, 4(6), 3891–3895.
- Ali, T. S. (2017). Effect of Ground Water Sodium Chloride Attack on Reinforced Concrete Footings, 4(1), 1–7.
- Al-Jabri, K. S., Al-Saidy, A. H., & Taha, R. (2011). Effect of copper slag as a fine aggregate on the properties of cement mortars and concrete. *Construction and Building Materials*, 25(2), 933–938. <https://doi.org/10.1016/j.conbuildmat.2010.06.090>
- Arivumangai, A., & Felixkala, T. (2014). Strength and Durability Properties of Granite Powder Concrete, 4, 1–6. <https://doi.org/10.5923/c.jce.201401.01>
- Bai, Y., Darcy, F., & Basheer, P. A. M. (2005). Strength and drying shrinkage properties of concrete containing furnace bottom ash as fine aggregate. *Construction and Building Materials*, 19(9), 691–697. <https://doi.org/10.1016/j.conbuildmat.2005.02.021>
- Balamurugan, G., & Perumal, P. (2013). Use of Quarry Dust to Replace Sand in Concrete – An Experimental Study. *International Journal of Scientific and Research Publications*, 3(1), 2250–3153. Retrieved from [www.ijsrp.org](http://www.ijsrp.org)
- Buchole, N. G. and J. (n.d.). Properties of High-Calcium Dry Bottom Ash for Structural Concrete. *Materials Journal*, 94(2). JOUR. <https://doi.org/10.14359/289>
- Containing, C., Husk, P. R., Abalaka, A. E., & Okoli, O. G. (2013). Strength Development and Durability Properties of, 4–12.
- Corrosion, C. S. (2009). Chloride Resistance of Concrete, (June).
- Dahl, O., Nurmesniemi, H., Pöykiö, R., & Watkins, G. (2009). Comparison of the characteristics of bottom ash and fly ash from a medium-size (32 MW) municipal district heating plant incinerating forest residues and peat in a fluidized-bed boiler. *Fuel Processing Technology*, 90(7), 871–878. <https://doi.org/10.1016/j.fuproc.2009.04.013>
- Elawady, E., Hefnawy, A. A. El, & Ibrahim, R. A. F. (2014). Comparative Study on Strength, Permeability and Sorptivity of Concrete and their relation with Concrete Durability, 4(4), 132–139.
- Ettringite Formation and Sulfate Attack on Concrete by M. Collepardi. (n.d.).
- Fu, T. C., Yeih, W., Chang, J. J., & Huang, R. (2014). The Influence of Aggregate Size and Binder Material on the Properties of Pervious Concrete, 2014.
- Ganesh Prabhu, G., Hyun, J. H., & Kim, Y. Y. (2014). Effects of foundry sand as a fine

- aggregate in concrete production. *Construction and Building Materials*, 70, 514–521. <https://doi.org/10.1016/j.conbuildmat.2014.07.070>
- Gorai, B., Jana, R. K., & Premchand. (2003). Characteristics and utilisation of copper slag - A review. *Resources, Conservation and Recycling*, 39(4), 299–313. [https://doi.org/10.1016/S0921-3449\(02\)00171-4](https://doi.org/10.1016/S0921-3449(02)00171-4)
- Guwahati, T. (2015). EFFECT OF SILICA FUME ON SOME PROPERTIES, (March).
- Hamid Mir, A. (2015). Improved Concrete Properties Using Quarry Dust as Replacement for Natural Sand. *International Journal of Engineering Research and Development*, 11(3), 2278–67.
- Haque, M. B., & Tuhin, I. A. (2012). Effect of Aggregate Size Distribution on Concrete Compressive Strength, 19(5), 35–39.
- Ilangovana, R., Mahendrana, N., & Nagamanib, K. (2008). Strength and Durability Properties of Concrete Containing Quarry Rock Dust As Fine Aggregate. *ARPN Journal of Engineering and Applied Sciences*, 3(5), 20–26.
- Jariyathitipong, P., Hosotani, K., Fujii, T., & Ayano, T. (2014). Sulfuric Acid Resistance of Concrete with Blast Furnace Slag Fine Aggregate, 8(11), 1403–1413.
- Joshy, B. M. (2014). Resistance to sodium sulphate and sodium chloride attack of fly ash based geopolymer concrete, 2(10), 22–27.
- Keerthinarayana, S., & Srinivasan, R. (2010). Study on Strength and Durability of Concrete By Partial Replacement of Fine Aggregate Using. *Most*, (Lx).
- Lohani, T. K., Padhi, M., Dash, K. P., & Jena, S. (2012). Optimum utilization of Quarry dust as partial replacement of sand in concrete, 1(2), 391–404. <https://doi.org/10.6088/ijaser.0020101040>
- Malik, M. I., Jan, S. R., Peer, J. A., & Nazir, S. A. (2015). Study of Concrete Involving Use of Quarry dust as Partial Replacement of Fine Aggregates International organization of Scientific Research, 5(2), 5–10.
- Miyamoto, S., Minagawa, H., & Hisada, M. (n.d.). a Study on the Reaction Mechanism of Hardened Cement Chemically Damaged By.
- Of, E., Ions, C., On, S., Of, C., & Concrete, R. (1996). EFFECT OF CHLORIDE IONS SOURCE ON CORROSION OF REINFORCED NORMAL AND, 107–112.
- Okonkwo, V. O., & E, A. E. (2015). EFFECTS OF AGGREGATE GRADATION ON THE PROPERTIES OF CONCRETE MADE FROM GRANITE CHIPPINGS, 4(12), 17–20.
- Padmalal, D., Maya, K., Sreebha, S., & Sreeja, R. (2008). Environmental effects of river sand mining: a case from the river catchments of Vembanad lake, Southwest coast of India. *Environmental Geology*, 54(4), 879–889. article. <https://doi.org/10.1007/s00254-007-0870-z>
- Pereira De Oliveira, L. A., De Castro Gomes, J. P., & Gonilho Pereira, C. N. (2006). Study of Sorptivity of Self-Compacting Concrete With Mineral Additives. *Savaime Susitankinančio Betono Su Mineraliniais Priedais Įgerties Tyrimai.*, 12(3), 215–220. Retrieved from <http://search.ebscohost.com/login.aspx?direct=true&db=a9h&AN=22520815&lang=es&site=ehost-live>

- Pitroda, J., & Umrigar, F. S. (2013). Evaluation of Sorptivity and Water Absorption of Concrete with Partial Replacement of Cement by Thermal Industry Waste ( Fly Ash ), 2(7), 245–249.
- Ramasubramani, R., & Divya, S. (2016). Replacement of Sand by Sheet Glass Powder in Concrete, 1(1).
- Ramezaniyanpour, A. M. (2012). Sulfate Resistance and Properties of Portland - Limestone Cements. *Department of Civil Engineering, Doctorado*, 185.
- Reddy, B. M., Rao, H. S., George, M. P., & Pradesh, A. (2012). Effect of Hydrochloric Acid ( HCl ) on Blended Cement ( Fly Ash based ) and Silica Fume Blended Cement and their Concretes, 1(9), 476–480.
- Saiyad, A. (2016). Experimental Study on Use of Quarry Dust and Fly Ash with Partial Replacement of Fine Aggregates and Cement in Concrete, 1(6), 92–96.
- Scrivener, K. (2013). Durability Aspects, 2(1), 40–46.
- Shanmugavadivu, P. M. (2011). Durability Properties of Concrete with Natural sand and Manufactured sand, (Icse), 978–981.
- Siddique, R., & Noumowe, A. (2008). Utilization of spent foundry sand in controlled low-strength materials and concrete. *Resources, Conservation and Recycling*, 53(1–2), 27–35. <https://doi.org/10.1016/j.resconrec.2008.09.007>
- Sokołowska, J. J., & Woyciechowski, P. (n.d.). Effect of acidic environments on cement concrete degradation.
- SUDHIR et al. (2013). Effect of Quarry Dust As Partial Replacement of Sand in Concrete. *Indian Streams Research Journal*, 3(2013.6.05), 254–258. <https://doi.org/10.13140/2.1.2742.0804>
- Vijayakumar, G., Vishaliny, M. H., & Govindarajulu, D. (2013). Studies on Glass Powder as Partial Replacement of Cement in Concrete Production. *International Journal of Emerging Technology and Advanced Engineering*, 3(2), 153–157.
- Vyawahare, M. R., & Mohitkar, V. M. (2015). STRENGTH AND SORPTIVITY STUDY OF COMBINED POWDER AND VMA TYPE SELF-CONSOLIDATING CONCRETE WITH SILICA FUME AND CRUSHER DUST, 5(5), 41–50.
- Xu, H., Zhao, Y., Cui, L., & Xu, B. (2013). Sulphate attack resistance of high-performance concrete under compressive loading. *Journal of Zhejiang University SCIENCE A*, 14(7), 459–468. <https://doi.org/10.1631/jzus.A1300067>