

FAST RESPONSE FIBRE BRAGG GRATING (FBG) PRESSURE TRANSDUCER



INVENTOR: MOHD HAFIZI BIN ZOHARI, Ph.D. FACULTY: FACULTY OF MECHANICAL ENGINEERING, UNIVERSITI MALAYSIA PAHANG, 26600 PEKAN, PAHANG, MALAYSIA EMAIL: hafizi@ump.edu.my

CO-INVENTORS: MUHAMMAD AIZZUDDIN BIN ABDULLAH; VORATHIN A/L EPIN ; AZIMAN BIN ABDULLAH







www.ump.edu.my

PRODUCT / BACKGROUND

FBG pressure sensor has shown a great potential in replacing conventional electrical pressure sensor due to its adaptability to harsh environment. However, increasing its sensitivity is still a challenge. In this work, bonding of FBG to a rubber-based diaphragm pressure transducer was proposed and experimentally presented. The improved design of the rubber-based diaphragm has enhanced the sensitivity and sensing range recorded at 118.03 nm/MPa or 7.614 x 10^{-2} MPa⁻¹ across a range of 0.08 MPa with a good linearity of 99.8%. Furthermore, the thermal-strain cross sensitivity was totally compensated.















NOVELTY

- Real-time wavelength pressure monitoring from spectrum analyzer device.
- New diaphragm-type design based on low Young's modulus natural rubber.
- The pressure transducer was joined with 12 mm x 40 mm male air hose fitting which gives universal snap-fit applications to any 12 mm female pneumatic coupler.

PUBLICATIONS

BENEFITS / USEFULNESS

Real-time data allows immediate real-time decision

Predictive maintenance becomes more efficient and

Enable continuous monitoring of pressure.

- ISI
 - Hafizi, Z. M., Epaarachchi, J., & Lau, K. T. (2015). Impact location determination on thin laminated composite plates using an NIR-FBG sensor system. *Measurement*, 61, 51-57. Q2-IF: 1.742
- Vorathin, E., Hafizi, Z. M., Ghani, S. A. Che., Siregar, J. P., & Lim, K. S. (2017). FBGs Real-Time Impact Damage Monitoring System of GFRP Beam Based on CC-LSL Algorithm. *International Journal of Structural Stability* and Dynamics, 18(5), 1850075. Q2-IF:1.617
 - Vorathin, E., Hafizi, Z. M., Aizzuddin, A. M., & Lim, K. S. (2018). A highly sensitive multiplexed FBG pressure

PRODUCT CHARACTERISTICS







ACHIEVEMENTS

- Creation, Innovation, Technology & Research Exposition (CITREX) 2018 Top 10 Gold medal
- Creation, Innovation, Technology & Research Exposition (CITREX) 2017 – Silver medal
- International Invention, Innovation and Technology Exhibition (ITEX) 2017 – Silver medal
- Creation, Innovation, Technology & Research Exposition (CITREX) 2016 – Silver medal
- Advanced Innovation & Engineering Exhibition (AiNEX) 2016 – Gold medal with best awards

MARKETABILITY

Wavelength

 $\lambda_{\text{strain free}}$

Power, (dBm)

The report by ElectroniCast from May 2017 predicts the fibre optic sensor (FOS) market will increase at a compound annual growth rate (CAGR) of 7.35% from US\$3.38 billion (RM13.14 billion) in 2016 to US\$4.82 billion (RM18.74 billion) in 2021 and then at a CAGR of 4.41% to US\$5.98 billion (RM23.26 billion) by 2026. (source: Allwood, G., Wild, G., & Hinckley, S. (2017). Fiber bragg grating sensors for mainstream industrial processes. Electronics, 6(4), 92.)



transducer based on natural rubber diaphragm and ultrathin aluminium sheet. *Optics & Laser Technology*, 106, 177-181. **Q2-IF: 2.109**

SCOPUS

making.

less labor

• Zohari, Mohd Hafizi, Yusof, Mohd Fadhlan, Siregar, Januar Parlaungan, & Sing, Lim Kok. (2015). The Applications of FBG sensor for Realtime Strain Mapping of Thin Composite Plate under Point Loading. J. Electrical Systems Special issue AMPE2015.

COLLABORATORS

Academic institution

- Photonics Research Centre, Faculty of Science, University of Malaya, 50603 Kuala Lumpur, Malaysia Interested company
- NineSigma, Inc.
- GE Power

PATENT

• Title: *"Highly sensitive FBG pressure transducer ".* Currently under utility innovation drafting.