


“I hereby acknowledge that the scope and quality of this thesis is qualified for the
award of the Bachelor Degree of Electrical Engineering (Electronics)”

Signature :  _____

Name : NURULFADZILAH BINTI HASAN

Date : 30 NOVEMBER 2007

HOME AUTOMATION USING BLUETOOTH TECHNOLOGY

AHMAD THIBRAANI BIN TERMIZI

This thesis is submitted as partial fulfillment of the requirements for the award of the
Bachelor of Electrical Engineering (Electronics)

Faculty of Electrical & Electronics Engineering
Universiti Malaysia Pahang

NOVEMBER, 2007

PERPUSTAKAAN UNIVERSITI MALAYSIA PAHANG	
No. Pendaftaran 029344	No. Pengajian TK 5103-3 .A84 2007 vs Jenis
tarikh 14 FEB 2008	

“All the trademark and copyrights use herein are property of their respective owner. References of information from other sources are quoted accordingly; otherwise the information presented in this report is solely work of the author.”

Signature : *Ahmad Thibraani*

Author : AHMAD THIBRAANI BIN TERMIZI

Date : 30 NOVEMBER 2007

To my beloved family and my dear Intan Syahira

ACKNOWLEDGEMENT

The most directly responsible person for the success of this project is my wise project supervisor, Madam Nurulfadzilah Hasan. I wish to express my sincere appreciation to her for the given encouragement, guidance and inspiration throughout the project completion.

My special thank to Fadzilah Nanyan for the help and friendship.

I am also very thankful to all my colleagues and those who have provided assistance at various occasions. Their views and tips are useful indeed. Unfortunately, it is not possible to list all of them in this limited space.

I am very grateful to my family members: mama, papa, Baihaqky, Najua and Amirul. Thank you for the support you've given me all this long.

ABSTRACT

The world has witnessed significant advancement of technologies over the past decade. Those advance technologies existed to suit human's desire to make life easy and less complicated. Home automation is a system that is designed to enable user to "control" the house with only a few hits on the computer keyboard. Various "intelligent" appliances, i.e., microwave ovens, air-conditioners, washing machines and home theatres are set to realize the concept of a smart home. With home automation system it becomes possible to control home appliances, which can be interconnected and monitored using a single Microchip PIC16F877A microcontroller through a Personal Area Network (PAN) in home environment. This project focuses on the application of Bluetooth technology in home automation and networking environment. A network that is built in this project contains a master module and a slave module. The slave communicates with the master through a Bluetooth connection.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	TITLE	i
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	TABLE OF CONTENTS	vi
	LIST OF FIGURES	x
	LIST OF TABLES	xiv
	LIST OF ABBREVIATIONS	xv
	LIST OF APPENDICES	xvi
1	INTRODUCTION	1
	1.1 Background	1
	1.1.1 Home Automation	2
	1.1.2 Bluetooth Home Network	2
	1.2 Problem Statement	3
	1.3 Project Objective	4
	1.4 Project Scopes	4
	1.5 Thesis Outline	5

2	LITERATURE REVIEW	6
2.1	The Network of Home Automation	6
2.2	Medium of Communication in Home Automation	7
2.3	Wireless Communication in Home Automation	8
2.4	Bluetooth Technology	10
2.4.1	Air Interface	11
2.4.2	Frequency Hopping	12
2.4.3	Link and Packets	13
2.4.4	Connection Establishment and Inquiry	14
2.4.5	Bluetooth Wireless Technology Profile	16
2.5	Universal Asynchronous Receiver/Transmitter (UART)	17
3	SYSTEM DESIGN	21
3.1	Introduction	21
3.2	Technical and Functional Specification	22
3.2.1	Power Source	23
3.2.2	Voltage Regulator	25
3.2.3	Bluetooth Module	28
3.2.4	Microcontroller	30
3.2.5	7-Segment Decoder	32
3.2.6	DC Motor	34
3.2.7	DC Motor Driver	35
3.2.8	Light Emitting Diode	36
3.3	Design Implementation	37
3.3.1	Microcontroller Circuit	38
3.3.2	Bluetooth Module Circuit	40
3.3.3	7-Segment Circuit	41
3.3.4	DC Motor Circuit	43

3.4	Programming the Microcontroller	45
3.4.1	Compiling the Program	45
3.4.2	Load Hex Files into PIC16F877A	47
3.5	Configuring the KC-21 Bluetooth Module	48
3.5.1	Writing the AT Command for KC-21 Bluetooth Module	49
3.5.2	HyperTerminal	51
4	RESULT AND ANALYSIS	52
4.1	Introduction	52
4.2	Powering Up the Slave Module	52
4.3	Establishing Communication Between Master and Slave Module	53
4.4	Features of the System Design	57
4.4.1	Password Protection	58
4.4.2	Controlling the Slave Module	59
4.4.3	Device Status Display	60
4.4.4	One Connection at a Time	61
4.5	Performance of the System	62
4.5.1	Hardware Functionality	62
4.5.2	Connection between Slave and Master	64
4.5.3	Device Response Time	65
5	CONCLUSION AND RECOMMENDATIONS	66
5.1	Conclusion	66
5.2	Design Challenges	67
5.3	Future Recommendation	68
5.3.1	Installing the Actual Home Appliances	68
5.3.2	Graphic User Interface (GUI)	68

5.3.3	Timer Control	69
5.4	Costing	69
	Commercialization	71
	REFERENCES	72
	APPENDIX	
	Appendix A – KC-21 Bluetooth OEM module	
	Datasheet	75

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Bluetooth link system diagram	11
2.2	Bluetooth frequency hopping technique	13
2.3	Bluetooth connection procedure	14
2.4	Bluetooth technology profiles	17
3.1	Hardware configurations of devices	22
3.2	Rectangular-size alkaline battery	23
3.3	9.0 V alkaline battery voltage and current discharge characteristics	24
3.4	12 V AC/DC converter	24
3.5	1.5 V AA size battery	25
3.6	AA size alkaline battery voltage and current discharge characteristics	25
3.7	LM7805 5.0V voltage regulator	26

3.8	LM7805 voltage regulator characteristics	26
3.9	LM1117-3.3 3.3V voltage regulator	26
3.10	LM1117-3.3 voltage regulator characteristics	27
3.11	KC-21 class 2 Bluetooth module	28
3.12	PIC16F877A microcontroller	30
3.13	melabs U2 Programmer	31
3.14	melabs U2 Programmer software window	31
3.15	MPLAB IDE software window	32
3.16	Common cathode 7-segment display	33
3.17	Small size DC motor	34
3.18	White LED	37
3.19	PIC16F877A microcontroller pin configuration	39
3.20	Schematic diagram for PIC16Fb77A microcontroller	39
3.21	KC-21 Bluetooth module data	40
3.22	Schematic diagram of KC-21 Bluetooth module	41
3.23	IC 4511 7-segment decoder pin assignment	42
3.24	Common cathode 7-segment pin assignment	42

3.25	Schematic diagram of 7-segment circuit design	43
3.26	L293B motor driver pin assignment	44
3.27	Schematic diagram of DC motor circuit design	44
3.28	The result from compiling the C program using MPLAB IDE	46
3.29	Machine code display in Microsoft Notepad software	47
3.30	PIC16F877A attached to the melabs U2 Programmer	48
3.31	Dialogue box when the program successfully loaded	48
3.32	AT command for changing baud rate	50
3.33	Baudrate successfully changed	50
3.34	Device's local name successfully changed	51
4.1	Slave module when powered on	53
4.2	Bluetooth dongle attached to the USB port of the computer	54
4.3	Human Device Interface (HDI) software window	55
4.4	Connection between master and slave module is established	56

4.5	Connection status between master and slave module	57
4.6	“Enter Password” request in Hyperterminal window	58
4.7	List of instructions of the remote devices for user to control	60
4.8	Status display when DC motor is turned on	61
4.9	The operating DC motor and its corresponding 7-segment display	62
4.10	The light white LED and its corresponding 7-segment display	63

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	RS-232 signal pin assignments	20
3.1	KC-21 Bluetooth module parameters	29
3.2	Truth table of BCD to 7-segment LED configuration	33
3.3	Motor characteristics from manufacturer at 4.5V	35
3.4	In system motor parameters at 6.0 V	35
3.5	L293B pin functions	36
5.1	List of components and cost involved	70

LIST OF ABBREVIATIONS

AC	–	Alternating Current
BCD	–	Binary Coded Decimal
CEBus	–	Consumer Electronic Bus
DC	–	Direct Current
GSM	–	Global System for Mobile Communications
GUI	–	Graphic User Interface
HDI	–	Human Device Interface
I/O	–	Input/output
IC	–	Integrated Circuit
ISM	–	Industrial, Scientific and Medical
LAN	–	Local Area Network
LED	–	Light Emitting Diode
LSB	–	Least Significant Bit
OEM	–	Original Equipment Manufacturer
PAN	–	Personal Area Network
PC	–	Personal computer
PIC	–	Programmable Intelligent Computer
Rx	–	Receive
SPP	–	Serial Port Profile
Tx	–	Transmit
UART	–	Universal Asynchronous Receiver/Transmitter
USB	–	Universal Serial Bus

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	KC-21 Bluetooth OEM module datasheet	75