

REFERENCES

- Ahmad, S., & Azad, a. (2013). An exploratory study on correlating the permeability of concrete with its porosity and tortuosity. *Advances in Cement Research*, 25(5), 288–294. <https://doi.org/10.1680/adcr.12.00052>
- Azman, E., Shaari, J., & Kok, V. (2011). Wastewater production , treatment and use in Malaysia, 1–13. <https://doi.org/10.1016/j.watres.2014.11.002>
- Beck, K., Brunetaud, X., Mertz, J., & Al-Mukhtar, M. (2010). On the use of eggshell lime and tuffeau powder to formulate an appropriate mortar for restoration purposes. *Limestone in the Built Environment: Present-Day Challenge for the Preservation of the Past*, (March), 137–145. <https://doi.org/10.1144/sp331.12>
- Cyr, M., Coutand, M., & Clastres, P. (2007). Technological and environmental behavior of sewage sludge ash (SSA) in cement-based materials. *Cement and Concrete Research*, 37(8), 1278–1289. <https://doi.org/10.1016/j.cemconres.2007.04.003>
- Garcés, P., Pérez Carrión, M., García-Alcocel, E., Payá, J., Monzó, J., & Borrachero, M. V. (2008). Mechanical and physical properties of cement blended with sewage sludge ash. *Waste Management*, 28(12), 2495–2502. <https://doi.org/10.1016/j.wasman.2008.02.019>
- Hobbs, D. W. (2003). Thaumassite sulfate attack in field and laboratory concretes: Implications for specifications. *Cement and Concrete Composites*, 25(8), 1195–1202. [https://doi.org/10.1016/S0958-9465\(03\)00145-8](https://doi.org/10.1016/S0958-9465(03)00145-8)
- Horgnies, M., & Chen, J. J. (2014). Superhydrophobic concrete surfaces with integrated microtexture. *Cement and Concrete Composites*, 52, 81–90. <https://doi.org/10.1016/j.cemconcomp.2014.05.010>
- Jayasankar, R., Mahindran, N., & Ilangovan, R. (2010). Studies on Concrete using Fly Ash , Rice Husk Ash and Egg Shell Powder. *International Journal of Civil and Structural Engineering*, 1(3), 362–372.
- Justnes, H. (2013). Aspects of replacing gypsum with other calcium salts in Portland cement. *Advances in Cement Research*, 25(1), 44–50. <https://doi.org/10.1680/adcr.12.00033>
- Karthick, J., Jeyanthi, R., & Petchiyammal, M. (2014). Experimental Study on Usage of Egg Shell as Partial Replacement for Sand in Concrete. *International Journal of Advanced Research in Education Technology*, 1(1), 7–10.
- Kawabata, C. Y., Savastano Junior, H., & Sousa-Coutinho, J. (2012). Rice husk derived waste materials as partial cement replacement in lightweight concrete. *Ciência E Agrotecnologia*, 36(5), 567–578. <https://doi.org/10.1590/S1413-70542012000500010>

- Kelessidis, A., & Stasinakis, A. S. (2012). Comparative study of the methods used for treatment and final disposal of sewage sludge in European countries. *Waste Management*, 32(6), 1186–1195. <https://doi.org/10.1016/j.wasman.2012.01.012>
- Madaki, Y. S., & Lau, S. (2013). Palm oil Effluent (POME) from Malaysia Palm Oil Mills: Waste or Resource. *International Journal of Science, Environment and Technology*, 2(6), 1138–1155. Retrieved from www.ijset.net
- Matar, M., Builes B, S., Johnson, O. A., Napiah, M., Kamaruddin, I., Industrial, C., ... México, C. (2014). Use of wastewater sludge in concrete mixes, 8(4), 565–570. Retrieved from <http://repositorio.utp.edu.co/dspace/bitstream/11059/1835/1/62839B932.pdf>
- Monz??, J., Pay??, J., Borrachero, M. V., & Girb??s, I. (2003). Reuse of sewage sludge ashes (SSA) in cement mixtures: The effect of SSA on the workability of cement mortars. *Waste Management*, 23(4), 373–381. [https://doi.org/10.1016/S0956-053X\(03\)00034-5](https://doi.org/10.1016/S0956-053X(03)00034-5)
- Oberlink, A. E., & Robl, T. (2011). Non-Portland cement activation of blast furnace slag. *World of Coal Ash (WOCA)*. Retrieved from http://uknowledge.uky.edu/gradschool_theses/25/
- Repository, I. (n.d.). Combined anaerobic respiration (CAD) of sewage sludge and other urban solid wastes This item is held in Loughborough University ' s Institutional Repository (<https://dspace.lboro.ac.uk/>) and was harvested from the British Library ' s EThOS service (ht.
- Sales, A., & de Souza, F. R. (2009). Concretes and mortars recycled with water treatment sludge and construction and demolition rubble. *Construction and Building Materials*, 23(6), 2362–2370. <https://doi.org/10.1016/j.conbuildmat.2008.11.001>
- Salmiati, Salim, M. R., Ujang, Z., & Azman, S. (2012). Potential of Sewage Sludge as Soil Amendment. *2012 2nd International Conference on Environment and Industrial Innovation*, 35, 66–70.
- Shuhadah, S. and A. G. S. (2009). LDPE-Isophthalic Acid-Modified Egg Shell Powder. *Journal of Physical Science*, 20(1), 87–98.
- Siuris, A. (2011). Properties of Sewage Sludge Resulted From Urban Wastewater Treatment in The Republic of Moldova. *Scientific Papers, LIV*, 103–108.
- Stroh, J., Schlegel, M. C., Irassar, E. F., Meng, B., & Emmerling, F. (2014). Applying high resolution SyXRD analysis on sulfate attacked concrete field samples. *Cement and Concrete Research*, 66, 19–26. <https://doi.org/10.1016/j.cemconres.2014.07.015>
- Yerramala, A. (2014). Properties of concrete with eggshell powder as cement replacement. *Indian Concrete Journal*, 88(10), 94–102.

- Yuan, H., Dangla, P., Chatellier, P., & Chaussadent, T. (2013). Degradation modelling of concrete submitted to sulfuric acid attack. *Cement and Concrete Research*, 53, 267–277. <https://doi.org/10.1016/j.cemconres.2013.08.002>
- Yusuf, R. O., Noor, Z. Z., Moh', N. a., Moh', D. F., Din, D., & Abba, A. H. (2012). Use of sewage sludge ash (SSA) in the production of cement and concrete - a review. *International Journal of Global Environmental Issues*, 12(2/3/4), 214. <https://doi.org/10.1504/IJGENVI.2012.049382>
- Zhang, Q., Le Roy, R., Vandamme, M., & Zuber, B. (2014). Long-term creep properties of cementitious materials: Comparing microindentation testing with macroscopic uniaxial compressive testing. *Cement and Concrete Research*, 58, 89–98. <https://doi.org/10.1016/j.cemconres.2014.01.004>