## FLOW BEHAVIOUR ENHANCEMENT IN MICRO-CHANNELS

## LAM MIAN MIAN

BACHELOR OF CHEMICAL ENGINEERING UNIVERSITI MALAYSIA PAHANG

## FLOW BEHAVIOUR ENHANCEMENT IN MICRO-CHANNELS

## LAM MIAN MIAN

Thesisi submitted in partial fulfilment of the requirements

for the award of the degree of

Bachelor of Chemical Engineering

Faculty of Chemical & Natural Resources Engineering
UNIVERSITI MALAYSIA PAHANG

## SUPERVISOR'S DECLARATION

We hereby declare that we have checked this thesis and in our opinion, this thesis is adequate in terms of scope and quality for the award of the degree of Bachelor of Chemical Engineering.

Signature :

Name of main supervisor : PROF. DR. HAYDER A. ABDUL BARI

Position : PROFESSOR
Date : JANUARY 2017

### STUDENT'S DECLARATION

I hereby declare that the work in this thesis is my own except for quotations and summaries which have been duly acknowledged. The thesis has not been accepted for any degree and is not concurrently submitted for award of other degree

Signature :

Name : LAM MIAN MIAN

ID Number : KC13055

Date : JANUARY 2017

Dedicated to my lovely family for their support, love and care.

#### **ACKNOWLEDGEMENT**

I would like to express my special appreciation and thanks to my supervisor, Prof. Dr. Hayder A. Abdul Bari. You have been a brilliant mentor for me. I would like to thank you for your never-ending support during my tenure as a research student under your guidance, for giving insightful comments and suggestions of which without it, my research path would be a difficult one. Your advice on my research has been valuable.

A special thanks to my family. Words cannot express how grateful I am to my mother and father for the love and support throughout these years. Your prayer for me was what sustained me thus far. I would like express appreciation to my beloved husband who always be my support in the moments when there was no one to answer my queries and for all the sacrifices you have made on my behalf.

I am also indebted to the Ministry of Higher Education and Universiti Malaysia Pahang for funding my study.

I would also like to thank all of my friends who supported me in writing, and motivate me to strive towards my goal. I am sincerely grateful to the staffs of Chemical Engineering and Natural Resources Faculty who helped me in many ways and made my stay in UMP pleasant and unforgettable.

# **Table of Contents**

SUPERVISOR'S DECLARATION	IV
STUDENT'S DECLARATION	V
ACKNOWLEDGEMENT	VII
ABSTRACT	VIII
ABSTRAK	IX
LIST OF TABLES	XII
LIST OF FIGURES	XIII
LIST OF ABBREVIATIONS	XVI
I INTRODUCTION	1
1.1 Background	1
1.2 Motivation	2
1.3 Problem Statement	2
1.4 Objectives	3
1.5 Scopes	3
2 LITERATURE REVIEW	4
2.1 Fabrication of Micro-channel Technologies	4
2.1.1 Soft Lithography Method	5
2.1.2 Microinjection Moulding	7
2.1.3 Hot Embossing	8
2.1.4 Laser Ablation	9
2.1.5 Summary	10
2.2 Micro Particle Image Velocimetry (μ-PIV)	11
2.3 Drag Reduction in Micro-channels	12
2.3.1 Drag Reduction (DR)	12
2.3.2 Drag Reducing Additives	13
2.3.3 Insoluble Additives	13
2.3.4 Soluble Additives	14
2.3.4.1 Synthetic Polymeric Additives	15
2.3.4.2 Natural Polymeric Additives	18
2.3.5 Summary	20
3 MATERIALS AND METHODS	
3.1 Raw Materials	

	3.1	.1	Transported Liquid	21
	3.1	.2	Chemicals	21
3	.2	Nat	ural Polymer Solution Preparation	21
3	.3	Fab	rication of Micro-channels	22
	3.3	.1	Fabrication Procedure	24
3	.4	Equ	ipments	25
	3.4	.1	Microchannels	25
	3.4	.2	Plasma Cleaner	25
	3.4	.3	Spin Coater	26
	3.4	.4	Micro Pattern Generator	26
	3.4	.5	Desiccator	26
	3.4	.6	Vacuum Oven	27
	3.4	.7	Pressure & Vacuum Controller	27
3	.5	Exp	perimental Set-up	27
3	.6	Exp	erimental Procedure	. 28
3	.7	Exp	perimental Procedure of micro-PIV	28
4	RE	SUL	TS AND DISCUSSIONS	30
4	.1	Ove	erview	30
4	.2	Res	ult and Discussion of Flow Increment	30
	4.2	.1	Effect of Concentration	30
	4.2	.2	Effect of Length in Micro-channels	35
	4.2	.3	Effect of Width in Micro-channels	39
	4.2	.4	Summary	44
4	.3	Res	ult and Discussions for Micro-PIV	44
	4.3	.1	The CCD Images	44
	4.3	.2	Velocity Profiles	46
5	CO	NCL	.USION	. 52
REF	ERI	ENC	ES	53
APP	EN]	DIX	A	62
APP	EN	DIX	В	64
APP	EN	DIX	C	92

# LIST OF TABLES

Table 2-1: Main advantages and disadvantages for the fabrication techniques	of the
microfluidic devices.	11
Table 3-1: The schematic of Y-shaped micro-channels.	22
Table 4-1: The Maximum %FI Achieved by DRA.	44

# LIST OF FIGURES

Figure 2-1: Fabrication scheme for Soft lithography (Flores & Wang, 2010)	7
Figure 2-2: Fabrication scheme for Laser ablation (Fiorini & Chiu, 2005)	0
Figure 2-3: SEM picture of slag waste particles (A) SEM picture with 9 x mag. (B) SEM picture of particle surface with 500 x mag (Kamarulizam et al.,2011)	4
Figure 2-4: PEO improves left ventricular function, ventricular wall motion and	
reduction of infarct myocardium in rat model (Chen et al., 2011) 1	6
Figure 2-5: Mean arterial pressure and tissue perfusion in animal models (Marhefka et	
al., 2006)	8
Figure 3-1: The monosaccharides present in xanthan gum	1
Figure 3-2: Fabrication steps of the micro-channel.	5
Figure 3-3: Plasma cleaner	5
Figure 3-4: Spin coater. 2	6
Figure 3-5: Micro Pattern Generator	6
Figure 3-6: Desiccator.	6
Figure 3-7: Vacuum oven	7
Figure 3-8: Pressure & vacuum controller.	7
Figure 3-9: Schematic diagram of experimental setup consisted of (a) computer (b)	
pressure and vacuum controller (c) reservoir containing solution (d) flow sensor (e) Y-	
shaped micro-channel (f) beaker as storage tank	8
Figure 4-1: %FI of various Xanthan gum concentrations varying the operating pressure	
in micro-channel having the tail length of 70mm	0
Figure 4-2: %FI of various Xanthan gum concentrations varying the operating pressure	
in micro-channel having the tail length of 60mm	1
Figure 4-3: %FI of various Xanthan gum concentrations varying the operating pressure	
in micro-channel having the tail length of 50mm	1
Figure 4-4: %FI of various Xanthan gum concentrations varying the operating pressure	
in micro-channel having the tail length of 40mm	2

Figure 4-5: %FI of various Xanthan gum concentrations varying the operating pressure in micro-channel having the width of 500µm
Figure 4-6: %FI of various Xanthan gum concentrations varying the operating pressure in micro-channel having the width of 300µm
Figure 4-7: %FI of various Xanthan gum concentrations varying the operating pressure in micro-channel having the width of 200µm
Figure 4-8: %FI of Xanthan gum in various tail length of micro-channel by varying the operating pressure having the concentration of 20ppm
Figure 4-9: %FI of Xanthan gum in various tail length of micro-channel by varying the operating pressure having the concentration of 50ppm
Figure 4-10: %FI of Xanthan gum in various tail length of micro-channel by varying the operating pressure having the concentration of 100ppm
Figure 4-11: %FI of Xanthan gum in various tail length of micro-channel by varying the operating pressure having the concentration of 150ppm
Figure 4-12: %FI of Xanthan gum in various tail length of micro-channel by varying the operating pressure having the concentration of 200ppm
Figure 4-13: %FI of Xanthan gum in various tail length of micro-channel by varying the operating pressure having the concentration of 300ppm
Figure 4-14: %FI of Xanthan gum in various tail length of micro-channel by varying the operating pressure having the concentration of 400ppm
Figure 4-15: %FI of Xanthan gum in various tail length of micro-channel by varying the operating pressure having the concentration of 500ppm
Figure 4-16: %FI of Xanthan gum in various width of micro-channel by varying the operating pressure having the concentration of 20ppm
Figure 4-17: %FI of Xanthan gum in various width of micro-channel by varying the operating pressure having the concentration of 50ppm
Figure 4-18: %FI of Xanthan gum in various width of micro-channel by varying the operating pressure having the concentration of 100ppm

Figure 4-19: %FI of Xanthan gum in various width of micro-channel by varying the	
operating pressure having the concentration of 150ppm	. 41
Figure 4-20: %FI of Xanthan gum in various width of micro-channel by varying the operating pressure having the concentration of 200ppm.	. 41
Figure 4-21: %FI of Xanthan gum in various width of micro-channel by varying the operating pressure having the concentration of 300ppm.	. 42
Figure 4-22: %FI of Xanthan gum in various width of micro-channel by varying the operating pressure having the concentration of 400ppm.	. 42
Figure 4-23: %FI of Xanthan gum in various width of micro-channel by varying the operating pressure having the concentration of 500ppm.	. 43

## LIST OF ABBREVIATIONS

DR Drag reduction

DRA Drag reduction agent

DRP Drag reduction polymer

%DR Drag reduction efficacy

HA Hyaluronic acid

PA Polyacrylamide

PAM Polyacrylamide

PDMS Poly (dimethyl siloxane)

PEO Poly (ethylene oxide)

PNVF Poly (N-vinylformamide)

RBC Red blood cell

TMCS Trichloromethylsilane