

## CHAPTER 6.0

### REFERENCES

- Abd, R. M., Nour, A. H., & Sulaiman, A. Z. (2014). Experimental Investigation on Dynamic Viscosity and Rheology of Water-Crude Oil Two Phases Flow Behavior at Different Water Volume Fractions. *American Journal of Engineering Research*, (3), 2320–847. Retrieved from [www.ajer.org](http://www.ajer.org)
- Abdel-raouf, E. M. E. (2012). *Crude Oil Emulsions- Composition Stability and Characterization*. (M. E.-S. Abdel-Raouf, Ed.). Croatia: InTech. <https://doi.org/10.5772/2677>
- Abdurahman H. N., & M. Nuraini. (2010). Chemical Destabilization on Water in Crude Oil Emulsions. *International Journal of Chemical, Molecular, Nuclear, Materials and Metallurgical Engineering*, 4(2), 217–220.
- Abu-Zaid, M. (2004). Performance of single cylinder, direct injection Diesel engine using water fuel emulsions. *Energy Conversion and Management*, 45(5), 697–705. [https://doi.org/10.1016/S0196-8904\(03\)00179-1](https://doi.org/10.1016/S0196-8904(03)00179-1)
- Al-Sabagh, A. M., Emara, M. M., Noor El-Din, M. R., & Aly, W. R. (2011). Formation of water-in-diesel oil nano-emulsions using high energy method and studying some of their surface active properties. *Egyptian Journal of Petroleum*, 20(2), 17–23. <https://doi.org/10.1016/j.ejpe.2011.06.005>
- Armas, O., Ballesteros, R., Martos, F. J., & Agudelo, J. R. (2004). Characterization of light duty Diesel engine pollutant emissions using water-emulsified fuel. <https://doi.org/10.1016/j.fuel.2004.11.015>
- Bernstein, L., Bosch, P., Canziani, O., Chen, Z., Christ, R., Davidson, O., ... Madan, P. (2007). Climate Change 2007 Synthesis Report. *Intergovernmental Panel on Climate Change [Core Writing Team IPCC]*.
- Chen, G., & Tao, D. (2005). An experimental study of stability of oil–water emulsion. *Fuel Processing Technology*, 86(5), 499–508. <https://doi.org/10.1016/j.fuproc.2004.03.010>
- Cofala, J., Amann, M., Klimont, Z., Kupiainen, K., & Höglund-Isaksson, L. (2007). Scenarios of global anthropogenic emissions of air pollutants and methane until 2030. *Atmospheric Environment*, 41(38), 8486–8499. <https://doi.org/10.1016/j.atmosenv.2007.07.010>
- Corsini, A., Fanfarillo, G., Rispoli, F., & Venturini, P. (2015). Pollutant emissions in common-rail Diesel engines in extraurban cycle: rapeseed oils vs Diesel fuel. *Energy Procedia*, 82, 141–148. <https://doi.org/10.1016/j.egypro.2015.12.006>
- Debnath, B. K., Saha, U. K., & Sahoo, N. (2015). A comprehensive review on the

- application of emulsions as an alternative fuel for diesel engines. *Renewable and Sustainable Energy Reviews*, 42, 196–211. <https://doi.org/10.1016/j.rser.2014.10.023>
- Fahd, M. E. A., Wenming, Y., Lee, P. S., Chou, S. K., & Yap, C. R. (2013). Experimental investigation of the performance and emission characteristics of direct injection diesel engine by water emulsion diesel under varying engine load condition. *Applied Energy*, 102, 1042–1049. <https://doi.org/10.1016/j.apenergy.2012.06.041>
- Fingas, M. F. (2014). Water-in-oil emulsions: formation and prediction. *Journal of Petroleum Science Research*, 3(1), 38. <https://doi.org/10.14355/jpsr.2014.0301.04>
- Fingas, M., & Fieldhouse, B. (2004). Formation of water-in-oil emulsions and application to oil spill modelling. *Journal of Hazardous Materials*, 107, 37–50. <https://doi.org/10.1016/j.jhazmat.2003.11.008>
- Furusawa, K., Sato, A., Shirai, J., & Nashima, T. (2002). Depletion Flocculation of Latex Dispersion in Ionic Micellar Systems. *Journal of Colloid and Interface Science*, 253(2), 273–278. <https://doi.org/10.1006/jcis.2002.8515>
- Ghannam, M. T., & Selim, M. Y. E. (2009). Stability Behavior of Water-in-Diesel Fuel Emulsion. *Petroleum Science and Technology*, 27(4), 396–411. <https://doi.org/10.1080/10916460701783969>
- H, S. P., Gonsalvis, J., & Vijay, V. S. (2015). Effect of Introduction of Water into Combustion Chamber of Diesel Engines – A Review, 5, 28–33. <https://doi.org/10.5923/c.ep.201501.06>
- Hagos, F. Y., Aziz, A. R. A., & Tan, I. M. (2011). Water-in-diesel emulsion and its micro-explosion phenomenon-review. In *2011 IEEE 3rd International Conference on Communication Software and Networks* (pp. 314–318). IEEE. <https://doi.org/10.1109/ICCSN.2011.6014903>
- Issaka, S. A., Nour, A. H., & Yunus, R. M. (2013). Theoretical Survey and Experimental Assessment on the Commercial Surfactants to Produce Stable Water-in-Petroleum of Miri Light and Kuwait Heavy Crude Oil Emulsions. *International Journal of Engineering Sciences & Research Technology*, 2(12), 3542–3554. Retrieved from <http://>
- Issaka, S. A., Nour, A. H., & Yunus, R. M. (2015a). 20-80 % Water-in-Diesel Emulsion Fuel Formulations and Stability Study for Duration of Two Weeks, 3(7), 1394–1398.
- Issaka, S. A., Nour, A. H., & Yunus, R. M. (2015b). Effect Of 20% Water Content On The Properties (Cetane Number, Rheology And Stability) Of Emulsion Fuel In Comparison To The Commercial Diesel. *International Journal of Current Research*, 7(7), 17798–17805.

- Issaka, S., H. Nour, A., & Yunus, R. (2015). Testing New Surfactant Formulations on Stable 20-80% water-in- diesel Emulsion Fuel Production (One Week Stability). *Oriental Journal of Chemistry*, 31(3), 1717–1722. <https://doi.org/10.13005/ojc/310352>
- Ithnin, A. M., Noge, H., Kadir, H. A., & Jazair, W. (2014). An overview of utilizing water-in-diesel emulsion fuel in diesel engine and its potential research study. <https://doi.org/10.1016/j.joei.2014.04.002>
- Jiao, J., & Burgess, D. J. (2003a). Ostwald ripening of water-in-hydrocarbon emulsions. *Journal of Colloid and Interface Science*, 264(2), 509–516. [https://doi.org/10.1016/S0021-9797\(03\)00276-5](https://doi.org/10.1016/S0021-9797(03)00276-5)
- Jiao, J., & Burgess, D. J. (2003b). Rheology and stability of water-in-oil-in-water multiple emulsions containing Span 83 and Tween 80. *AAPS PharmSci*, 5(1), 62–73. <https://doi.org/10.1208/ps050107>
- Kachuri, L., Villeneuve, P. J., Parent, M.-É., Johnson, K. C., & Harris, S. A. (2016). Workplace exposure to diesel and gasoline engine exhausts and the risk of colorectal cancer in Canadian men. *Environmental Health*, 15(1), 4. <https://doi.org/10.1186/s12940-016-0088-1>
- Kannan, K., & Udayakumar, M. (2009). NOx And HC Emission Control Using Water Emulsified Diesel In Single Cylinder Diesel Engine, 4(8).
- Langevin, D., Poteau, S., Hénaut, I., & Argillier, J. F. (2004). Crude Oil Emulsion Properties and their Application to Heavy Oil Transportation. *Oil & Gas Science and Technology – Rev. IFP*, 59(5), 511–521.
- Lin, C.-Y., & Chen, L.-W. (2008). Comparison of fuel properties and emission characteristics of two- and three-phase emulsions prepared by ultrasonically vibrating and mechanically homogenizing emulsification methods. *Fuel*, 87(10–11), 2154–2161. <https://doi.org/10.1016/j.fuel.2007.12.017>
- Lin, C.-Y., & Wang, K.-H. (2004). Diesel engine performance and emission characteristics using three-phase emulsions as fuel. *Fuel*, 83(4–5), 537–545. <https://doi.org/10.1016/j.fuel.2003.08.012>
- Long, D. S., Smith, M. L., Pries, A. R., Ley, K., & Damiano, E. R. (2004). Microviscometry reveals reduced blood viscosity and altered shear rate and shear stress profiles in microvessels after hemodilution.
- Maiboom, A., & Tauzia, X. (2011). NOx and PM emissions reduction on an automotive HSDI Diesel engine with water-in-diesel emulsion and EGR: An experimental study. *Fuel*, 90(11), 3179–3192. <https://doi.org/10.1016/j.fuel.2011.06.014>
- Marrone, N. J., Kennedy, I. M., & Dryer, F. L. (1983). Internal Phase Size Effects on Combustion of Emulsions. *Combustion Science and Technology*, 33(5–6), 299–307. <https://doi.org/10.1080/00102208308923682>

- Mayank Sharma. (n.d.). Tests for Identification of Emulsion Types. Retrieved March 23, 2016, from <http://www.preservearticles.com/2011122319138/tests-for-identification-of-emulsion-types.html>
- Morozumi, Y., & Saito, Y. (2010). Effect of Physical Properties on Microexplosion Occurrence in Water-in-Oil Emulsion Droplets. *Energy & Fuels*, *24*(3), 1854–1859. <https://doi.org/10.1021/ef9014026>
- Mura, E., Massoli, P., Josset, C., Loubar, K., & Bellettre, J. (2012). Study of the micro-explosion temperature of water in oil emulsion droplets during the Leidenfrost effect. *Experimental Thermal and Fluid Science*, *43*, 63–70. <https://doi.org/10.1016/j.expthermflusci.2012.03.027>
- Nadeem, M., Rangkuti, C., Anuar, K., Haq, M. R. U., Tan, I. B., & Shah, S. S. (2006a). Diesel engine performance and emission evaluation using emulsified fuels stabilized by conventional and gemini surfactants. *Fuel*, *85*(14–15), 2111–2119. <https://doi.org/10.1016/j.fuel.2006.03.013>
- Nadeem, M., Rangkuti, C., Anuar, K., Haq, M. R. U., Tan, I. B., & Shah, S. S. (2006b). Diesel engine performance and emission evaluation using emulsified fuels stabilized by conventional and gemini surfactants. <https://doi.org/10.1016/j.fuel.2006.03.013>
- Nordli, K. G., Sjöblom, J., Kizling, J., & Stenius, P. (1991). Water-in-crude oil emulsions from the Norwegian continental shelf 4. Monolayer properties of the interfacially active crude oil fraction. *Colloids and Surfaces*, *57*(1), 83–98. [https://doi.org/10.1016/0166-6622\(91\)80182-N](https://doi.org/10.1016/0166-6622(91)80182-N)
- Ochoterena, R., Lif, A., Nydén, M., Andersson, S., & Denbratt, I. (2010). Optical studies of spray development and combustion of water-in-diesel emulsion and microemulsion fuels. *Fuel*, *89*(1), 122–132. <https://doi.org/10.1016/j.fuel.2009.06.039>
- Otsubo, Y., & Prud'homme, R. K. (1994). Rheology of oil-in-water emulsions. *Rheologica Acta*, *33*(1), 29–37. <https://doi.org/10.1007/BF00453461>
- Parent, M.-E., Rousseau, M.-C., Boffetta, P., Cohen, A., & Siemiatycki, J. (2007). Exposure to diesel and gasoline engine emissions and the risk of lung cancer. *American Journal of Epidemiology*, *165*(1), 53–62. <https://doi.org/10.1093/aje/kwj343>
- Park, J. W., Huh, K. Y., & Park, K. H. (2000). Experimental study on the combustion characteristics of emulsified diesel in a rapid compression and expansion machine. *Proceedings of the Institution of Mechanical Engineers, Part D: Journal of Automobile Engineering*, *214*(5), 579–586. <https://doi.org/10.1243/0954407001527862>
- Raeie, N., Emami, S., & Karimi Sadaghiyani, O. (2014). Effects of injection timing, before and after top dead center on the propulsion and power in a diesel engine.

*Propulsion and Power Research*, 3(2), 59–67.  
<https://doi.org/10.1016/j.jprr.2014.06.001>

Samec, N. (2002). Numerical and experimental study of water/oil emulsified fuel combustion in a diesel engine. *Fuel*, 81(16), 2035–2044.  
[https://doi.org/10.1016/S0016-2361\(02\)00135-7](https://doi.org/10.1016/S0016-2361(02)00135-7)

Selim, M. Y. E., & Elfeky, S. M. S. (2001). Effects of diesel/water emulsion on heat flow and thermal loading in a precombustion chamber diesel engine. *Applied Thermal Engineering*, 21(15), 1565–1582. [https://doi.org/10.1016/S1359-4311\(01\)00019-9](https://doi.org/10.1016/S1359-4311(01)00019-9)

Selim, M. Y. E., & Ghannam, M. T. (2009). Combustion Study of Stabilized Water-in-Diesel Fuel Emulsion. *Energy Sources, Part A: Recovery, Utilization, and Environmental Effects*, 32(3), 256–274.  
<https://doi.org/10.1080/15567030802467621>

Sudrajad, A., Hirotsugu, F., & Ali, I. (2011). Experimental study of exhaust emissions of W/O emulsion fuel in DI single cylinder diesel engine. *Modern Applied Science*, 5(5), 73–79. <https://doi.org/10.5539/mas.v5n5p73>

Taylor, P. (1998). Ostwald ripening in emulsions. *Advances in Colloid and Interface Science*, 75(2), 107–163. [https://doi.org/10.1016/S0001-8686\(98\)00035-9](https://doi.org/10.1016/S0001-8686(98)00035-9)

Wasan, D. ., Nikolov, A. ., & Aimetti, F. (2004). Texture and stability of emulsions and suspensions: role of oscillatory structural forces. *Advances in Colloid and Interface Science*, 108, 187–195. <https://doi.org/10.1016/j.cis.2003.10.021>

Yahaya Khan, M., Abdul Karim, Z. A., Hagos, F. Y., Aziz, A. R. A., & Tan, I. M. (2014). Current Trends in Water-in-Diesel Emulsion as a Fuel. *The Scientific World Journal*, 2014, 1–15. <https://doi.org/10.1155/2014/527472>