

REFERENCES

- Abaticchio, P., Bottino, A., Roda, G.C., Capannelli, G. and Munari, S. (1990). Characterization of ultrafiltration polymeric membranes. *Desalination*, 78(2), 235-255.
- Abbas, M.F., Elkady, T.Y. and Al-Shamrani, M.A. (2015). Calibrations for volume change measurements using osmotic suction control technique. *HBRC Journal*, 13(1), 39-46.
- Adogbo, G.M. and Mohammed, I. (2012). Effect of kaolinite clay on properties of drilling mud. *International Journal of Scientific and Engineering Research*, 3(11), 1-7.
- Agus, S.S. and Schanz, T. (2005). Comparison of four methods for measuring total suction. *Vadose Zone Journal-Soil Science Society of America*, 4(4), 1087-1095.
- Agus, S.S. and Schanz, T. (2006). Drying, wetting, and suction characteristic curves of a bentonite-sand mixture. *Fourth International Conference on Unsaturated Soils*, pp. 1405-1414.
- Al-Rawas, A.A. and Goosen, M.F. (2006). *Expansive soils: recent advances in characterization and treatment*. London: Taylor and Francis.
- Alvarez, R. and Lavado, R.S. (1998). Climate, organic matter and clay content relationships in the Pampa and Chaco soils, Argentina. *Geoderma*, 83(1), 127-141.
- Asad, A., Kar, S., Ahmeduzzaman, M.H.R. and Hassan, R. (2013). Suitability of bentonite clay: an analytical approach. *International Journal of Earth Science*, 2(3), 88-95.
- ASTM D 4943-08. (2010). Standard test method for shrinkage factors of soils by wax method.
- Bai, X. (1992). *Microstructural deformation of clay*. Ph.D. Thesis. University of Glasgow, Scotland.
- Barbour, S.L. (1987). The role of physicochemical effects on the behavior of clay soils. *Proceeding of 40th Canadian Geotechnical Conference in Regina, Saskatchewan*, pp. 323-342.
- Barbour, S.L. and Yang, N. (1993). A review of the influence of clay-brine interactions on the geotechnical properties of Ca-montmorillonite clayey soils from western Canada. *Canadian Geotechnical Journal*, 30, 920-934.
- Barton, C.D. (2002). Clay minerals. In *Encyclopedia of soil science*. New York : Marcel Dekker.

- Bell, D.J., Hoare, M. and Dunhill, P. (1983). The formation of protein precipitates and their centrifugal recovery. *Advances in biochemical engineering/biotechnology* (Vol. 26). Berlin: Springer-Verlag.
- Benson, H.J. (2001). *Microbiological applications: a laboratory manual in general microbiology*. McGraw Hill Science.
- Binnig, G., Quate, C.F. and Gerber, C. (1986). Atomic force microscope. *Physical Review Letters*, 56(9), 930-933.
- Birle, E., Heyer, D. and Vogt, N. (2008). Influence of the initial water content and dry density on the soil–water retention curve and the shrinkage behaviour of a compacted clay. *Acta Geotechnica*, 3(3), 191-200.
- Biron, D.D.S., Poletto, P., Duarte, J., Zeni, M., Bergmann, C.P. and Santos, V.D. (2015). Preparation and characterization of PA66/alumina composite membrane. *Materials Research*, 18(4), 748-755.
- Blatz, J.A., Cui, Y.J. and Oldecop, L. (2008). Vapour equilibrium and osmotic technique for suction control. *Geotechnical and Geological Engineering*, 26, 661-673.
- Blume, H.P., Brümmer, G.W., Fleige, H., Horn, R., Kandeler, E., Kögel-Knabner, I., Wilke, B.M. et al. (2015). *Scheffer/Schachtschabel soil science*. London: Springer.
- Bohn, H.L., Strawn, D.G. and O'Connor, G.A. (2015). *Soil chemistry*. UK: John Wiley and Sons.
- Borchard, G., Mueller, C., Capelle, M.A.H. and Arvinte, T. (2010). Stabilized protein formulations and use thereof. *U.S. patent application no. 13/505,491*. Switzerland: Therapeomic Ag.
- Bowen, W.R. and Doneva, T.A. (2000). Atomic force microscopy studies of membranes: effect of surface roughness on double-layer interactions and particle adhesion. *Journal of Colloid and Interface Science*, 229(2), 544-549.
- Bowen, W.R., Hilal, N., Lovitt, R.W. and Wright, C.J. (1999). Characterisation of membrane surfaces: direct measurement of biological adhesion using an atomic force microscope. *Journal of Membrane Science*, 154(2), 205-212.
- Bowen, W.R. and Mohammad, A.W. (1998). Characterization and prediction of nanofiltration membrane performance: a general assessment. *Chemical Engineering Research and Design*, 76(8), 885-893.
- Brandt, T. and Wiese, F. (2004). Physical and chemical characteristics of different polyethersulfone membranes. In *Polyethersulfone: membranes for multiple clinical applications* (Vol. 138). Basel: Karger Publishers.

- Brown, G. (1953). The dioctahedral analogue of vermiculite. *Clay Minerals Bulletin*, 2(10), 64-69.
- BS 1377-2. (1990). Soils for civil engineering purposes. Part 2: classification tests. British Standard Institution.
- BS 1377-3. (1990). Methods of test for soils for civil engineering purposes. Chemical and electro-chemical tests.
- BS 4359-1. (1996). Determination of the specific surface area of powders.
- Bulut, R. and Leong, E.C. (2008). Indirect measurement of suction. *Geotechnical and Geological Engineering*, 26(6), 633-644.
- Bulut, R., Par, S.W. and Lytton, R.L. (2000). Comparison of total suction values from psychrometer and filter paper methods. *Proceedings of the Asian Conference on Unsaturated Soils, UNSAT-ASIA 2000*, pp. 269–273.
- Burges, H.D. (2012). *Formulation of microbial biopesticides: beneficial microorganisms, nematodes and seed treatments*. Netherlands: Springer Science and Business Media.
- Calvo, J.I., Hernandez, A., Pradanos, P., Martinez, L. and Bowen, W.R. (1995). Pore size distributions in microporous membranes II, bulk characterization of track-etched filters by air porometry and mercury porosimetry. *Journal of Colloid and Interface Science*, 176(2), 467-478.
- Campbell, G.S and Gee, W.G. (1986). Water potential : miscellaneous methods. In *Methods of soil analysis: physical and mineralogical methods* (Vol. 9). USA: Madison.
- Cardoso, R., Romero, E., Lima, A. and Ferrari, A. (2007). A comparative study of soil suction measurement using two different high-range psychrometers. In *Experimental unsaturated soil mechanics* (Vol. 112). Berlin Heidelberg: Springer.
- Carter, D.L., Heilman, M.D. and Gonzalez, C.L. (1965). Ethylene glycol monoethyl ether for determining surface area of silicate minerals. *Soil Science*, 100(5), 356-360.
- Cerato, A.B. and Lutenegeger, A.J. (2002). Determination of surface area of fine-grained soils by the ethylene glycol monoethyl ether (EGME) method. *Geotechnical Testing Journal*, 25(3), 1-7.
- Cheung, S.C.H., Gary, M.N. and Dixon, D.A. (1987). Hydraulic and ionic diffusion properties of bentonite-sand buffer materials. *Coupled Processes Associated with Nuclear Waste Repositories*, pp. 393-407.
- Churchman, J. and Lowe, D.J. (2012). *Alteration, formation, and occurrence of minerals in soils*. Boca Raton : CRC Press.

- Ciullo, P.A. (1996). *Industrial minerals and their uses: a handbook and formulary*. USA: William Andrew.
- Cleall, P.J., Singh, R.M. and Thomas, H.R. (2011). Non-isothermal moisture movement in unsaturated kaolin-an experimental and theoretical investigation. *ASTM Geotechnical Testing Journal*, 34(5), 1-11.
- Clem, A.G. (1961). Industrial applications of bentonite. *Clays and Clay Minerals*, 10, 272-283.
- Croney, D. and Coleman, J.D. (1954). Soil structure in relation to soil suction. *Journal of Soil Science*, 5(1), 75-84.
- Cunningham, M.R. (2000). *The mechanical behaviour of a reconstituted unsaturated soil*. Ph.D. Thesis. University of London, UK.
- Cuperus, F.P. and Smolders, C.A. (1991). Characterization of UF membranes: membrane characteristics and characterization techniques. *Advances in Colloid and Interface Science*, 34, 135-173.
- Czurda, K. (2006). Encapsulation parameters in waste deposit technology: geologic barriers and liner systems. *Geo. Alp*, 3, 207-214.
- Daniel, D.E. (1993). *Geotechnical practice for waste management*. London: Chapman and Hall.
- Delage, P. (2002). On the behaviour of engineered clay barriers for nuclear waste disposal. *Proceedings of the International Workshop on Environmental Geomechanics*, pp. 161-172.
- Delage, P. and Cui, Y.J. (2008). An evaluation of the osmotic method of controlling suction. *Geomechanics and Geoengineering: An International Journal*, 3(1), 1-11.
- Delage, P., Cui, Y.J. and Tang, A.M. (2010). Clays in radioactive waste disposal. *Journal of Rock Mechanics and Geotechnical Engineering*, 2(2), 111-123.
- Delage P., Howat M. and Cui Y.J. (1998). The relationship between suction and swelling properties in a heavily compacted unsaturated clay. *Engineering Geology*, 50(1), 31-48.
- Delage, P. and Romero, E. (2008). *Geoenvironmental testing geotechnical and geological engineering*. Netherlands: Springer.
- Delage, P., Romero, E. and Tarantino, A. (2008). Recent developments in the techniques of controlling and measuring suction in unsaturated soils. In *Unsaturated soils: advances in geo-engineering*. London: Taylor and Francis Group.

- Diana, C and Nikki, F. (2000). An update of procedures for the measurement of color in pulp mill wastewaters (Technical Bulletin No. 803). Research Triangle Park, NC: National Council for Air and Stream Improvement, Inc.
- Dineen, K. and Burland, J.B. (1995). A new approach to osmotically controlled oedometer testing. *Proceedings of the 1st International Conference on Unsaturated Soils*, 2, 459-465.
- Douglas, L.A. (1989). Vermiculites. *Minerals in Soil Environments*, pp. 635-674.
- Drioli, E. and Giorno, L. (2010). *Comprehensive membrane science and engineering* (Vol. 1). Amsterdam: Elsevier.
- Dubrovin, E.V., Presnova, G.V., Rubtsova, M.Y., Egorov, A.M., Grigorenko, V.G. and Yaminsky, I.V. (2015). The use of atomic force microscopy for 3D analysis of nucleic acid hybridization on microarrays. *Acta Naturae*, 7(2), 25.
- Ebrahimi-Birang, N., Fredlund, D.G. and Samarasekera, L. (2007). Hysteresis of the soil-water characteristic curve in the high suction range. *Proceedings of the OttawaGeo Conference*, pp. 1061-1068.
- Elgabu, H.M. (2013). *Critical evaluation of some suction measurement techniques*. Ph.D. Thesis. University of Cardiff : UK.
- El-Khattab, M.M. (2013). *Post-permeation stability of modified bentonite suspensions under increasing hydraulic gradients*. Master Thesis. University of Texas, Austin.
- Ellis B. (2000). *Polymers: A property database*. USA: CRC Press.
- Emerson, W.W. and Chi, C.L. (1977). Exchangeable calcium, magnesium and sodium and the dispersion of illites in water. II. Dispersion of illites in water. *Soil Research*, 15(3), 255-262.
- Eslinger, E. and Pevear, D.R. (1988). *Clay minerals for petroleum geologists and engineers*. USA: Society of Economic Paleontologists and Mineralogists.
- Ezz El-Din, M.R., Molukhia, H. and Ramadan, A. (2001). Treatment of radioactive waste solutions using local clay minerals. *Arab Journal of Nuclear Sciences and Applications*, 34(2), 117-122.
- Fattah, M.Y., Yahya, A.Y. and Ahmed, B.A. (2012). Total and matric suction measurement of unsaturated soils in Baghdad region by filter paper method. *Journal of Engineering*, 18(5), 611-620.
- Ferro, V. and Mirabile, S. (2009). Comparing particle size distribution analysis by sedimentation and laser diffraction method. *Journal of Agricultural Engineering*, 40(2), 35-43.

- Fleureau, J.M., Kheirbek-Saoud, S., Soemitro, R. and Taibi, S. (1993). Behavior of clayey soils on drying-wetting paths. *Canadian Geotechnical Journal*, 30(2), 287-296.
- Fleureau, J.M., Verbrugge, J.C., Huergo, P.J., Correia, A.G. and Kheirbek-Saoud, S. (2002). Aspects of the behaviour of compacted clayey soils on drying and wetting paths. *Canadian Geotechnical Journal*, 39, 1341-1357.
- Foley, N.K. (1999). *Environmental characteristics of clays and clay mineral deposits*. US: Department of the Interior, US Geological Survey.
- Foster, M.D. (1954). The relation between composition and swelling in clays. *Clays and Clay Minerals*, 3(1), 205-220.
- Fredlund, D.G. (1989). Negative pore-water pressure in slope stability. *Proceedings of Simposio Suramericano de Deslizamientos, Paipa, Colombia*, pp. 1-31.
- Fredlund, D.G. (1996). The scope of unsaturated soil mechanics: an overview. *Proceedings of the First International Conference on Unsaturated Soils*, 3, 1155-1177.
- Fredlund, D.G. (2000). The 1999 RM hardy lecture: the implementation of unsaturated soil mechanics into geotechnical engineering. *Canadian Geotechnical Journal*, 37(5), 963-986.
- Fredlund, D.G., Gan, J. K. and Gallen, P. (1995). Suction measurements on compacted till specimens and indirect filter paper calibration technique. *Transportation Research Record*, 1481, 3-9.
- Fredlund, D.G. and Rahardjo, H. (1993). *Soil mechanics for unsaturated soils*. New York: John Wiley and Sons. Inc.
- Fredlund, D.G., Sheng, D. and Zhao, J. (2011). Estimation of soil suction from the soil-water characteristic curve. *Canadian Geotechnical Journal*, 48(2), 186-198.
- Fredlund, M.D., Fredlund, D.G. and Wilson, G.W. (1997). Estimation of unsaturated soil properties using a knowledge-based system. *Proceedings of the Fourth Congress on Computing in Civil Engineering, ASCE, Philadelphia*, pp. 16-18.
- Freeman, B. (2008). Novel fouling-reducing coatings for ultrafiltration, nanofiltration, and reverse osmosis membranes (Final Scientific/Technical Report). The University Of Texas, Austin.
- Garand-Sheridan, A.M. (2008). *Evaluation of novel polyethersulfone membranes developed using charged surface modifying macromolecules for the removal of pharmaceutically active compounds and endocrine disrupting compounds from drinking water*. Ph.D. Thesis. University of Ottawa, Canada.

- Gavrilescu, M., Pavel, L.V. and Cretescu, I. (2009). Characterization and remediation of soils contaminated with uranium. *Journal of Hazardous Materials*, 163(2), 475-510.
- Geise, G.M., Lee, H.S., Miller, D.J., Freeman, B.D., McGrath, J.E. and Paul, D.R. (2010). Water purification by membranes: the role of polymer science. *Journal of Polymer Science Part B: Polymer Physics*, 48(15), 1685-1718.
- Ghosh, A.K., Bindal, R.C., Prabhakar, S. and Tewari, P.K. (2011). Composite polyamide reverse osmosis (RO) membranes—recent developments and future directions. *BARC Newsletter*, 321, 43-51.
- Gibb, F.G. (2000). A new scheme for the very deep geological disposal of high-level radioactive waste. *Journal of the Geological Society*, 157(1), 27-36.
- Grim, R.E. (1968). *Clay mineralogy*. 2nd Edition. New York: McGraw-Hill, Inc.
- Grim, R.E. and Guven, N. (1978). *Bentonites: geology, mineralogy, properties and uses*. New York: Elsevier.
- Guggenheim, S. (1997). Introduction to the properties of clay minerals. In *Teaching mineralogy* (Vol. 3). Washington: Mineralogical Society of America.
- Haghighi, A. (2011). *Thermo-hydro-mechanical behaviour of kaolin clay*. Ph.D. Thesis. University of Heriot-Watt, UK.
- Haines, W.B. (1930). Studies in the physical properties of soil. V. The hysteresis effect in capillary properties, and the modes of moisture distribution associated therewith. *The Journal of Agricultural Science*, 20(1), 97-116.
- Han, S., Kim, C. and Kwon, D. (1995). Thermal degradation of poly(ethyleneglycol). *Polymer Degradation and Stability*, 47(2), 203-208.
- Harrison, N.R. (1990). Bentonite slurry-grout cut-off walls. *International Journal Rock Mechanical Mining Science Geomechanic*, 36(12), 21-26.
- Harvey, C.C. and Lagaly, G. (2006). Conventional applications. In *Developments in clay science*. Netherlands: Elsevier.
- Hathaway, J.C. (1955). Studies of some vermiculite-type clay minerals. *Clays and Clay Minerals*, 395, 74-86.
- Henderson, J.C. (1970). *Specific gravity determination of marine sediments*. Master Thesis. Naval Postgraduate School Monterey Calif, California.
- Hendricks, S.B., Nelson, R.A. and Alexander, L.T. (1940). Hydration mechanism of the mineral montmorillonite saturated with various cations. *Journal of the American Chemical Society*, 62(6), 1457-1464.

- Hernandez, A., Calvo, J.I., Pradanos, P. and Tejerina, F. (1998). Pore size distributions of track-etched membranes; comparison of surface and bulk porosities. *Colloids and Surfaces: Physicochemical and Engineering Aspects*, 138(2), 391-401.
- Hilal, N., Bowen, W.R., Alkhatib, L. and Ogunbiyi, O. (2006). A review of atomic force microscopy applied to cell interactions with membranes. *Chemical Engineering Research and Design*, 84(4), 282-292.
- Hilal, N., Khayet, M. and Wright, C.J. (2012). *Membrane modification: technology and applications*. Boca Raton: CRC Press.
- Holtz, W.G. and Gibbs, H.J. (1956). Engineering properties of expansive clays. *Transactions of the American Society of Civil Engineers*, 121(1), 641-663.
- Hosseini, S.S., Bringas, E., Tan, N.R., Ortiz, I., Ghahramani, M. and Shahmirzadi, M.A.A. (2016). Recent progress in development of high performance polymeric membranes and materials for metal plating wastewater treatment: a review. *Journal of Water Process Engineering*, 9, 78-110.
- Houston, W.N., Houston, S.L. and Wagner, A.M. (1994). Laboratory filter paper suction measurements. *Geotechnical Testing Journal*, 17(2), 185-194.
- Howell, J., Sanchez, V. and Field, R.W. (2012). *Membranes in bioprocessing: theory and applications*. UK: Springer-Science and Business Media.
- Hu, P., Yang, Q. and Luan, M. (2010). Measurement of soil suction and soil-water characteristics of bentonite-sand mixtures. *ASME 2010 29th International Conference on Ocean, Offshore and Arctic Engineering*, pp. 853-858.
- Hueckel, T.A. (1992). Water-mineral interaction in hygromechanics of clays exposed to environmental loads: a mixture-theory approach. *Canadian Geotechnical Journal*, 29(6), 1071-1086.
- Humphrey, J.P. and Boyd, D.E. (2011). *Clay: types, properties and uses*. New York: Nova.
- Irawan, S. and Samsuri, A. (2007). Drilling mud material cost saving through utilization of treated Malaysian local bentonite. *Mission-Oriented Research: Petrochemical Catalysis Technology*, 5(2), 13-20.
- Ismadji, S., Soetaredjo, F.E. and Ayucitra, A. (2015). Natural clay minerals as environmental cleaning agents. In *Clay materials for environmental remediation*. Switzerland: Springer International Publishing.
- Jahanshahi, M., Rahimpour, A. and Peyravi, M. (2010). Developing thin film composite poly (piperazine amide) and poly (vinyl-alcohol) nanofiltration membranes. *Desalination*, 257(1), 129-136.

- Jayanth, S., Iyer, K. and Singh, D.N. (2012). Influence of drying and wetting cycles on SWCCs of fine grained soils. *Journal of Testing and Evaluation*, 40(3), 376-386.
- Jindaluang, W., Kheoruenromne, I., Suddhiprakarn, A., Singh, B.P. and Singh, B. (2013). Influence of soil texture and mineralogy on organic matter content and composition in physically separated fractions soils of Thailand. *Geoderma*, 195, 207-219.
- Johari, A., Habibagahi, G. and Ghahramani, A. (2006). Prediction of soil-water characteristic curve using a genetic based neural network. *Scientia Iranica*, 13(3), 284-294.
- Johnson, D.J. and Hilal, N. (2013). Membrane characterization by atomic force microscopy. In *Encyclopedia of membrane science and technology*. USA: John Wiley and Sons.
- Jones, U.S. (1982). *Fertilizers and soil fertility*. 2nd Edition. Virginia: Reston Publishing Co., Inc.
- Jones, L.D. and Jefferson, I. (2012). *Expansive soils*. London: ICE Publishing.
- Kanani, D.M., Fissell, W.H., Roy, S., Dubnisheva, A., Fleischman, A. and Zydney, A.L. (2010). Permeability–selectivity analysis for ultrafiltration: effect of pore geometry. *Journal of Membrane Science*, 349(1), 405-410.
- Kassiff, G. and Shalom, A.B. (1971). Experimental relationship between swell pressure and suction. *Géotechnique*, 21(3), 245-255.
- Katsumi, T., Ishimori, H., Onikata, M. and Fukagawa, R. (2008). Long-term barrier performance of modified bentonite materials against sodium and calcium permeant solutions. *Geotextiles and Geomembranes*, 26(1), 14-30.
- Khairuddin, A.K and Radzuan J. (1992). Mineralogic and physic-chemical study of Lahad Datu. *Geology Society of Malaysia Bulletin*, 31, 39-49.
- Khalili, N., Russell, A. and Khoshghalb, A. (2014). *Unsaturated soils: research and applications*. New York: CRC Press.
- Khulbe, K.C., Feng, C.Y. and Matsuura, T. (2008). Membrane surface morphology and membrane performance. In *Synthetic polymeric membranes: characterization by atomic force microscopy*. Germany: Springer Science and Business Media.
- Kim, K.J., Fane, A.G., Aim, R.B., Liu, M.G., Jonsson, G., Tessaro, I.C., Bargeman, D., et al. (1994). A comparative study of techniques used for porous membrane characterization: pore characterization. *Journal of Membrane Science*, 87(1-2), 35-46.
- Kogel, J.E. (2006). *Industrial minerals and rocks: commodities, markets, and uses*. USA: SME.

- Komine, H. (2008). Theoretical equations on hydraulic conductivities of bentonite-based buffer and backfill for underground disposal of radioactive wastes. *Journal of Geotechnical Geoenvironment Engineering*, 4(497), 497-508.
- Krahn, J. and Fredlund, D.G. (1972). On total, matric and osmotic suction. In *The emergence of unsaturated soil mechanics* (Vol. 114). USA: The Williams and Wilkins Co.
- Kubicek, C.P. and Druzhinina, I.S. (2007). *Environmental and microbial relationships* (Vol. 4). New York: Springer Science and Business Media.
- Kutowy, O. and Sourirajan, S. (1975). Cellulose acetate ultrafiltration membranes. *Journal of Applied Polymer Science*, 19(5), 1449-1460.
- Lagerwerff, J.V., Ogata, G. and Eagle, H.E. (1961). Control of osmotic pressure of culture solutions with polyethylene glycol. *Science*, 133(3463), 1486-1487.
- Lambe, T.W. (1958). The structure of compacted clay. *Journal of the Soil Mechanics and Foundations Division*, 84, 1-34.
- Lambe, T.W. and Whitman, R.V. (1969). *Soil mechanics*. New York: John Wiley and Sons.
- Last, J.A., Russell, P., Nealey, P.F. and Murphy, C.J. (2010). The applications of atomic force microscopy to vision science. *Investigative Ophthalmology and Visual Science*, 51(12), 6083-6094.
- Lau, W.J., Ismail, A.F., Misdan, N. and Kassim, M.A. (2012). A recent progress in thin film composite membrane: a review. *Desalination*, 287, 190-199.
- Lavkulich, L.M. (1981). *Methods manual, pedology laboratory*. Department of Soil Science, University of British Columbia, Vancouver, British Columbia, Canada.
- Lee, J.O., Cho, W.J., Kang, C.H. and Chun, K.S. (2001). Swelling and hydraulic properties of Ca-bentonite for the buffer of a waste repository. *Symposium of Technologies for the Management of Radioactive Waste from Nuclear Power Plants and Back End Nuclear Fuel Cycle Activities*, 52, 1-10.
- Lee, S.Y., Hyder, L.K. and Alley, P.D. (1987). Mineralogical characterization of selected shales in support of nuclear waste repository studies: progress report (No. ORNL/TM-10567). USA: Oak Ridge National Lab.
- Leng, S.S. (2011). *Branched polyethylene glycol for protein precipitation*. Ph.D. Thesis. National university of Singapore, Singapore.

- Lentsch, S., Aimar, P. and Orozco, J.L. (1993). Separation albumin-PEG: transmission of PEG through ultrafiltration membranes. *Biotechnology and Bioengineering*, 41(11), 1039-1047.
- Leong, E.C., Tripathy, S. and Rahardjo, H. (2003). Total suction measurement of unsaturated soils with a device using chilled mirror dew-point technique. *Géotechnique*, 53(2), 173-182.
- Lepilleur, B. and Schmitt, E. (1995). The study on swelling clays (Technical Report). National School of Bridges and Road, Paris.
- Levitt, D.G. and Young, M.H. (2003). Soils, hygroscopic water content. In *Encyclopedia of water science*. New York: Marcel Dekker Inc.
- Likos, W.J., Lu, N. and Godt, J.W. (2013). Hysteresis and uncertainty in soil water-retention curve parameters. *Journal of Geotechnical and Geoenvironmental Engineering*, 140(4), 04013050:1-04013050:11.
- Longobardi, A. (2008). Observing soil moisture temporal variability under fluctuating climatic conditions. *Hydrology and Earth System Sciences Discussions*, 5(2), 935-969.
- Lu, N. and Likos, W.J. (2004). *Unsaturated soil mechanics*. US: John Wiley and Sons Inc.
- Lv, C., Su, Y., Wang, Y., Ma, X., Sun, Q. and Jiang, Z. (2007). Enhanced permeation performance of cellulose acetate ultrafiltration membrane by incorporation of Pluronic F127. *Journal of Membrane Science*, 294(1), 68-74.
- Mackenzie, R.C. (1959). The classification and nomenclature of clay minerals. *Clay Minerals. Bulletin*, 4, 52-66.
- Magdoff, F. and Weil, R.R. (2004). *Soil organic matter in sustainable agriculture*. Boca Raton: CRC Press.
- Mantri, S. and Bulut, R. (2014). Evaluating performance of a chilled mirror device for soil total suction measurements. *Advances in Transportation Geotechnics and Materials for Sustainable Infrastructure GSP 250*, pp. 56-64.
- Marcial, D., Delage, P. and Cui Y.J. (2002). On the high stress compression of bentonites. *Canadian Geotechnical Journal*, 39(4), 812-820.
- McDowell, L.A. (2004). *An alternative medium for the measurement of soil suction by the filter paper method*. Ph.D. Thesis. University of Tennessee, Knoxville.
- McKeen, R.G. (1980). Field studies of airport pavements on expansive clay. *Proceedings of the 4th International Conference on Expansive Soils*, pp. 242-261.

- Mendes, J. (2011). *Assessment of the impact of climate change on an instrumented embankment: an unsaturated soil mechanics approach*. Ph.D. Thesis. Durham University, UK.
- Meunier, A. (2005). *Clays*. New York: Springer Science and Business Media.
- Michel, B.E. and Kaufmann, M.R. (1973). The osmotic potential of polyethylene glycol 6000. *Plant Physiology*, 51(5), 914-916.
- Miller, W., Alexander, R., Chapman, N., McKinley, J.C. and Smellie, J.A.T. (2000). *Geological disposal of radioactive wastes and natural analogues* (Vol. 2). UK: Elsevier.
- Minagawa, K., Matsuzawa, Y., Yoshikawa, K. and Khokhlov, A.R. (1994). Direct observation of the coil-globule transition in DNA molecules. *Biopolymers*, 34(4), 555-558.
- Misdan, N., Lau, W.J., Ismail, A.F., Matsuura, T. and Rana, D. (2014). Study on the thin film composite poly (piperazine-amide) nanofiltration membrane: impacts of physicochemical properties of substrate on interfacial polymerization formation. *Desalination*, 344, 198-205.
- Misdan, N., Lau, W.J., Ong, C.S., Ismail, A.F. and Matsuura, T. (2015). Study on the thin film composite poly (piperazine-amide) nanofiltration membranes made of different polymeric substrates: effect of operating conditions. *Korean Journal Chemical Engineering*, 32(4), 75.
- Mitchell, J.K. (1993). *Fundamentals of soil behavior*. 2nd Edition. New York: John Wiley and Sons.
- Mohamed, A.M.O. and Antia, H.E. (1998). *Geoenvironmental engineering* (Vol. 82). Amsterdam: Elsevier.
- Mohammad, A.W. (1998). *Predictive models for nanofiltration membrane processes*. Ph.D. Thesis. University of Wales, Swansea.
- Mohd Tadza, M.Y. (2011). *Soil-water characteristic curves and shrinkage behaviour of highly plastic clays: an experimental investigation*. Ph.D. Thesis. Cardiff University, UK.
- Mohd Tadza, M.Y., Asras, M.F.F., Mohd Tadza, M.A., Ismail, J., Mahazam, N. and Mohd Azmi, N.S. (2016). Intrusion of polyethylene glycol during osmotic tests: identifying cellulose acetate degrading microbes. *Jurnal Teknologi*, 72, 1-6.
- Mohd Tadza, M.Y., Mahazam, N. and Tripathy, S. (2017a). An evaluation of osmotic technique under ultraviolet germicidal irradiation exposure. *International Journal*, 12(32), 30-36.

- Mohd Tadza, M.Y., Mohd Azmi, N.S., Mustapha, R., Desa, N.D. and Samuding, K. (2017b). Malaysian alternative to international reference bentonite buffer in underground nuclear waste repository. *AIP Conference Proceedings*, 1799(1), 030002:1 – 030002:6.
- Money, N.P. (1989). Osmotic pressure of aqueous polyethylene glycols – relationship between molecular weight and vapour pressure deficits. *Plant Physiology*, 91, 766-769.
- Monroy, R., Ridley, A., Dineen, K. and Zdravkovic, L. (2006). The suitability of the osmotic technique for the long-term testing of partly saturated soils. *Geotechnical Testing Journal*, 30(3), 220-226.
- Mulder, M. (1996). *Basic principles of membrane technology*. Netherlands: Kluwer Academic Publishers.
- Munir, A. (2006). Dead end membrane filtration: laboratory feasibility studies in environmental engineering (Technical Report). PID A: 37589962.
- Murray, E.J. and Sivakumar, V. (2010). *Unsaturated soils: a fundamental interpretation of soil behaviour*. USA: John Wiley and Sons.
- Nagaraj, T.S. and Sivapullaiah, P.V. (1981). Plummet balance - a potential tool for subsieve particle size analysis. *Geotechnical Testing Journal*, 4(1), 36-40.
- Nam, S., Gutierrez, M., Diplas, P., Petrie, J., Wayllace, A., Lu, N. and Muñoz, J.J. (2010). Comparison of testing techniques and models for establishing the SWCC of riverbank soils. *Engineering Geology*, 110(1), 1-10.
- Nanda, D., Tung, K.L., Li, Y.L., Lin, N.J. and Chuang, C.J. (2010). Effect of pH on membrane morphology, fouling potential, and filtration performance of nanofiltration membrane for water softening. *Journal of Membrane Science*, 349(1), 411-420.
- Naylor, T.D. (1996). Polymer membranes-materials, structures and separation performance. *Rapra Review Reports*, 8(5), 12-14.
- Ng, C.W., Cui, Y., Chen, R. and Delage, P. (2007). The axis-translation and osmotic techniques in shear testing of unsaturated soils: a comparison. *Soils and Foundations*, 47(4), 675-684.
- Ng, C.W. and Menzies, B. (2007). *Advanced unsaturated soil mechanics and engineering*. New York: Taylor and Francis.
- Northrup, C.J.M. (1980). *Scientific basis for nuclear waste management* (Vol. 2). New York: Plenum Publication Corporation.
- Ochoa, N.A., Pradanos, P., Palacio, L., Pagliero, C., Marchese, J. and Hernandez, A. (2001). Pore size distributions based on AFM imaging and retention of multi disperse polymer solutes: characterisation of polyethersulfone UF membranes

- with dopes containing different PVP. *Journal of Membrane Science*, 187(1), 227-237.
- Oh, T.H., Pang, S.Y. and Chua, S.C. (2010). Energy policy and alternative energy in Malaysia: issues and challenges for sustainable growth. *Renewable and Sustainable Energy Reviews*, 14(4), 1241-1252.
- Ojovan, M.I. and Lee, W.E. (2013). *An introduction to nuclear waste immobilisation*. 2nd Edition. Amsterdam: Elsevier.
- Önal, M. (2006). Physicochemical properties of bentonites: an overview. *Communication Faculty Science University Ankara Series B*, 52(2), 7-21.
- Paine, P.L. and Scherr, P. (1975). Drag coefficients for the movement of rigid spheres through liquid-filled cylindrical pores. *Biophysical Journal*, 15(10), 1087.
- Palanikumar, M. (2013). *Soil mechanics*. New Delhi: PHI Learning Private Limited.
- Pan, H., Qing, Y. and Pei-yong, L. (2010). Direct and indirect measurement of soil suction in the laboratory. *Electronic Journal of Geotechnical Engineering*, 15(3), 1.
- Peberdy, J.F. (2013). *Penicillium and acremonium*, (Vol. 1). New York: Springer Science and Business Media.
- Pei-yong, L. and Qing, Y. (2009). Test study on soil water characteristic curve of bentonite-sand mixtures. *Electronic Journal Geotechnical Engineering*, 14, 1-8.
- Polidori, E. (2007). Relationship between the Atterberg limits and clay content. *Soils and Foundations*, 47(5), 887-896.
- Poppe, L.J., Paskevich, V.F., Hathaway, J.C. and Blackwood, D.S. (2001). A laboratory manual for x-ray powder diffraction. *US Geological Survey Open-File Report*, 1(041), 1-88.
- Powrie, W. (2013). *Soil mechanics: concepts and applications*. Boca Raton: CRC Press.
- Prakash, K., Sridharan, A., Baba, J.A. and Thejas, H.K. (2008). Determination of shrinkage limit of fine-grained soils by wax method. *Geotechnical Testing Journal*, 32(1), 86-89.
- Prakash, K., Sridharan, A., Thejas, H.K. and Swaroop, H.M. (2012). A simplified approach of determining the specific gravity of soil solids. *Geotechnical and Geological Engineering*, 30(4), 1063-1067.
- Praneeth, K. (2014). *Synthesis and characterization of novel polymeric membranes for water purification and effluents treatment*. Ph.D. Thesis. RMIT University, Australia.

- Pusch, R. (1992). Use of bentonite for isolation of radioactive waste products. *Clay Miner*, 27(3), 353-361.
- Pusch, R. and Yong, R.N. (2006). *Microstructure of smectite clays and engineering performance*. 1st Edition. London: CRC Press.
- Qu, P., Tang, H., Gao, Y., Zhang, L. and Wang, S. (2010). Polyethersulfone composite membrane blended with cellulose fibrils. *BioResources*, 5(4), 2323-2336.
- Rahardjo, H. and Leong, E.C. (2006). Suction measurement. *ASCE Geotechnical Special Publication*, 147(1), 81-104.
- Rath, D.L. (1986). Origin and characteristics of Wyoming bentonite deposits. *Public Information Circular*, 25, 84-90.
- Rautioaho, E. and Korkiala-Tanttu, L. (2009). Bentomap: survey of bentonite and tunnel backfill knowledge. Finland: VTT Technical Research Centre.
- Ray, R.P. and Morris, K.B. (1995). Automated laboratory testing for soil/water characteristic curves. *Proceedings of the First International Conference on Unsaturated Soils*, 2, 547-552.
- Reeves, G.M., Sims, I. and Cripps, J.C. (2006). *Clay materials used in construction*. London: The Geological Society.
- Richards, B.G. (1965). *Measurement of the free energy of soil moisture by the psychrometric technique using thermistors*. London: Butterworth and Company Ltd.
- Ridley, A.M. (1995). Discussion on laboratory filter paper suction measurements by Houston et al. *Geotechnical Testing Journal*, 18(3), 391-396.
- Ridley, A.M. and Burland, J.B. (1993). A new instrument for the measurement of soil moisture suction. *Géotechnique*, 43(2), 321-324.
- Robinson, Jr.G.R., Lesure, F.G., Marlowe, J.I., Foley, N.K. and Clark, S.H. (1992). *Bedrock geology and mineral resources of the Knoxville 1° x 2° quadrangle, Tennessee, North Carolina, and South Carolina*. US: Geological Survey Bulletin.
- Romero E. (1999). *Characterisation and thermo-hydromechanical behaviour of unsaturated Boom clay: an experimental study*. Ph.D. Thesis. University Catalunya, Barcelona.
- Romero, E. (2001). Controlled-suction techniques. *Proceedings of the 4th National Brazilian Symposium on Unsaturated Soils*, pp. 535-542.
- Roxburgh, I.S. (1987). *Geology of high-level nuclear waste disposal*. New York: Springer Science and Business Media.

- Saarenketo, T. (1998). Electrical properties of water in clay and silty soils. *Journal of Applied Geophysics*, 40, 73–88.
- Saleh, T.A. and Gupta, V.K. (2016). *Nanomaterial and polymer membranes: synthesis, characterization, and applications*. USA: Elsevier.
- Sangrey, D.A. and Mitchell, R.J. (1976). Soil specimen preparation for laboratory testing. *Soil Specimen Preparation for Laboratory Testing, Symposium, 1975, Montreal, Canada*, 599, 340-341.
- Santamarina, J.C., Klein, K.A., Wang, Y.H. and Prencke, E. (2002). Specific surface: determination and relevance. *Canadian Geotechnical Journal*, 39(1), 233-241.
- Sarimah, M., Radzuan, J., Samsuri, A. and Osman, A.M. (2000). Properties study of a local bentonite as an additive in oil and gas industry. *Proceedings Advances in Malaysian Energy Research Conference, Uitm, Shah Alam*, pp. 14-17.
- Sasanian, S. (2011). *The behaviour of cement stabilized clay at high water contents*. Ph.D. Thesis. University of Western Ontario, Canada.
- Schnecker, J., Wild, B., Hofhansl, F., Alves, R.J.E., Bárta, J., Čapek, P., Hofer, A. et al. (2014). Effects of soil organic matter properties and microbial community composition on enzyme activities in cryoturbated arctic soils. *PLoS One*, 9(4), e94076:1- e94076:10.
- Schofield, R.K. (1935). The pF of the water in soil. *Transactions of 3rd International Congress of Soil Science*, 2, 37-48.
- Sellin, P. and Leupin, O.X. (2013). The use of clay as an engineered barrier in radioactive-waste management—a review. *Clays and Clay Minerals*, 61(6), 477-498.
- Sharma, R.R. and Chellam, S. (2005). Temperature effects on the morphology of porous thin film composite nanofiltration membranes. *Environmental Science and Technology*, 39(13), 5022-5030.
- Shen, M.F., Tan, X.H., Xin, Z.Y., Xie, Y. and Xu, Q. (2013). Laboratory research of soil water characteristic curve by osmotic method and filter paper method. *Electronic Journal of Geotechnical Engineering*, 18, 5422-5434.
- Sillers, W.S., Fredlund, D.G. and Zakerzadeh, N. (2001). Mathematical attributes of some soil-water characteristic curve models. In *Unsaturated soil concepts and their application in geotechnical practice*. Netherlands: Springer.
- Singer, J.K., Anderson, J.B., Ledbetter, M.T., McCave, I.N., Jones, K.P.N. and Wright, R. (1988). An assessment of analytical techniques for the size analysis of fine-grained sediments. *Journal of Sedimentary Petrology*, 58(3), 534-543.

- Slatter, E.E., Jungnickel, C.A., Smith, D.W. and Allman, M.A. (2000). Investigation of suction generation in apparatus employing osmotic methods. In *Unsaturated soils for Asia*. Rotterdam: Balkema.
- Sorenson, T.S. (1999). *Surface chemistry and electrochemistry of membranes* (Vol. 79). New York: CRC Press.
- Sperazza, M., Moore, J.N. and Hendrix, M.S. (2004). High-resolution particle size analysis of naturally occurring very fine-grained sediment through laser diffractometry: research methods papers. *Journal of Sedimentary Research*, 74(5), 736-743.
- Stutz, E., Kahr, G. and Defago, G. (1989). Clays involved in suppression of tobacco black rot by a strain of *Pseudomonas fluorescens*. *Soil Biology and Biochemistry*, 21, 361-366.
- Sun, W., Sun, D.A., Fang, L. and Liu, S. (2014). Soil-water characteristics of Gaomiaozi bentonite by vapour equilibrium technique. *Journal of Rock Mechanics and Geotechnical Engineering*, 6(1), 48-54.
- Suraj De Silva, G.P.R. (1987). *Experimental study of behavior of an unsaturated silt under controlled suction*. Ph.D Thesis. National School of Bridges and Road, Paris.
- Syers, J.K., Campbell, A.S. and Walker, T.W. (1970). Contribution of organic carbon and clay to cation exchange capacity in a chronosequence of sandy soils. *Plant and Soil*, 33, 104-112.
- Tahir, S., Musta, B. and Rahim, I. (2010). Geological heritage features of Tawau volcanic sequence, Sabah. *Bulletin of the Geological Society of Malaysia*, 56, 79-85.
- Tang, G.X. (1999). *Suction characteristics and elastic-plastic modelling of unsaturated sand bentonite mixture*. Ph.D. Thesis. University of Manitoba, Canada.
- Tang, A.M. and Cui Y.J. (2005). Controlling suction by the vapour equilibrium technique at different temperatures and its application in determining the water retention properties of MX80 clay. *Canadian Geotechnical Journal*, 42(1), 287-296.
- Tang, G.X., Graham, J. and Wan, A.W.L. (1998) On yielding behaviour of an unsaturated sand-bentonite mixture. *Proceedings of the 2nd International Conference on Unsaturated Soils*, 1, 149–154.
- Tarantino, A., Gallipoli, D., Augarde, C.E., De Gennaro, V., Gomez, R., Laloui, L., Péron, H. et al. (2011). Benchmark of experimental techniques for measuring and controlling suction. *Geotechnique*, 61(4), 303-312
- Tarantino, A. and Mongiovi, L. (2000). A study of the efficiency of semi-permeable membranes in controlling soil matrix suction using the osmotic technique.

Proceedings of the Asian Conference on Unsaturated Soils UNSAT-Asia 2000, pp. 303-308.

- Tchillingarian, G. (1952). Study of the dispersing agents. *Journal of Sedimentary Petrology*, 22(4), 229-233.
- Theng, B.K.G. (1982). Clay-polymer interactions: summary and perspectives. *Clays and Clay Minerals*, 30(1), 1-10.
- Theng, B.K.G. and Orchard, V.A. (1995). *Interactions of clays with microorganisms and bacterial survival in soil: a physicochemical perspective*. Boca Raton: CRC/Lewis Publishers.
- Thewlis, J. (1962). *Encyclopaedic dictionary of physics* (Vol. 6). Oxford: Pergamon Press.
- Thomas, H.R., Cleall, P.J. and Seetharam, S.C. (2002). Numerical modelling of the thermalhydraulic-chemical-mechanical behaviour of unsaturated clay. In *Environmental geomechanics*. Switzerland: FPF Press.
- Toll, D.G. (2012). The behaviour of unsaturated soils. In *A handbook of tropical residual soil engineering*. London: Taylor and Francis.
- Tomita, K., Tateyama, H. and Oba, N. (1970). Formation of vermiculite and kaolin mineral from hornblende. *The Journal of the Japanese Association of Mineralogists, Petrologists and Economic Geologists*, 64(2), 64-71.
- Tripathy, S., Elgabu, H. and Thomas, H. (2014a). Soil-water characteristic curves from various laboratory techniques. *Unsaturated Soils: Research & Applications*, pp. 1701-1707.
- Tripathy, S., Mohd Tadza, M.Y. and Thomas, H.R. (2011). On the intrusion of polyethylene glycol during osmotic tests. *Geotechnique Letters*, 1, 47-51.
- Tripathy, S., Mohd Tadza, M.Y. and Thomas, H.R. (2014b). Soil-water characteristic curves of clays. *Canadian Geotechnical Journal*, 51(8), 869-883.
- Tripathy, S. and Rees, S.W. (2013). Suction of some polyethylene glycols commonly used for unsaturated soil testing. *Geotechnical Testing Journal*, 36(5), 768-780.
- Tripathy, S. and Schanz, T. (2007). Compressibility behaviour of clays at large pressures. *Canadian Geotechnical Journal*, 44, 355-362.
- Tripathy, S., Thomas, H.R. and Bag, R. (2015). Geoenvironmental application of bentonites in underground disposal of nuclear waste: characterization and laboratory tests. *Journal of Hazardous, Toxic, and Radioactive Waste*, 21(1), D4015002:1- D4015002:12.

- Tylkowski, B. and Tsibranska, I. (2015). Overview of main techniques used for membrane characterization. *Journal of Chemical Technology and Metallurgy*, 50(1), 3-12.
- van Olphen, H. (1977). *An introduction to clay colloid chemistry: for clay technologists, geologists, and soil scientists*. New York: Interscience.
- van Olphen, H. and Fripiar, J.J. (1981). Data handbook for clay materials and other non-metallic minerals. *Soil Science*, 131(1), 62.
- Vanapalli, S.K., Fredlund, D.G. and Pufahl, D.E. (1996a). The relationship between the soil-water characteristic curve and the unsaturated shear strength of a compacted glacial till. *ASTM Geotechnical Testing Journal*, 19(2), 259-268.
- Vanapalli, S.K., Fredlund, D.G., Pufahl, D.E. and Clifton, A.W. (1996b). Model for the prediction of shear strength with respect to soil suction. *Canadian Geotechnical Journal*, 33, 379-392.
- Verwey, E.J.W. and Overbeek, J.T.G. (1948). *Theory of the stability of the lyophobic colloids*. Amsterdam: Elsevier.
- Villar, M.V. and Lloret, A. (2008). Influence of dry density and water content on the swelling of a compacted bentonite. *Applied Clay Science*, 39(1), 38-49.
- Wang, J., Su, R., Chen, W., Guo, Y., Jin, Y., Wen, Z. and Liu, Y. (2006). Deep geological disposal of high-level radioactive wastes in China. *Chinese Journal of Rock Mechanics and Engineering*, 25(4), 649-658.
- Wang, L., Dumont, R.S. and Dickson, J.M. (2012). Nonequilibrium molecular dynamics simulation of water transport through carbon nanotube membranes at low pressure. *The Journal of Chemical Physics*, 137(4), 044102:1-044102:14.
- Wei, W., Xia, S., Liu, G., Gu, X., Jin, W. and Xu, N. (2010). Interfacial adhesion between polymer separation layer and ceramic support for composite membrane. *AIChE Journal*, 56(6), 1584-1592.
- Williams, J. and Shaykewich, C.F. (1969). An evaluation of polyethylene glycol (PEG) 6000 and PEG 20,000 in the osmotic control of soil water matric potential. *Canadian Journal of Soil Science*, 49(3), 397-401.
- Woods, R.J. and Pikaev, A.K. (1994). *Applied radiation chemistry: radiation processing*. Canada: John Wiley and Sons.
- Wypych, G. (2016). *Handbook of fillers*. Canada: ChemTec Publishing.
- Wyss, M. (2012). *Rock friction and earthquake prediction* (Vol. 6). Switzerland: Birkhäuser.

- Yang, N. and Barbour, S.L. (1992). The impact of soil structure and confining stress on the hydraulic conductivity of clays in brine environments. *Canadian Geotechnical Journal*, 29(5), 730-739.
- Yang, Q., Hu, Y.J. and Xue, L. (2011). Back-propagation model for nanofiltration process simulation in pesticide wastewater treatment. In *Advanced Materials Research* (Vol. 168). Switzerland: Trans Tech Publications.
- Yang, W., Zheng, Y. and Zaoui, A. (2015). Swelling and diffusion behaviour of Na-vermiculite at different hydrated states. *Solid State Ionics*, 282, 13-17.
- Yong, R.N., Mohamed A.M.O. and Warkentin, B.P. (1992). *Principles of contaminant transport in soils*. New York: Elsevier Scientific Publishing Co.
- Yong, R.N., Nakano, M. and Pusch, R. (2012). *Environmental soil properties and behaviour*. New York: CRC Press.
- Yong, R.N., Pusch, R. and Nakano, M. (2009). *Containment of high-level radioactive and hazardous solid wastes with clay barriers*. London: CRC Press.
- Yoon, S.H. (2015). *Membrane bioreactor processes: principles and applications*. New York: CRC Press.
- Yuan, S., Liu, X. and Buzzi, O. (2016). Calibration of a coupled model to predict the magnitude of suction generated by osmotic technique with PES membranes and temperature effect. *Geotechnical Testing Journal*, 40(1), 144-149.
- Yukselen, Y. and Kaya, A. (2006). Comparison of methods for determining specific surface area of soils. *Journal of Geotechnical and Geoenvironmental Engineering*, 132(7), 931-936.
- Yukselen-Aksoy, Y., Kaya, A., and Ören, A.H. (2008). Seawater effect on consistency limits and compressibility characteristics of clays. *Engineering Geology*, 102(1), 54-61.
- Zborowski, M., Malchesky, P.S., Jan, T.F. and Hall, G.S. (1992). Quantitative separation of bacteria in saline solution using lanthanide Er (III) and a magnetic field. *Microbiology*, 138(1), 63-68.
- Zemlyanukhin, V.I., Kuznetsov, Y.V., Lazarev, L.N., Lyubtsev, R.I. and Shashukov, E.A. (1979). Clay-phosphate ceramics and vitromets: alternatives to monolithic high level waste glass products. In *Scientific basis for nuclear waste management*. USA: Springer.
- Zhang, X.C. and Norton, L.D. (2002). Effect of exchangeable Mg on saturated hydraulic conductivity, disaggregation and clay dispersion of disturbed soils. *Journal of Hydrology*, 260(1), 194-205.

- Zhang, Y., Xiao, C., Liu, E., Du, Q., Wang, X. and Yu, H. (2006). Investigations on the structures and performances of a polypiperazine amide/polysulfone composite membrane. *Desalination*, 191(1), 291-295.
- Zhao, K. (2014). Fabrication of a poly (piperazine-amide)/polysulfone hollow fiber membrane for effective removal of heavy metals in industrial wastewater. *7th International Conference on Biomedical Engineering and Informatics (BMEI 2014)*, pp. 61-65.
- Zhou, C., Hou, Z., Lu, X., Liu, Z., Bian, X., Shi, L. and Li, L. (2010). Effect of molecular weight on structure and performance of ultrafiltration membranes. *Industrial and Engineering Chemistry Research*, 49(20), 9988-9997.
- Zotarelli, L., Dukes, M.D. and Morgan, K.T. (2010). Interpretation of soil moisture content to determine soil field capacity and avoid over-irrigating sandy soils using soil moisture sensors (Technical Report). University of Florida: AE460.
- Zur, B. (1966). Osmotic control of the matric soil water potential : soil-water system. *Soil Science*, 102(6), 394-398.