

## Thermo-electrical performance of PEM fuel cell using Al<sub>2</sub>O<sub>3</sub>nanofluids

*Irnizakaria<sup>a</sup>; W.A.N.W.Mohamed<sup>a</sup>; W.H.Azmi<sup>b</sup>; A.M.I.Mamat<sup>a</sup>; RizalmanMamat<sup>bd</sup>;  
W.R.W.Daud<sup>c</sup>*

<sup>a</sup> Faculty of Mechanical Engineering, Universiti Teknologi Mara (UiTM), 40450 Shah Alam, Selangor, Malaysia

<sup>b</sup> Faculty of Mechanical Engineering, Universiti Malaysia Pahang, 26600 Pekan, Pahang, Malaysia

<sup>c</sup> Fuel Cell Institute, Universiti Kebangsaan Malaysia, 43600 Bangi, Selangor, Malaysia

<sup>d</sup> Faculty of Bioengineering and Technology, Universiti Malaysia Kelantan, 17600 Jeli, Kelantan, Malaysia

### ABSTRACT

Nanofluid adoption as an alternative coolant for Proton Exchange Membrane (PEM) fuel cell is a new embarkation which hybridizes the nanofluids and PEM fuel cell studies. In this paper, findings on the thermo-electrical performance of a liquid-cooled PEM fuel cell with the adoption of Al<sub>2</sub>O<sub>3</sub> nanofluids were established. Thermo-physical properties of 0.1, 0.3 and 0.5% volume concentration of Al<sub>2</sub>O<sub>3</sub> nanoparticles dispersed in water and water: Ethylene glycol (EG) mixtures of 60:40 were measured and then adopted in PEM fuel cell as cooling medium. The result shows that the cooling rate improved up to 187% with the addition of 0.5% volume concentration of Al<sub>2</sub>O<sub>3</sub> nanofluids to the base fluid of water. This is due to the excellent thermal conductivity property of nanofluids as compared to the base fluid. However, there was a penalty of higher pressure drop and voltage drop experienced. Thermo electrical ratio (TER) and Advantage ratio (AR) were then established to evaluate the feasibility of Al<sub>2</sub>O<sub>3</sub> nanofluid adoption in PEM fuel cells in terms of both electrical and thermo-fluid performance considering all aspects including heat transfer enhancement, fluid flow and PEM fuel cell performance. Upon analysis of these two ratios, 0.1% volume concentration of Al<sub>2</sub>O<sub>3</sub> dispersed in water shows to be the most feasible nanofluid for adoption in a liquid-cooled PEM fuel cell.

### KEYWORDS:

Nanofluids; Heat transfer; PEM fuel cell; Thermo-electrical ratio; Advantage ratio