

UNIVERSITI MALAYSIA PAHANG

BORANG PENGESAHAN STATUS TESIS *

JUDUL: MATHEMATICAL MODELING TO PREDICT SURFACE ROUGHNESS IN MILLING PROCESS

SESI PENGAJIAN: 2008/2009

Saya,

GAN SIN YI

mengaku membenarkan tesis Sarjana Muda ini disimpan di perpustakaan dengan syarat-syarat kegunaan seperti berikut:

1. Tesis ini adalah hak milik Universiti Malaysia Pahang (UMP).
2. Perpustakaan dibenarkan membuat salinan untuk tujuan pengajian sahaja.
3. Perpustakaan dibenarkan membuat salinan tesis ini sebagai bahan pertukaran antara institusi pengajian tinggi.
4. **Sila tandakan (✓)

SULIT

(Mengandungi maklumat yang berdarjah keselamatan atau kepentingan Malaysia seperti yang termaktub di dalam AKTA RAHSIA RASMI 1972)

TERHAD

(Mengandungi maklumat TERHAD yang telah ditentukan oleh organisasi / badan di mana penyelidikan dijalankan)

TIDAK TERHAD

Disahkan oleh:

(TANDATANGAN PENULIS)

(TANDATANGAN PENYELIA)

MOHD FADZIL FAISAE AB RASHID

(Nama Penyelia)

Tarikh: **14 NOVEMBER 2008**

Tarikh: **14 NOVEMBER 2008**

CATATAN: ** Jika tesis ini SULIT atau TERHAD, sila lampirkan surat daripada pihak berkuasa/organisasi berkenaan dengan menyatakan sekali tempoh tesis ini perlu dikelaskan sebagai SULIT atau TERHAD.

- ♦ Tesis dimaksudkan sebagai tesis bagi Ijazah Doktor Falsafah dan Sarjana secara Penyelidikan, atau disertasi bagi pengajian secara kerja kursus dan penyelidikan, atau Laporan Projek Sarjana Muda (PSM).

MATHEMATICAL MODELING TO PREDICT SURFACE ROUGHNESS IN
MILLING PROCESS

GAN SIN YI

A report submitted in partial fulfilment of the requirements
for the award of the degree of
Bachelor of Mechanical Engineering and Manufacturing

Faculty of Mechanical Engineering
UNIVERSITI MALAYSIA PAHANG

NOVEMBER 2008

TABLE OF CONTENTS

	Page
SUPERVISOR'S DECLARATION	ii
STUDENT'S DECLARATION	iii
DEDICATION	iv
ACKNOWLEDGEMENTS	v
ABSTRACT	vi
ABSTRAK	vii
TABLE OF CONTENTS	viii
LIST OF TABLES	xi
LIST OF FIGURES	xii
LIST OF ABBREVIATIONS & SYMBOLS	xiii

CHAPTER 1 INTRODUCTION

1.1	Introduction on the Research	1
1.2	Problem Statement	2
1.3	Objectives	3
1.4	Scope of Project	3

CHAPTER 2 LITERATURE REVIEW

2.1	Introduction	4
2.2	Milling Process	4
2.2.1	CNC Milling Fanuc α-T14tE	6
2.2.2	Importance of Modeling Process	9
2.2.3	Importance of Predict Surface Roughness	10

2.3	Previous Research on Method and Parameter for Surface Roughness Prediction in Milling Process	11
2.4	Multiple Regression Analysis	
2.4.1	Introduction	17
2.4.2	Assumptions Underlying Regression	18
2.4.3	Assumptions about the Error Term	19
2.4.4	Estimation of Parameters β_0 and β_1	20
2.5	Analysis of Variance(ANOVA)	
2.5.1	Introduction	24
2.5.2	ANOVA Summary Table	25

CHAPTER 3 METHODOLOGY

3.1	Introduction	26
3.2	Flow Chart for Project Final Year I & II	26
3.3	Experiment Design	28
3.4	Experiment Procedure	30
3.5	Data Analysis	33

CHAPTER 4 RESULTS AND DISCUSSION

4.1	Introduction	39
4.2	Experimental Results	39
4.3	Data Analysis	
4.3.1	Stepwise method	41
4.3.2	Adjusted R^2	45
4.4	ANOVA Test	48
4.5	Average Percentage Deviation and Accuracy of the Model	
4.5.1	Percentage variation of testing data set	49
4.5.1.1	Sample calculation for testing data set	50
4.5.2	Percentage variation of training data set	52
4.5.2.1	Sample calculation for training data set	54

4.6	Relationship Between Actual Surface Roughness and Predicted Surface Roughness	56
-----	---	----

CHAPTER 5 CONCLUSION AND RECOMMENDATIONS

5.1	Introduction	60
5.2	Conclusions	61
5.3	Recommendations	62

REFERENCES	63
-------------------	----

APPENDICES

A	Data Collection	65
	A.1 Data 1	66
	A.2 Data 2	67
B	Figures	68
C	Measuring Results	71

LIST OF TABLES

Table No.	Page
2.1 Characteristic of part for FANUC CNC Milling	6
2.2 Method and parameter research on past studies	15
2.3 Data on Size and Price	22
2.4 ANOVA summary table	25
3.1 Experimental design for prediction method	29
3.2 Training data set	34
3.3 Testing data set	36
4.1 Data collected from milling process	40
4.2 60 Training data set	42
4.3 Variable entered/removed	44
4.4 Model summary by stepwise method	45
4.5 Variable included in the Multiple Regression Method	46
4.6 ANOVA table	48
4.7 Percentage Deviation of Testing data sets	49
4.8 Percentage deviation of training data set	52
4.9 Actual Ra and predicted Ra	56

LIST OF FIGURES

Figure No.		Page
2.1	Milling Process	5
2.2	CNC Milling Fanuc α-T14lE	6
3.1	Flow Chart for Project Final Year I	27
3.2	Turrent	30
3.3	Mounting workpiece in the vise	31
3.4	Coolant	31
3.5	Compact operator's panel and 10.4 color LCD	32
4.1	Scatter plot of the actual Ra and the predicted Ra of the multiple regression prediction model	59

LIST OF ABBREVIATIONS & SYMBOLS

ANOVA	Analysis of Variance
CNC	Computer Numerical Control
β	Regression coefficients
ϕ_i	Percentage deviation
$\bar{\phi}$	Average percentage deviation
$\hat{\mu}_{y/x}$	Estimate of the mean of y for any given x

ABSTRACT

Surface roughness (R_a) is one of the most important requirements in machining process. In order to obtain better surface roughness, the proper setting of cutting parameters is crucial before the process take place. This research presents the development of mathematical model for surface roughness prediction before milling process in order to evaluate the fitness of machining parameters; spindle speed, feed rate and depth of cut. 84 samples were run in this study by using FANUC CNC Milling α -T14iE. Those samples were randomly divided into two data sets- the training sets ($m=60$) and testing sets($m=24$). ANOVA analysis showed that at least one of the population regression coefficients was not zero. Multiple Regression Method was used to determine the correlation between a criterion variable and a combination of predictor variables. It was established that the surface roughness is most influenced by the feed rate. By using Multiple Regression Method equation, the average percentage deviation of the testing set was 9.8% and 9.7% for training data set. This showed that the statistical model could predict the surface roughness with about 90.2% accuracy of the testing data set and 90.3% accuracy of the training data set.

ABSTRAK

Kekasaran permukaan merupakan keperluan yang paling penting bagi penggunaan mesin. Bagi mendapatkan kekasaran permukaan yang baik, parameter mesin yang sesuai adalah sangat penting sebelum menjalankan sebarang proses. Tujuan kajian ini adalah untuk menghasilkan satu persamaan matematik yang dapat meramalkan kekasaran permukaan sebelum proses penggilingan. Kelajuan mata alat, kadar dan kedalaman pemotongan bahan merupakan pembolehubah dalam kajian ini. 84 sampel telah dijalankan dalam kajian ini dengan menggunakan FANUC CNC Milling α -T14iE. Sampel tersebut telah diagih secara rawak kepada 2 set data, iaitu set latihan($m=60$) dan set ujian($m=24$). Analysis ANOVA menunjukkan bahawa sekurang-kurangnya satu koefisien regresi daripada populasi bukan sifar. Kaedah regresi berganda digunakan untuk menentukan hubung kait diantara satu pembolehubah dengan kombinasi pembolehubah yang lain. Kaedah tersebut telah menunjukkan bahawa kadar pemotongan adalah pembolehubah yang paling mempengaruhi kekasaran permukaan. Dari persamaan yang dihasilkan oleh kaedah regresi berganda, purata peratusan ketidaktepatan bagi set ujian adalah 9.8% dan 9.7% untuk set latihan. Ini menunjukkan bahawa model statistik dapat meramalkan kekasaran permukaan set ujian dengan 90.2% ketepatan dan 90.3% ketepatan untuk set latihan.

CHAPTER 1

INTRODUCTION

1.1 INTRODUCTION ON THE RESEARCH

To realize full automation in machining, computer numerically controlled (CNC) machine tools have been implemented during the past decades. CNC machine tools require less operator input, provide greater improvements in productivity, and increase the quality of the machined part. End milling is the most common metal removal operation encountered. It is widely used to mate with other part in die, aerospace, automotive, and machinery design as well as in manufacturing industries (Julie Z.Zhang et al., 2006).

Surface roughness is an important measure of the technological quality of a product and a factor that greatly influences manufacturing cost. The quality of the surface plays a very important role in the performance of milling as a good-quality milled surface significantly improves fatigue strength, corrosion resistance, or creep life. (Dr. Mike S.Lou et al., 1999) In addition, surface roughness also affects surface friction, light reflection, ability of holding a lubricant, electrical and thermal contact resistance. Consequently, the desired surface roughness value is usually specified for an individual part, and specific processes are selected in order to achieve the specified finish. Surface specification can also be a good reference point in determining the stability of a production process, because the stability of the machine is contingent on the quality of the operating part (Oğuz çolak et al., 2005).

This research investigates to predicting surface roughness by using multiple regression prediction models. Three milling parameters have been selected, spindle speed, feed rate and depth of cut.

1.2 PROBLEM STATEMENT

In manufacturing industries, manufacturers focused on the quality and productivity of the product. To increase the productivity of the product, computer numerically machine tools have been implemented during the past decades. Surface roughness is one of the most important parameters to determine the quality of product. The mechanism behind the formation of surface roughness is very dynamic, complicated, and process dependent. Several factors will influence the final surface roughness in a CNC milling operations such as controllable factors (spindle speed, feed rate and depth of cut) and uncontrollable factors (tool geometry and material properties of both tool and workpiece). Some of the machine operator using ‘trial and error’ method to set-up milling machine cutting conditions (Julie Z.Zhang et al., 2006). This method is not effective and efficient and the achievement of a desirable value is a repetitive and empirical process that can be very time consuming.

In order to solve the problem, develop one surface prediction technique which is termed the multiple regression prediction models to optimize the cutting conditions. This method can find the best conditions required for the machining independent variables such as speed, feed and depth of cut that would result in the best machining response. Thus, manufacturers can improve the quality and productivity of the product with minimum cost and time.

1.3 OBJECTIVES

The objectives of this study are to:

- (i) Develop a mathematical model for predicted surface roughness in milling process.
- (ii) Compare the predicted surface roughness and the actual surface roughness.
(Average percentage deviation less than 10%)

1.4 SCOPE OF PROJECT

The experiment is performed by using a FANUC CNC Milling α-T14iE. The workpiece tested is 6061 Aluminum 400mmx100mmx50mm. The end-milling and four-flute high speed steel is chosen as the machining operation and cutting tool. The diameter of the tool is D=10mm. 84 specimens are run in this experiment. 60 specimens are used to build a prediction model and the testing set contain 24 specimens. Spindle speed, feed rate and depth of cut are selected as consider parameters. Four levels of spindle speed- 750, 1000, 1250, and 1500 revolutions per minute (rpm), seven levels of feed rate- 152, 229, 305, 380, 457, 515, 588 millimeter per minute (mmpm), and three levels of depth of cut – 0.25, 0.76, 1.27 millimeter (mm) are determined.

REFERENCES

- Babur Ozcelik & Mahmut Bayramoglu. 2005. *The statistical modeling of surface roughness in high-speed flat end milling.*
- Dr. Mike S.Lou, Dr. Joseph C. Chen & Dr. Caleb M.li. 1999. *Surface Roughness Prediction Technique For CNC End-Milling.*
- Gall, M., Borg, W.R. & Gall, J.P. 1996. Educational Research, Sixth Edition, Longman, New York.
- Hasan Oktem, Tuncay Erzurumlu & Fehmi Erzincanli. 2005. *Prediction of roughness with roughness with Genetic Programming.*
- Hun-Keun Chang, Jin-Hyun Kim, II Hae Kim, Dong Younf Jang & Dong Chul Han. 2006. *In-process surface roughness prediction using displacement signals from spindle motion.*
- Huynh, V.M. & Fan, Y. 1992. *Surface texture measurement and characterization with applications to machine tool monitoring.* The international Journal of advanced manufacturing technology.
- Julie Z.Zhang, Joseph C.Chen & E.Daniel Kirby. 2006. *Surface Roughness optimization in an end milling operation using the Taguchi design method.*
- Kuang-Hua Fuh & Chih-Fu Wu. 1994. *A proposed statistical model for surface quality prediction in end-milling of Al Alloy*

M. Brezocnik, M. Kovacic & M. Ficko. 2004. *Prediction of minimum surface roughness in end milling mold parts using neural network and Genetic Algorithm.*

Mandara D. Savage & Joseph C. Chen. 2001. *Multiple regression-based multilevel in-process surface roughness recognition system in milling operations.*

Mr. John L. Yang & Dr. Joseph C. Chen. 2001., *A systematic approach for identifying optimum surface roughness performance in end-milling operations.*

Oğuz çolak, Cahit Kurbanoğlu & M. Cengiz Kayacan. 2005. *Milling surface roghness prediction using evolutionary programming methods.*

W. Wang, S.H, Kweon & S.H. Yang. 2005. *A study on roughness of the micro-end-milled surface produce by a miniatured machine tool.*