

Prediction of emissions and performance of a gasoline engine running with fusel oil–gasoline blends using response surface methodology

Ahmed N. Abdalla^a, Hai Tao^b, Salem A. Bagaber^c, Obed M. Ali^d, Mohammed Kamil^e, Xiao Ma^f, Omar I. Awad^f

^aFaculty of Electronic and Information Engineering, Huaiyin Institute of Technology, China

^bBaoji University of Arts and Sciences, Shaanxi, China

^cFaculty of Manufacturing Engineering, Universiti Malaysia Pahang, 26600 Pekan, Malaysia

^dRenewable Energy Research Unit, Northern Technical University, Kirkuk, Iraq

^eDepartment of Mechanical and Nuclear Engineering, University of Sharjah, United Arab Emirates

^fState Key Laboratory of Automotive Safety and Energy, Tsinghua University, Beijing, China

ABSTRACT

In this study, the engine performance and emissions of gasoline were examined by applying a response surface methodology (RSM) optimisation approach. Fusel oil–gasoline blends were used to operate an engine at various speeds and loads. The optimal fusel oil–gasoline blend mix ratio was determined to minimise fuel consumption and nitrogen oxide and hydrocarbon emissions and to maximise the brake power (BP). The results demonstrate that the engine load and speed have a significant effect on performance and emissions. In addition, the blended fuels (F10 and F20) were shown to reduce NO_x emissions. Furthermore, insignificant effects on engine performance were observed for fusel oil compared with pure gasoline. The design of experiments (DoE) method, which is a statistical technique, indicated that F20 was the optimum blend ratio among the three studied fuels, based on the RSM. The optimal parameters were a load corresponding to 60% of the wide open throttle engine load and an engine speed of 4500 rpm for the F20 blend, resulting in a high desirability value of 0.852 for the test engine, with values of 67.6 kW, 235.17 g/kW.h, 0.118%vol, and 1931.4 ppm for the BP, brake-specific fuel consumption, CO emission, and NO_x emission, respectively.

KEYWORDS

Design of experiments; Response surface methodology; Fusel oil; Spark-ignition engine; Performance; Emissions

REFERENCES

1. P. Kwanchareon, A. Luengnaruemitchai, S. Jai-In
Solubility of a diesel–biodiesel–ethanol blend, its fuel properties, and its emission characteristics from diesel engine
Fuel, 86 (7) (2007), pp. 1053-1061
[\[Google Scholar\]](#)
2. I. Arto, I. Capellán-Pérez, R. Lago, G. Bueno, R. Bermejo
The energy requirements of a developed world
Energy Sustain Dev, 33 (2016), pp. 1-13
[\[Google Scholar\]](#)
3. I. Yusri, R. Mamat, W. Azmi, G. Najafi, N. Sidik, O.I. Awad
Experimental investigation of combustion, emissions and thermal balance of secondary butyl alcohol-gasoline blends in a spark ignition engine
Energy Convers Manage, 123 (2016), pp. 1-14
[\[Google Scholar\]](#)
4. T. Chuah, A. Wan Azlina, Y. Robiah, R. Omar
Biomass as the renewable energy sources in Malaysia: an overview
Int J Green Energy, 3 (3) (2006), pp. 323-346
[\[Google Scholar\]](#)
5. O.I. Awad, O.M. Ali, R. Mamat, A.A. Abdullah, G. Najafi, M.K.Kamarulzaman, *et al.*
Using fusel oil as a blend in gasoline to improve SI engine efficiencies: a comprehensive review
Renew Sustain Energy Rev, 69 (2017), pp. 1232-1242
[\[Google Scholar\]](#)