

Vibration analysis of hybrid-reinforced unsaturated polyester composites

M. H. M. Hamdan¹, J. P. Siregar¹, S. M. Sapuan², C. Tezara³, Z. M. Hafizi⁴, M. R. M. Rejab¹, D. Bachtiar¹, J. Jamiluddin¹

¹Structural Materials and Degradation Focus Group, Faculty of Mechanical and Manufacturing Engineering, Universiti Malaysia Pahang, Pahang, Malaysia

²Department of Mechanical and Manufacturing Engineering, Universiti Putra Malaysia, Selangor, Malaysia

³Department of Mechanical Engineering, Faculty of Engineering and Quantity Surveying, INTI International University, Negeri Sembilan, Malaysia

⁴Advanced Structural Integrity and Vibration Research (ASIVR), Faculty of Mechanical and Manufacturing Engineering, Universiti Malaysia Pahang, Pahang, Malaysia

ABSTRACT

This chapter reviews recent work on natural fiber–reinforced polyester hybrid composites. The vibration behavior of jute/roselle fiber–reinforced unsaturated polyester hybrid composites was also studied. All composite specimens were fabricated with the hand lay-up method, but with different layering sizes and sequences. A total of 12 types of jute (J)–roselle (S) woven fiber–reinforced unsaturated polyester resin hybrid composites were prepared, namely JJ, JS, SJ, SS, JJJ, SSS, SSJ, SJS, JSS, SJJ, JJS, and JSJ. The natural frequencies and damping properties obtained from experimental and numerical analyses through ANSYS finite element software were compared. The results showed that the varying layering sizes and layering sequences on the hybrid composites produced a significant effect on the natural frequency and damping ratio. Nevertheless, a high percentage of error (>20) was produced by the three-layer composites based on the numerical analysis.

KEYWORDS

Natural fiber; Biocomposite; Hybrid composite; Natural frequency; Damping properties

DOI: <https://doi.org/10.1016/B978-0-12-816129-6.00019-3>

ACKNOWLEDGMENT

Special thanks to Universiti Malaysia Pahang for providing laboratory facilities and financial support through a grant (RDU180335).