

Analysis of joint channel estimation and joint data detection in TD-SCDMA systems

Ali K. Marzook^a; A. Ismail^a; B. M. Ali^a; A. Sali^a; Mohannad H. Khalaf^b; S. Khatun^c

^a Department of Computer and Communication Systems Engineering Faculty of Engineering
University Putra Malaysia

^b Computer Engineering Department Basrah University, Iraq

^c Faculty of Computer Systems and Software Engineering University Malaysia Pahang

ABSTRACT

Time Division-Synchronous Code Division Multiple Access (TD-SCDMA) has several attractive characteristics that made it capable of meeting the requirements of G4 systems when applied as a platform directly. Joint detections, the unpaired spectrums with flexible sharing of resources, and some other advanced properties leads TD-SCDMA to achieve high data rate services. In this paper a comprehensive analysis is presented that involve accurate Joint Channel Estimation (JCE) for traditional and enhanced estimators based on two criterions: Least square (LS) & Minimum Mean Square Error (MMSE) at two scenarios of users' movements. In addition to a comprehensive Multi-Users Joint Detection (MUJD) is improved to mitigate Multiple Access Interference (MAI) and Inter-Symbol Interference (ISI) using the following detectors: Matched Filter (MF), Zero Forcing Block Linear Equalizer (ZF-BLE), and Minimum Mean Square Error Block Linear Equalizer (MMSE-BLE) for traditional and enhanced channel estimation criterions. Simulation results showed that equalizers fed by Channel Impulse Response (CIR) optimized according to enhanced LS or MMSE give a better performance to that ones when CIR obtained from traditional LS or MMSE criterion. The using of MMSE give the opportunity to implement adaptive equalizes to cope with fast fading and/or non stationary interference environments.

KEYWORDS:

TD-SDMA system; joint channel estimation (JCE); multi-users joint detection (MUJD)

REFERENCES

1. G. Liu, J. Zhang, P. Zhang, Y. Wang, X. Liu, and S. Li," Evolution map from TD-SCDMA to future B3G TDD", IEEE Communications Magazine, p.p 54-61, march 2006.
2. Sh. Chen, W. Wang, J. Han, G. Liu and Nan Li," Providing VoIP Service over TD-SCDMA HSDPA" IEEE Vehicular technology conference VTC spring 2008, p.p 2066-2070, 2008.
3. Sh. Zhi-yong, Y. Shi-ping, X. Zhen," Design and implementation of radio access link for group call service based on TD-SCDMA network", International Conference on Computer Application and System Modeling (ICCASM 2010),Volume 8, p.p 253-256, 2010.
4. Z. Shi, K. Liao, Sh. Yin and Q. Ou," Design and implementation of the mobile internet of things based on TD-SCDMA network', IEEE International conference on Information theory and information security (ICITIS), p.p 954-957, 2010.
5. F. Yang and Ch. Yan," Design of WSN gateway based on ZigBee and TD", International conference on electronics and information engineering on (ICEIE), volume 2, p.p 76-80, 2010.

