UNIVERSITI MALAYSIA PAHANG

ρεςι αρατιονιός τι	LESIS AND CODY DICHT
Author's Full Name Date of Birth Title	MUHAMMAD QAHRI HARIR BIN MOHD RAPI
	25 FEBRUARY 1994
	MINIMIZING WEAR OF EDM ELECTRODE
	IN MACHINING A HARD MATERIAL
Academic Session	SEM 2 2016/2017
I declared that this thesis i	s classified as:
CONFIDENTIAL	(Contains confidential information under the Official Secret Act 1972)*
RESTRICTED	(Contains restriction information as specified by the organization where research was done)*
OPEN ACCESS	I agree that my thesis to be published as online open access (Full text)
I acknowledge that Univer	sity Malaysia Pahang reserve the right as follows:
1. The Thesis is the Prop	erty of University Malaysia Pahang.
2. The Library of Univer purpose of research or	sity Malaysia Pahang has right to make copies for the nly.
3. The Library has the right	ght to make copies of the thesis for academic exchange.
Certified By: Juffer (Student's Signate	ure) (Supervisor's Signature)
940225-06-561 New IC /Passport Num Date: 8/6/2017	5 DR ZAMZURI BIN HAMEDON ber Name of Supervisor Date: %/6/2017

NOTES : *If the thesis is CONFIDENTIAL or RESTRICTICTED, please attach with the letter from the organization with period and reasons for confidentiality or restriction



SUPERVISOR'S DECLARATION

I hereby declare that I have checked this thesis and in my opinion, this thesis is adequate in terms of scope and quality for the award of the degree of Bachelor of Engineering in Manufacturing Engineering with Honor.

Signature

- Could'

:

Name of supervisor

: DR. ZAMZURI BIN HAMEDON: UMP SENIOR LECTURER

: 8.6.2017

Date

Position

iv



STUDENT'S DECLARATION

I hereby declare that the work in this thesis is my own except for quotation and summaries which have been duly acknowledged. The thesis has not been accepted for any degree and is not concurrently submitted for award of other degree.

Signature

aferta

C

Name

: MUHAMMAD QAHRI HARIR BIN MOHD RAPI

V

ID number

Date

: FA 13032

•

:

8/6/2017



Dedicated to my beloved parents,

MOHD RAPI BIN ISMAIL

NORMAIZA BINTI ABDUL HALIM

My siblings,

My supervisor,

DR ZAMZURI BIN HAMEDON

And all staffs of Universiti Malaysia Pahang

PERPU	ISTAKAAN
UNIVERSITI M	ALAYSIA PAHANG P
No. Perolehan	No. Panggilan
119215	FKP
Tarikh	2017
0 9 AUG 2017	BC.

ACKNOWLEDGEMENT

I grateful and would like to express my sincere gratitude to my supervisor, Dr. Zamzuri Bin Hamedon for his germinal ideas, invaluable guidance, continuous encouragement and constant support in making this research possible. He has always impressed me with his outstanding professional conduct, his strong conviction for science, and his belief that a degree program is only a start of a life-long learning experience. I am very appreciating his consistence support from the first day I applied to graduate program to these concluding moments. I am truly grateful for his forgiveness vision about my training in engineering and science, his tolerance of my naïve mistakes, and also his commitment to my future career. Then, I also sincerely thank for the time spent proofing-reading and correcting my many mistakes.

My sincere thanks also go to all my lab mates and members of the staff of Manufacturing Engineering Department, UMP, who have helped me a lot in many ways and made my stay at UMP pleasant and unforgettable.

I acknowledge my sincere indebtedness and gratitude to my lovely parent for their support, love, dream and sacrifice throughout my life. Special thanks should be given to all my friends, especially Hazirah binti A.Razak. I would like to acknowledge their comments and suggestions, which was crucial for the successful completion of this study.

ABSTRACT

Electrical discharge machining (EDM) is extremely being used in manufacture of aerospace and automotive parts, also used in development of dies and molds by machining and cut the materials that are strong and hard, which impossible to be machined by traditional machining techniques. However, the main problem of EDM is electrode wear which is mainly caused by debris. In this present study, three types of electrode designs were developed for comparison. The electrode with magnet is used to pull the debris and avoid it from accumulates at the bottom of machined area. Holes also being made at the electrode to improve the flows of debris so that it can be pulled straight away to the magnet inside the electrode. Video measuring system will helps in viewing the zoomed image of electrode so that the wear can be see clearer. Also, electronic balance is used to weigh the weight of electrode to know the amount of electrode wear. Finding from this project show that the electrode with magnet and holes will be more helpful in minimizing the wear of the EDM electrode compared to others.

ABSTRAK

Pelepasan elektrik pemesinan (EDM) sangat digunakan dalam pembuatan bahagian aeroangkasa dan automotif, juga digunakan dalam pembangunan acuan dengan pemesinan dan memotong bahan-bahan yang kuat dan keras, yang mustahil untuk dimesin oleh teknik pemesinan tradisional. Walau bagaimanapun, masalah utama EDM adalah memakai elektrod yang sebahagian besarnya disebabkan oleh serpihan. Dalam kajian ini, tiga jenis reka bentuk elektrod akan digunakan untuk perbandingan. Elektrod dengan magnet digunakan untuk menarik serpihan dan mengelakkan dari berkumpul di bahagian bawah kawasan dimesin. Lubang juga dibuat pada elektrod untuk meningkatkan aliran serpihan supaya ia boleh ditarik terus untuk magnet dalam elektrod. Sistem pengukuran video dapat membantu dalam melihat imej elektrod yang dizum supaya elektrod boleh melihat lebih jelas. Juga, penimbang berat elektrodik digunakan untuk menimbang berat elektrod bagi mengetahui jumlah haus elektrod. Apa yang diperolehi daripada projek ini menunjukkan bahawa elektrod EDM berbanding dengan jenis elektrod yang lain.

TABLE OF CONTENTS

			Page
SUP	ERVISOI	R'S DECLARATION	iv
STU	DENT'S	DECLARATION	v
ACH	KNOWLE	DGEMENT	vii
ABS	TRACT		viii
ABS	TRAK		ix
TAE	BLE OF C	ONTENTS	Х
LIST	Г ОГ ТАЕ	BLES	xii
LIST	Г OF FIG	URES	xiii
LIST	Г OF SYN	IBOLS	xiv
LIST	Г OF ABF	BREVIATIONS	XV
CHA	APTER 1	INTRODUCTION	1
1.1	INTROI	DUCTION	1
1.2	PROBL	EM STATEMENT	2
1.3	OBJECT	TIVES	4
1.4	PROJEC	CT SCOPE	4
CHA	APTER 2	LITERATURE REVIEW	5
2.1	INTROI	DUCTION	5
2.2	ELECTI	RICAL DISCHARGE MACHINING (EDM)	5
	2.2.1 2.2.2	EDM DIE SINKING EDM WIRE CUT	7 8
2.3	MATER	RIAL WORKPIECE	9
2.4	EDM EI	LECTRODE	9
2.5	WEAR		11
	2.5.1	ELECTRODE WEAR (EW) IN DIE SINKING	11
2.6	MAGNI	ET	13
2.7	PREVIC	DUS METHODS	14
	2.7.1 2.7.2 2.7.3 2.7.4	COATING POWDER MIXTURE IN DIELECTRIC FLUID ULTRASONIC VIBRATION ROTATIONAL MAGNETIC ASSIST	14 15 15 16
CHA	APTER 3	METHODOLOGY	17
3.1	INTROI	DUCTION	17
3.2	FLOWC	CHART OF PROJECT	18

3.3	ELECTI	RODE MATERIAL	19
3.4	WORKPIECE MATERIAL		
3.5	DESIGNING ELECTRODE		20
3.6	FABRICATION OF ELECTRODE		22
3.7	EDM PROCESS 2		24
3.8	ELECTI	RODE WEAR MEASURING METHOD	26
	3.8.1 3.8.2	EVALUATION METHOD WEIGHING METHOD	26 27
СНА	PTER 4	RESULTS AND DISCUSSION	29
4.1	INTROI	DUCTION	29
4.2	ELECTI	RODE WEAR	29
4.3	EFFECT	OF ELECTRODE WEAR ON MACHINING TIME	42
4.4	EFFECT	OF ELECTRODE WITH MAGNET ON SURFACE TEXTURE	44
СНА	PTER 5	CONCLUSION AND RECOMMENDATION	46
5.1	INTROI	DUCTION	46
5.2	CONCL	USION	46
5.3	RECOM	IMEDATIONS	47
REF	ERENCE	S	50
APP	ENDIX		55

LIST OF TABLES

Table 2.1: Mechanical properties of magnet used	14
Table 3.1: Mechanical properties of copper	19
Table 3.2: Chemical properties of P20 material	20
Table 3.3: Physical properties of P20 material	20
Table 3.4: Specifications of EDM die sinking machine	25
Table 4.1: Wear weights of electrodes before and after machined	37
Table 4.2: Weights loss of electrodes after machined	38
Table 4.3: Electrodes wear percentage	40
Table 4.4: Electrodes 1 (with magnet and holes) weight effects on time taken	42
Table 4.5: Electrodes 2 (with magnet only) weight effects on time taken	43
Table 4.6: Electrodes 3 (without magnet and holes) weight effects on time taken	43

LIST OF FIGURES

Figure 2.1. FDM Working Principle	6
Figure 2.2: EDM Die Sinking	7
Figure 2.3: Wire cut EDM	8
Figure 2.4: EDM Electrodes	10
Figure 2.5: EDM electrode wear types	12
Figure 2.6: Change of electrode due to wear	13
Figure 2.7: Stirrer of powder mixture	15
Figure 2.8: Experiment set up of magnetic assisted EDM	16
Figure 3.1: Flow Chart of project	18
Figure 3.2: Design of electrode with a hole at its center	21
Figure 3.3: Design of electrode 1 with holes at each side	22
Figure 3.4: Makino KE55 EDM milling machine	23
Figure 3.5: Three designs of electrodes	24
Figure 3.6: Mitsubishi EA12D EDM die sinking machine	25
Figure 3.7: Set up of Video measuring system (VMS)	26
Figure 3.8: Process of sample leveling using jig	27
Figure 3.9: Electronic balance	28
Figure 4.1: Initial condition images of electrodes	30
Figure 4.2: Electrodes images after 3mm (1st) depth machining	31
Figure 4.3: Electrodes images after 3mm (2nd) depth machining	32
Figure 4.4: Electrodes images after 3mm (3rd) depth machining	33
Figure 4.5: Electrodes images after 3mm (4th) depth machining	34
Figure 4.6: Electrodes images after 3mm (5th) depth machining	35
Figure 4.7: Electrodes images after 3mm (6th) depth machining	36
Figure 4.8: Graph of electrode weight before and after EDM process	38
Figure 4.9: Graph of electrode weight loss vs number of machining	39
Figure 4.10: Graph of accumulation of electrode weight loss vs number of machine	ning 39
Figure 4.11: Graph of wear percentage (%) vs types of electrode	40
Figure 4.12: Chart of value of electrode weight before and after machined	41
Figure 4.13: Graph of electrode weight (g) against machining time (min)	44
Figure 4.14: Work piece surface texture after EDMed	45

LIST OF SYMBOLS

mm Millimetre % percentage °C Degree Celsius g gram K kelvin μm Micrometre

LIST OF ABBREVIATIONS

EDM	Electrical Discharge Machining
VMS	Video measuring system
EWR	Electrode wear ratio
CNC	computer numerical control
MRR	material removal rate
FCC	face-centred cubic

CHAPTER 1

INTRODUCTION

1.1 INTRODUCTION

Electrical discharge machining (EDM) is a non-conventional process for the production of difficult and hard material workpiece that are problematic to machine by conventional machining processes (Kechagias et al., 2008). A chemist from England, Joseph Priestly, discovered the sparks of electrical discharge are able to caused erosive phenomenon. Then, in 1943, two of Russian scientists were invented the EDM process. At 1980, a computer numerical controlled (CNC) electrical discharge machine has been announced in USA (Choundhary & Jadoun, 2014).

EDM also extremely being used in manufacture of aerospace and automotive parts, also used in development of dies and molds (Kechagias et al., 2008). Electrical discharge machining is widely used to machine and cut materials that are tough, strong and hard, which impossible to be machined by traditional machining techniques. Nevertheless, by discharging of controlled sparks at a small gap between the electrode and workpiece (spark gap), the workpiece material being detached through melting and evaporation processes (Pham et al., 2006).

Besides, that different variation of EDM processes can be categorized regarding to the use of dielectric fluids (Leao & Pashby, 2004). Besides, Hydrocarbon oils, such as kerosene or paraffin, are typically being used in die sinking EDM, while deionized water is applied in wire cut and drilling EDM processes as the conductive dielectric mediums. The functions of dielectric fluid is to wash away the remains of material, known as debris, from the spark gap, and

also as a coolant which lower and maintain the temperature of both materials (Prasanna & Husain, 2016).

On the other hand, the range temperature of the plasma channel at the gap of electrode and workpiece is from 8000°C till 10000°C (Santos et al., 2016). Because of the high temperature of electrical sparks, materials that being eroded not just only workpiece, but also the electrode itself. So, the phenomenon of electrode wear is happened and many of research studies have been done by people around the world in order to find ways to improve and reduce wear of electrode.

Eliminating all electrode wears are difficult and quite impossible due to the thermoelectric process which has very high temperature of electrical discharge sparks. Moreover, wear of electrode will rise proportionally to the path of tool electrode and causing in shape changes and inaccuracies (Song et al., 2013).

As to this, research study is done to develop an EDM machine with magnetic field assist to reduce and lower the electrode wear in for machine hard conductive material.

1.2 PROBLEM STATEMENT

In manufacturing sector, there are some factors that have to give attention as important matters, for examples quality, economy and product efficiency. Electrode wear will gives effects to these three main things of the manufacturing industry companies. This is because when electrode wear occurs, the quality of the electrode is not good as before the wear occurs. There will change in shape and size of the electrodes, leading to not efficiency and low quality of products being made. There will be loss to the companies if their customers are not satisfy with their jobs and then reject the product. Besides, if they decide to solve the problem by making new electrodes, it will also costs them lots of money and time for complicated electrode designs.

2

So, improvement and ways to solve the problem of electrode wear must be done. Actually there were lots of research studies just to reduce wear of electrode in electrical discharge machining (EDM). Based on the previous researches, they still not able to eliminate completely the wear of electrode problem. This is because the wear of electrode occurs due to high temperature of electrical discharge. Other than that, debris also be one of the factors electrode wear to happen.

Debris is the remains of the removal workpiece material that produced in bottom gap between workpiece and electrode. The presence of debris can drastically lower the dielectric fluid breakdown strength (Jia, 2011). As the space is narrow, lots of debris is produced and it is hard to be removed. Debris also can cause increasing of process time as the machine will still try to remove material and attempts to make sure the gap clean and clear. The machining process efficiency and accuracy will be effected if the debris is not being removed in time.

Basically, the accumulation of debris can be cleaned and removed from the spark gap by flushing process (S. F. Miller et al, 2005). Flushing removes debris by blowing the EDM fluid to the workpiece machining area. Other than that, flushing allows the increase of material removal rate (MRR). Unfortunately, the limitation is not all debris being cleared. There still has debris left especially at the bottom of machining area and this will affect the machining efficiency and accuracy of EDM. The inactive pulses such as short circuit will occur because of the remained debris (Teimouri & Baseri, 2012).

This research study focused on improving EDM electrode performance using magnet support at copper electrode.

REFERENCES

Abbas, N. M., Yusoff, N., & Mahmod@wahab, R. (2012). Electrical Discharge Machining (EDM): Practices in Malaysian Industries and Possible Change towards Green Manufacturing. *Procedia Engineering*,41, 1684-1688.

Abdulkareem, S., Khan, A. A., & Konneh, M. (2009). Reducing Electrode Wear Using Cryogenic Cooling during Electrical Discharge Machining. *Advanced Materials Research*,83-86, 672-679.

Arthur, A., Dickens, P. M., & Cobb, R. C. (1996). Using rapid prototyping to produce electrical discharge machining electrodes. *Rapid Prototyping Journal*,2(1), 4-12.

Chiou, A., Tsao, C., & Hsu, C. (2015). A study of the machining characteristics of micro EDM milling and its improvement by electrode coating. *The International Journal of Advanced Manufacturing Technology*, 78(9-12), 1857-1864.

Dhar, N., Kamruzzaman, M., & Ahmed, M. (2006). Effect of minimum quantity lubrication (MQL) on tool wear and surface roughness in turning AISI-4340 steel. *Journal of Materials Processing Technology*, *172*(2), 299-304.

Goswami, A., & Kumar, J. (2017). Trim cut machining and surface integrity analysis of Nimonic 80A alloy using wire cut EDM. *Engineering Science and Technology, an International Journal*,20(1), 175-186.

Choundhary, S., K & Jadoun, R. S. (2014). Current Advanced Research Development of Electric Discharge Machining (EDM): A Review, *Int. J. Res. Advent Technol*, 2(3), 2321–9637.

Ho, K., & Newman, S. (2003). State of the art electrical discharge machining (EDM). *International Journal of Machine Tools and Manufacture*,43(13), 1287-1300.

Jeswani, M. (1979). Dimensional analysis of tool wear in electrical discharge machining. *Wear*, 55(1), 153-161.

Jha, B., Ram, K., & Rao, M. (2011). an overview of technology and research in electrode design and manufacturing in sinking electrical discharge machining, 2(4), 118-130.

Jia, Z. (2011). Statistical Description of Debris Particle Size Distribution in Electrical Discharge Machining. *Chinese Journal of Mechanical Engineering*,24(01), 67.

Kamei, T., Okada, A., & Okamoto, Y. (2016). High-speed Observation of Thin Wire Movement in Fine Wire EDM. *Procedia CIRP*,42, 596-600.

Kechagias, J., Iakovakis, V., Katsanos, M., & Maropoulos, S. (2008). EDM electrode manufacture using rapid tooling: a review. *Journal of Materials Science*,43(8), 2522-2535.

Khan, A. A. (2007). Electrode wear and material removal rate during EDM of aluminum and mild steel using copper and brass electrodes. *The International Journal of Advanced Manufacturing Technology*, *39*(5-6), 482-487.

Kiyak, M., Aldemir, B. E., & Altan, E. (2015). Effects of discharge energy density on wear rate and surface roughness in EDM. *The International Journal of Advanced Manufacturing Technology*, 79(1-4), 513-518.

Kumar, S., & Singh, R. (2010). Investigating surface properties of OHNS die steel after electrical discharge machining with manganese powder mixed in the dielectric. *The International Journal of Advanced Manufacturing Technology*, *50*(5-8), 625-633.

Kung, K., Horng, J., & Chiang, K. (2007). Material removal rate and electrode wear ratio study on the powder mixed electrical discharge machining of cobalt-bonded tungsten carbide. *The International Journal of Advanced Manufacturing Technology*, 40(1-2), 95-104.

Leao, F. N., & Pashby, I. R. (2004). A review on the use of environmentallyfriendly dielectric fluids in electrical discharge machining. *Journal of Materials Processing Technology*, *149*(1-3), 341-346.

Li, L., Li, Z. Y., Wei, X. T., & Cheng, X. (2014). Machining Characteristics of Inconel 718 by Sinking-EDM and Wire-EDM. *Materials and Manufacturing Processes*, *30*(8), 968-973.

Lin, J. L., Wang, K. S., Yan, B. H., & Tarng, Y. S. (2000). An Investigation into Improving Worn Electrode Reliability in the Electrical Discharge Machining Process. *The International Journal of Advanced Manufacturing Technology*, *16*(2), 113-119.

Lin, Y., & Lee, H. (2008). Machining characteristics of magnetic force-assisted EDM. *International Journal of Machine Tools and Manufacture*,48(11), 1179-1186.

Maradia, U., Knaak, R., Busco, W. D., Boccadoro, M., & Wegener, K. (2015). A strategy for low electrode wear in meso-micro-EDM. *Precision Engineering*, 42, 302-310.

Miko, B., Dregelyi-Kiss, A., & Poor, A. (2014). Study on surface quality and electrode wear in EDM technology. *Development in Machining Technology*, 1(4), 194-211.

Miller, S. F., Shi, E., Kao, C., Shih, A. J., & Qu, J. (2004). Investigation of Wire Electrical Discharge Machining of Thin Cross-Sections and Compliant Mechanisms. *Manufacturing Engineering and Materials Handling Engineering*. 45(15), 1717-1725.

Murray, J., Zdebski, D., & Clare, A. (2012). Workpiece debris deposition on tool electrodes and secondary discharge phenomena in micro-EDM. *Journal of Materials Processing Technology*,212(7), 1537-1547.

52

Pham, D. T., Ivanov, A., Bigot, S., Popov, K., & Dimov, S. (2006). An investigation of tube and rod electrode wear in micro EDM drilling. *The International Journal of Advanced Manufacturing Technology*, *33*(1-2), 103-109.

Prihandana, G. S., Sriani, T., Mahardika, M., Hamdi, M., Miki, N., Wong, Y. S., & Mitsui, K. (2014). Application of powder suspended in dielectric fluid for fine finish micro-EDM of Inconel 718. *The International Journal of Advanced Manufacturing Technology*, 75(1-4), 599-613.

Prasanna, J & Husain, I. (2016). A Study On the Impact of Magnetic Field On EDM process. *Department of Mechanical Engineering*, Anna University, 8(1), 35-38

Santos, R. F., Silva, E. R., Sales, W. F., & Raslan, A. A. (2016). Analysis of the Surface Integrity when Nitriding AISI 4140 Steel by the Sink Electrical Discharge Machining (EDM) Process. *Procedia CIRP*,45, 303-306.

Song, K. Y., Chung, D. K., Park, M. S., & Chu, C. N. (2013). Electrical discharge machining using a strip electrode. *Precision Engineering*, *37*(3), 738-745.

Teimouri, R., & Baseri, H. (2012). Study of Tool Wear and Overcut in EDM Process with Rotary Tool and Magnetic Field. *Advances in Tribology*, 2(12), 1-8.

Torres, A., Puertas, I., & Luis, C. (2015). Modelling of surface finish, electrode wear and material removal rate in electrical discharge machining of hard-to-machine alloys. *Precision Engineering*, 40, 33-45.

Uhlmann, E., & Domingos, D. C. (2016). Investigations on Vibration-assisted EDM-machining of Seal Slots in High-Temperature Resistant Materials for Turbine Components –Part II. *Procedia CIRP*, *42*, 334-339.

Zarepour, H., Tehrani, A. F., Karimi, D., & Amini, S. (2007). Statistical analysis on electrode wear in EDM of tool steel DIN 1.2714 used in forging dies. *Journal of Materials Processing Technology*, 187-188, 711-714.

53

Zaw, H., Fuh, J., Nee, A., & Lu, L. (1999). Formation of a new EDM electrode material using sintering techniques. *Journal of Materials Processing Technology*,89-90, 182-186.

Zhu, K., Wong, Y. S., & Hong, G. S. (2009). Multi-category micro-milling tool wear monitoring with continuous hidden Markov models. *Mechanical Systems and Signal Processing*, 23(2), 547-560.