

Strengthening of Reinforced Concrete Beams Using Bamboo Fiber/Epoxy Composite Plates in Flexure

Siew Choo Chin^{1,26a*}, Jacky Neing Sheng Moh^{1,b}, Shu Ing Doh^{1,c}, Fadzil Mat Yahaya^{1,d}, Jolius Gimbur^{2,e}

¹Faculty of Civil Engineering and Earth Resources, Universiti Malaysia Pahang, Lebuhraya Tun Razak, 26300 Gambang, Pahang, Malaysia

²Centre of Excellence for Advanced Research in Fluid Flow, Universiti Malaysia Pahang, Lebuhraya

Tun Razak, 26300 Gambang, Pahang, Malaysia

[a](mailto:scchin@ump.edu.my)scchin@ump.edu.my, [b](mailto:jackymoh94@gmail.com)jackymoh94@gmail.com, [c](mailto:dohsi@ump.edu.my)dohsi@ump.edu.my, [d](mailto:fadzil@ump.edu.my)fadzil@ump.edu.my, [e](mailto:jolius@ump.edu.my)jolius@ump.edu.my

ABSTRACT

Fiber reinforced polymer (FRP) is widely used in the construction industry for structural strengthening due to their outstanding mechanical properties. However, the production of synthetic fibers such as FRP is detrimental to the environment. Alternatively, natural fiber composite may be used as external strengthening material. This paper presents the potential of bamboo fiber composite plate (BFCP) to strengthen the reinforced concrete (RC) beams in flexure. The bamboo of species *Dendrocalamus asper* was used to produce the fiber and fiber-to-volume ratio was set at 2:5. The composite plate was fabricated by binding bamboo fibers with epoxy using a hand-lay-up method. The flexural and tensile strength of the BFCP was measured and all the beams were tested to failure under four-point bending test. It was found that BFCP exhibited a higher flexural and tensile strength compared to pure epoxy samples. Meanwhile, the RC beams strengthened using BFCP exhibited an increment of 10-12% in beam structural capacity compared to the un-strengthened beams. Bonding of BFCP in the flexure zone was able to divert the vertical cracks into diagonal at the edge of the composite plate. Findings from this work may serve as a useful guide to strengthen RC beams using a BFCP.

Keywords: Bamboo fiber composite, reinforced concrete beams, natural fibers, strengthening, structural, flexure

DOI: <https://doi.org/10.4028/www.scientific.net/KEM.821.465>

ACKNOWLEDGEMENTS

We thank Universiti Malaysia Pahang (UMP) for provision of Research Grant (RDU180309). We acknowledge the help of FKASA lab technicians for assisting in the four-point loading test.