

Z-source inverter pulse width modulation: A survey

M.S.Bakar^a; N.A.Rahim^b; K.H.Ghazali^a; A.H.M.Hanafi^a

^aFakulti Kejuruteraan Elektrik & Elektronik, Universiti Malaysia Pahang, Pekan, Pahang, Malaysia.

^bUMPEDAC, Universiti Malaya, Kuala Lumpur, Malaysia

ABSTRACT

The paper presents switching techniques for pulse-width-modulated-based z-source inverter; simple boost PWM, maximum boost PWM, maximum constant boost PWM, modified-reference PWM, modified space vector PWM, hysteresis current control, and sine carrier PWM. Concepts and ideas behind the techniques are briefly explained. An overall view is summed up of the PWM controls, in terms of their achievements and system involvement in ZSI.

KEYWORDS:

z-source inverter, pulse width modulation.

ACKNOWLEDGMENT

This work was financed by the Engineering Science Program of Universiti Malaysia Pahang (UMP), vote number RDU0903134. The author thanks UMPEDAC for placement throughout his research tenure.

REFERENCES

1. F.Z.Peng; "Z-source inverter"; IEEE Transactions on Industry Applications, vol. 39, pp. 504-510, 2003
2. P.C.Loh, D. M. Vilathgamuwa, Y. S. Lai, C. Geok Tin, Y. Li; "Pulsewidth modulation of Z-source inverters"; IEEE Transactions in Power Electronics, vol. 20, pp. 1346-1355,2005.
3. A.H.Rajaei, S.Kaboli, A.Emadi; "Sliding-Mode Control of Z-source inverter"; Industrial Electronics,. IECON 2008. 34th Annual Conference of IEEE.
4. R.Strzelecki ,G.S. Zinoviev; "Power Electronics in Smart Electrical Energy Networks"; Springer, 2008.
5. F.Z.Peng, S. Miaosen, Q. Zhaoming; "Maximum boost control of the Z-source inverter"; IEEE Transactions in Power Electronics, vol. 20, pp. 833-838, 2005.