## ENHANCEMENT OF SURFACE INTEGRITY IN CRYOGENIC HIGH SPEED BALL NOSE END MILLING PROCESS OF INCONEL 718

Musfirah Abdul Hadi<sup>a\*,</sup> Jaharah A. Ghani<sup>b</sup>

a Department of Manufacturing Technology, Faculty of Engineering Technology, University Malaysia Pahang, 26300 Gambang, Pahang, Malaysia

b Department of Mechanical & Materials Engineering, Faculty of Engineering and Built Environment, University Kebangsaan Malaysia, 43600 Bangi, Selangor, Malaysia musfirah@ump.edu.my

## Abstract:

Surface integrity of machined subsurface in any machining process has become an important aspect because of increased quality demands especially in high accuracy demand industries like aerospace, automotive, defense and medical applications. The attention of these industries is to achieve a good surface roughness, avoid plastically deformed layer and most cases increasing the hardness at the subsurface area for robust application. As is known, Inconel 718 is a difficult-to-machine material and it is often used in the manufacture of turbine gas and jet engines for aerospace applications. In most cases, Inconel 718 machining will be resulting an excessive heat generated at the cutting zone. This can cause in a variety of problems during machining such as rapid tool wear, damage on machined surface and microstructural defects. Hence, various cooling methods have been made to address these problems and improve the quality of machined surface. In this study, a cryogenic cooling technique using nitrogen liquids (LN2) was developed to cool the tool-chip interface during milling Inconel 718. The goal of this paper is to presents a comparison study on surface roughness, machined surface microhardness and subsurface microstructure changes between cryogenic cooling and dry techniques. The experiments conducted using a PVD coated with TiAIN/AICrN ball nose tungsten carbide for varying cutting speeds ranging between 140–160 m/min, a feed rate of 0.15-0.20 mm/tooth, and radial depth of cut of 0.2-0.4 mm. The results revealed that the cryogenic cooling technique is more effective than dry cutting for improving surface roughness and lessening deformation of microstructure changes underneath the machined surface. However, machining in dry technique has produced a high microhardness for machined surface compared to cryogenic cooling technique. Overall, the utilization of the cryogenic technique has improved the surface roughness to a maximum of 88% and reduced the plastic deformation layer, while dry machining can improve the surface microhardness up to 5%.

Keywords : Surface Integrity; Cryogenic; End Milling; Inconel 718

## References

- 1. Alauddin, M., Mazid, M. A., El Baradi, M. A. & Hashmi, M. S. J. 1998. Cutting forces in the end milling of Inconel 718. Journal of Materials Processing Technology 77(1-3): 153–159.
- 2. Aramcharoen, A. & Chuan, S. K. 2014. An Experimental Investigation on Cryogenic Milling of Inconel 718 and its Sustainability Assessment. Procedia CIRP 14: 529–534.
- 3. Bermingham, M. J., Kirsch, J., Sun, S., Palanisamy, S. & Dargusch, M. S. 2011. New observations on tool life, cutting forces and chip morphology in cryogenic machining Ti-6Al-4V. International Journal of Machine Tools and Manufacture 51(6): 500–511.
- 4. Dudzinski, D., Devillez, A., Moufki, A., Larrouquère, D., Zerrouki, V. & Vigneau, J. 2004. A review of developments towards dry and high speed machining of Inconel 718 alloy. International Journal of Machine Tools and Manufacture 44(4): 439–456.
- 5. Ezugwu, E. O., Bonney, J. & Yamane, Y. 2003. An overview of the machinability of aeroengine alloys. Journal of Materials Processing Technology 134(2): 233–253