

## Coal bottom ash as sand replacement in concrete : a review

*Khairunisa Muthusamy<sup>a,b</sup>, Mohamad Hafizuddin Rasi<sup>d</sup>, Gul Ahmed Jokhio<sup>c</sup>, Ahmed Mokhtar Albshir Budiea<sup>d</sup>, Mohd Warid Hussin<sup>e</sup>, Jahangir Mirza<sup>f</sup>*

<sup>a</sup> Faculty of Civil Engineering Technology, Universiti Malaysia Pahang, Lebuhraya Tun Razak, 26300 Gambang, Malaysia

<sup>b</sup> Earth Resources and Sustainability Centre, Universiti Malaysia Pahang, Lebuhraya Tun Razak, 26300 Gambang, Malaysia

<sup>c</sup> The British University in Dubai, Block 11, 1st and 2nd floor, Dubai International Academic City, PO Box 345015, Dubai, United Arab Emirates

<sup>d</sup> Faculty of Civil and Environmental Engineering, Universiti Tun Hussein Onn Malaysia, 86400 Parit Raja, Batu Pahat, Johor, Malaysia

<sup>e</sup> Forensic Engineering Centre, School of Civil Engineering, Faculty of Engineering, Universiti Teknologi Malaysia, Malaysia

<sup>f</sup> School of Engineering, University of Guelph, Guelph, Ontario N1G 2W1, Canada

### ABSTRACT

There is a need to improve the sustainability of concrete by incorporating waste by-products and at the same time controlling the use of precious river sand as well as invaluable land from becoming waste disposal area. Coal bottom ash (CBA) is one such by products that can be used as river sand substitute in concrete. The present study investigates the effects of CBA on fresh, mechanical, and durability properties of concrete as reported in literature. The chemical and physical properties of CBA are diverse from various sources and years of investigation as it is influenced by the coal combustion system. Being rich in silica, CBA has pozzolanic characteristic. Many experimental works revealed that CBA can be used in appropriate proportion to enjoy the benefits of workability, enhanced concrete strength and durability. Almost all the researchers promote the idea of turning variety of wastes to wealth to save valuable green area for better use rather than dumpsite and reduce high dependency on river sand mining supply to ensure the sustainability of green river environment for prosperity of all the nations.

### KEYWORDS

Coal bottom ash; Sand replacement; Sustainable concrete; Mechanical properties; Durability

**ACKNOWLEDGEMENTS**

The authors would like to thank Kementerian Pendidikan Malaysia and Universiti Malaysia Pahang for supporting the study through the following financial grant FRGS/1/2019/TK06/UMP/02/3.