

Facile fabrication of thin metal oxide films on porous carbon for high density charge storage

Bincy Lathakumary Vijayan^a, Izan Izwan Misnon^a, Gopinathan M. Anil Kumar^b, Keita Miyajima^b, Mogalahalli Venkatesh Reddy^c, Karim Zaghbi^c, Chelladurai Karuppiah^d, Chun-Chen Yang^d, Rajan Jose^{a,†}

^aNanostructured Renewable Energy Materials Laboratory, Faculty of Industrial Sciences & Technology, Universiti Malaysia Pahang, 26300 Kuantan, Malaysia

^bR&D Center, Noritake Co Ltd, 300 Higashiyama, Miyoshi, Aichi 470-0293, Japan

^cCentre of Excellence in Transportation Electrification and Energy Storage (CETEES), Hydro-Québec, Varennes, QC J3X 1S1, Canada

^dBattery Research Center of Green Energy, Ming Chi University of Technology, New Taipei City, Taiwan

ABSTRACT:

In an effort to minimize the usage of non-renewable materials and to enhance the functionality of the renewable materials, we have developed thin metal oxide coated porous carbon derived from a highly abundant non-edible bio resource, i.e., palm kernel shell, using a one-step activation-coating procedure and demonstrated their superiority as a supercapacitive energy storage electrode. In a typical experiment, an optimized composition contained ~10 wt% of Mn₂O₃ on activated carbon (AC); a supercapacitor electrode fabricated using this electrode showed higher rate capability and more than twice specific capacitance than pure carbon electrode and could be cycled over 5000 cycles without any appreciable capacity loss in 1 M Na₂SO₄ electrolyte. A symmetric supercapacitor prototype developed using the optimum electrode showed nearly four times higher energy density than the pure carbon owing to the enhancements in voltage window and capacitance. A lithium ion capacitor fabricated in half-cell configuration using 1 M LiPF₆ electrolyte showed larger voltage window, superior capacitance and rate capability in the ~10 wt% Mn₂O₃@AC than the pure analogue. These results demonstrate that the current protocol allows fabrication of superior charge storing electrodes using renewable materials functionalized by minimum quantity of earthborn materials.

DOI: <https://doi.org/10.1016/j.icis.2019.11.077>

ACKNOWLEDGMENTS

This work has been carried out as part of Noritake Co. Ltd (Japan) – Universiti Malaysia Pahang (Malaysia) co-funded project on ceramic reinforced porous carbon paste ([RDU 192701](#)).