

**STUDY OF SAND BRICK RATIO 1:6 FOR
PARTIAL REPLACEMENT OF SAND WITH
PALM OIL CLINKER (5%, 10% AND 15%)**

NUR SYAHIRA BINTI CHE MOHD NAWI

B. ENG (HONS.) CIVIL ENGINEERING

UNIVERSITI MALAYSIA PAHANG



STUDENT'S DECLARATION

I hereby declare that the work in this project is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at University Malaysia Pahang or any other institutions.

(Student's Signature)

Full Name : NUR SYAHIRA BINTI CHE MOHD NAWI

ID Number : AA15265

Date : 31 May 2019

STUDY OF SAND BRICK RATIO 1:6 FOR PARTIAL REPLACEMENT OF
SAND WITH PALM OIL CLINKER (5%, 10% AND 15%)

NUR SYAHIRA BINTI CHE MOHD NAWI

Project submitted in fulfillment of the requirements
for the award of the
B. Eng (Hons.) Civil Engineering

Faculty of Civil Engineering & Earth Resources
UNIVERSITI MALAYSIA PAHANG

MAY 2019

ACKNOWLEDGEMENTS

Alhamdulillah, thanks to Allah S.W.T because with his grace I am able to complete this final year project successfully as to fulfil the requirements of final year student to complete my studies on the Degree in Civil Engineering Degree, University Malaysia Pahang.

Besides that, I would like to sincerely thank Madam Shariza Binti Mat Aris for guiding and continuously providing me with the knowledge required to conduct the research successfully besides sharing the excitement of new discoveries. Her faith and encouragement kept me steadfast in the process of acquiring the knowledge.

On top of that, I would like to thank my dearest family members especially mother Mrs.Ragayah and my classmates who have been always there for me whenever I faced obstacles due to my nature of work. Their presence and support gave me the strength and courage to overcome the arduous task in completing the thesis successfully.

ABSTRAK

Pada masa kini, industri pembinaan dan sistem pengurusan alam sekitar telah mengalami pembangunan yang pesat. Malangnya, pembangunan pesat industri pembinaan dan pengurusan alam sekitar telah membawa kepada pencemaran alam sekitar dan peningkatan penghasilan sisa daripada pelbagai sumber. Industri kelapa sawit adalah salah satu industri utama di Malaysia. Menurut Lembaga Minyak Sawit Malaysia (MPOB, 2015), pada tahun 2014 industri minyak sawit di Malaysia menghasilkan kira-kira 90 juta tan minyak sawit. Salah satu sisa yang dihasilkan dalam industri kelapa sawit adalah klinker kelapa sawit (POC). Penyelidikan ini adalah bertujuan untuk mengkaji mengenai penggunaan klinker kelapa sawit (POC) sebagai bahan penggantian separa untuk agregat halus dalam campuran bata simen dan pasir. Kajian ini akan memberi manfaat kepada alam sekitar dengan mengurangkan penggunaan pasir semula jadi. Kesan penggunaan peratusan yang berbeza POC untuk LWSB digunakan untuk mengkaji kekuatan mampatan. Terdapat tiga siri formulasi campuran simen pasir bata dengan ketumpatan campuran 1600 kg/m^3 telah disediakan yang terdiri daripada 5%, 10%, 15% sebagai pengganti pasir, separa daripada jumlah isipadu pasir akan digantikan dengan POC. Hasil daripada menggantikan POC telah menunjukkan bahawa kekuatan yang dihasilkan oleh bata tersebut mempunyai nilai kekuatan yang baik dan memenuhi keperluan di dalam standard JKR.

ABSTRACT

Nowadays, the construction industry and environmental management system has experienced a rapid development. Unfortunately, the rapid development of construction industry and environmental management has led to environmental pollution and the increased of waste generation from various sources. The oil palm industry is one of the major industries in Malaysia. According Malaysia Palm Oil Board (MPOB, 2015), palm oil industry in Malaysia produces about 90 million tons of palm oil in year 2014. A massive number of production will results to the massive number of waste produced. One of the waste produced in the oil palm industry is palm oil clinker (POC). This research is to study on the use of palm oil clinker (POC) as partial replacement for fine aggregate in cement sand brick. This study will benefits on reducing the use of natural sand. The effect of using different percentages of POC to LWSB due to compressive strength was investigated. There are three series of mix formulation of cement sand brick with mix density of 1600 kg/m^3 were prepared that comprise of 5%, 10%, 15% as partial sand replacement from the total volume of sand was replaced with POC. The outcomes from replacing POC has resulting a good strength as in per requirement in JKR standard.

TABLE OF CONTENT

DECLARATION

TITLE PAGE

ACKNOWLEDGEMENTS **ii**

ABSTRAK **iii**

ABSTRACT **iv**

TABLE OF CONTENT **v**

LIST OF TABLES **ix**

LIST OF FIGURES **x**

LIST OF SYMBOLS **xii**

LIST OF ABBREVIATIONS **xiii**

CHAPTER 1 INTRODUCTION **1**

1.1 Background of Study 1

1.2 Problem Statement 2

1.3 Objective of Study 2

1.4 Scope of Study 2

CHAPTER 2 LITERATURE REVIEW **4**

2.1 Introduction 4

2.2 General 4

2.2.1 Sand Brick 4

2.2.2 Palm Oil Clinker 5

2.3 Type of Brick 6

2.3.1	Clay Brick	6
2.3.2	Common Brick	6
2.3.3	Facing Brick	7
2.3.4	Engineering Brick	7
2.4	Material	8
2.4.1	Cement	8
2.4.2	Water	8
2.4.3	Sand	9
2.4.4	Palm Oil Clinker	10
2.5	Methods	10
2.5.1	Density	10
2.5.2	Water Absorption Rate	11
2.5.3	Compressive Strength	11
2.5.4	Flexural Strength	12
2.6	Curing Days	13
CHAPTER 3 METHODOLOGY		14
3.1	Introduction	14
3.2	Research Design	14
3.3	Preparation of Materials	16
3.3.1	Sand	16
3.3.2	Water	16
3.3.3	Cement	17
3.3.4	Palm Oil Clinker	17
3.4	Specimen Preparation	18
3.4.1	Curing	19

3.5	Method of Testing	22
3.5.1	Density Test	22
3.5.2	Water Absorption Test	23
3.5.3	Compressive Strength	24
3.5.4	Flexural Strength Test	25
CHAPTER 4 RESULTS AND DISCUSSION		26
4.1	Introduction	26
4.2	Sand Brick Test	26
4.2.1	Compressive Strength Test	27
4.2.2	Flexural Strength Test	37
4.2.3	Water Absorption Test	47
4.2.4	Density Test	50
4.3	Discussion	51
CHAPTER 5 CONCLUSION		52
5.1	Introduction	52
5.2	Conclusion	52
5.3	Recommendation	53
REFERENCES		54
APPENDIX A Compressive Strength (Water Curing) For 28 Days		57
APPENDIX B Compressive Strength (Water Curing) For 60 Days		58
APPENDIX C Compressive Strength (Water Curing) For 90 Days		59
APPENDIX D Compressive Strength (Air Curing) For 28 Days		60
APPENDIX E Compressive Strength (Air Curing) 60 Days		61

APPENDIX F Compressive Strength (Air Curing) For 90 Days	62
APPENDIX G Flexural Strength (Water Curing) For 28 Days	63
APPENDIX H Flexural Strength (Water Curing) For 60 Days	64
APPENDIX I Flexural Strength (Water Curing) For 90 Days	65
APPENDIX J Flexural Strength (Air Curing) For 28 Days	66
APPENDIX K Flexural Strength (Air Curing) For 60 Days	67
APPENDIX L Flexural Strength (Air Curing) For 90 Days	68
APPENDIX M Density and Water Absorption (Water Curing)	69
APPENDIX N Density and Water Absorption (Air Curing)	70

LIST OF TABLES

Table 2.1	Dimension of sand brick	5
Table 2.2	Oxide Composition of Ordinary Portland cement (Fahim Sediqi, 2013)	8
Table 2.3	Types of biomass and quantity produced	10
Table 2.4	Brick classification based on BS 392:1985	12
Table 2.5	Source: Nishita Sharma , 2017	13
Table 3.1	Volume of cement	17
Table 3.2	Mix Design	19
Table 3.3	Total Sample for Control Sample	20
Table 3.4	Total Sample for Mix 5%	20
Table 3.5	Total Sample for Mix 10%	21
Table 3.6	Total Sample for Mix 15%	21
Table 4.1	Compressive Strength Results (Water Curing)	35
Table 4.2	Compressive Strength Results (Air Curing)	36
Table 4.3	Flexural Strength Results (Water Curing)	45
Table 4.4	Flexural Strength Results (Air Curing)	46

LIST OF FIGURES

Figure 2.1	Sand Brick	4
Figure 2.2	Palm Oil Clinker	5
Figure 2.3	Clay Brick	6
Figure 2.4	Common Brick	6
Figure 2.5	Facing Brick	7
Figure 2.6	Engineering Brick	7
Figure 2.7	Cement	8
Figure 2.8	Design and Control of Concrete Mixtures”, EB001.14, PCA, 2002	9
Figure 2.9	Sand	9
Figure 2.10	Palm Oil Clinker	10
Figure 3.1	Flow of Research	15
Figure 3.2	Sieve	16
Figure 3.3	Tap Water	16
Figure 3.4	Cement	17
Figure 3.5	Sample Preparation	18
Figure 3.6	Specimen Preparation	18
Figure 3.7	Water Curing	19
Figure 3.8	Air Curing	20
Figure 3.9	Compressive Strength Test	24
Figure 3.10	Flexural Strength Test	25
Figure 4.1	Control Sample for Water Curing	27
Figure 4.2	Control Sample for Air Curing	28
Figure 4.3	5% of POC (Water Curing)	29
Figure 4.4	10% of POC (Water Curing)	30
Figure 4.5	15% of POC (Water Curing)	31
Figure 4.6	Ratio 5% POC (Air Curing)	32
Figure 4.7	Ratio 10% POC (Air Curing)	33
Figure 4.8	Ratio 15% POC (Air Curing)	34
Figure 4.9	Average for Water Curing	35
Figure 4.10	Average for Air Curing	36
Figure 4.11	Control Sample for Water Curing	37
Figure 4.12	Control Sample for Air Curing	38
Figure 4.13	5% POC (Water Curing)	39

Figure 4.14	10% POC (Water Curing)	40
Figure 4.15	15% POC (Water Curing)	41
Figure 4.16	5% POC (Air Curing)	42
Figure 4.17	10% POC (Air Curing)	43
Figure 4.18	15% POC (Air Curing)	44
Figure 4.19	Average for Water Curing	45
Figure 4.20	Average for Air Curing	46
Figure 4.21	Water Absorption for Sample 1	47
Figure 4.22	Water Absorption for Sample 2	48
Figure 4.23	Water Absorption for Sample 3	49
Figure 4.24	Density	50

LIST OF SYMBOLS

ρ	Density
m	Mass
V	Volume of brick
W	Water absorption rate
N/mm^2	Newton per millimetre square
Kg/mm^3	Kilogram per millimetre cube

LIST OF ABBREVIATIONS

POC	Palm Oil Clinker
MPOB	Malaysia Palm Oil Board
JKR	Jabatan Kerja Raya
PWD	Public Work Department
CTMS	Centre of Technology Management & Services

CHAPTER 1

INTRODUCTION

1.1 Background of Study

Nowadays, the construction industry and environmental management system has experienced a rapid development. Unfortunately, the rapid development of construction industry and environmental management has led to environmental pollution and the increased of waste generation from various sources. The oil palm industry is one of the major industries in Malaysia. According Malaysia Palm Oil Board (MPOB, 2015), palm oil industry in Malaysia produces about 90 million tons of palm oil in year 2014. A massive number of production will results to the massive number of waste produced. One of the waste produced in the oil palm industry is palm oil clinker (POC).

Palm oil clinker (POC) is a waste that are produced after the completion of the incineration process of palm oil shell and palm oil fibre in the boiler under temperature of about 850°C to heat the water until the steam was generated (Ahmmad et al., 2015). Physically palm oil clinker (POC) are porous, grey in colour, irregular in shape and much lighter compare to normal aggregate (Kandasan and Razak, 2015). POC size normally in sizes of 150mm to 200mm and it is easily to be found in Malaysia. Thus, POC has a potential to be used as replacement in construction material and one of the suggested material that can be replace by POC is sand. Sand is one of the material that largely used in construction industry and were obtained from natural resources. Lately, the price of the sand has increase due to the limited resources and demand for the material. Utilizing POC as a partial sand replacement might be a good move for the construction industry since the POC is low-cost compared to ordinary sand and at the same time we are able to preserve the environment from polluted.

1.2 Problem Statement

As the world is moving towards the concept of 3R (Recycle, Reuse, Reduce) and a sustainable environment, the reuse of waste materials not only helps to save the environment but also preserves the reduction of natural resources. Using a waste from the oil palm industry in the construction industry is a smart move towards creating sustainable environment. Palm Oil clinker (POC) is one of the waste produced by oil palm industry. Around 2.6 million tons of solid waste was produced annually by the palm oil industry which mostly composed of POC and palm oil shell (Basri et al., 1999). POC has a potential to be used as partial replacement for the fine aggregate in cement sand brick production after being crushed.

The source of the ordinary sand was from the natural resources and it is not renewable. Thus, reducing the natural sand used is one of the way to sustain the environment. Overuse of natural sand from river can causes river channel degradation and erosion, head cutting, increased turbidity, stream bank erosion and sedimentation of riffle areas (Kondolf,1993). Thus, a study on the use of palm oil clinker (POC) as partial replacement for fine aggregate in cement sand brick with a view of utilization of the resources and to save environment is necessary. In order to examine the effectiveness of POC as a partial sand replacement in cement sand brick and it applicability, few lab testing were conducted and the result will be compare with plain cement sand brick.

1.3 Objective of Study

The objectives of the study are:

- a) To determine the optimum ratio of palm oil clinker in cement sand brick.
- b) To investigate the characteristics of cement sand brick with palm oil clinker in terms of density, water absorption rate, compressive strength and flexural strength.

1.4 Scope of Study

In this study, the dimensions of the brick are according to the Public Work Department (PWD) Standard Specification for Buildings Works, 2005, Section E – Brickworks, it stated that, all cement sand brick shall comply with MS 27. The nominal size of cement sand brick is, the length is 225 mm (± 3.2), width is 113mm (± 1.6) and depth is 75mm $\pm (1.6)$.

The ratio used for the brick mixture is 6 ratio 1 (6:1), 6 parts for sand and 1 part for cement. The percentage of sand brick with palm oil clinker as partial replacement for fine aggregate are limited to percentage of ratio 5% 10% and 15%. The specimen will be examined in detail on the characteristics of the cement sand brick that are brick density, water absorption rate, compressive strength and flexural strength. The laboratory testing for the properties of the sand brick will be conducted at 28 days, 60 days and 90 days.

REFERENCES

- Abutaha, F., Abdul Razak, H. and Kanadasan, J. (2016) 'Effect of palm oil clinker (POC) aggregates on fresh and hardened properties of concrete', *Construction and Building Materials*. Elsevier Ltd, 112(May 2018), pp. 416–423. doi: 10.1016/j.conbuildmat.2016.02.172.
- Abutaha, F. and Razak, H. A. (2017) 'Effect of Coating Palm Oil Clinker Aggregate on the Engineering Properties of Normal Grade Concrete', *Coatings*, 7(10), p. 175. doi: 10.3390/coatings7100175.
- Ahmad, M. H. and Mohd, S. (2007) 'Mechanical Properties of Palm Oil Clinker Concrete', *1st Engineering Conference on Energy & Environment Engineering Conference on Energy & Environment*, (December).
- Ali, N. M. *et al.* (2016) 'Mix Design : Effect of Mixing Constituents towards Palm Oil Clinker Lightweight Aggregate Concrete', (October), pp. 747–751.
- American Society for Testing and Materials (2017) 'Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units', *American Society for Testing and Materials*, 04, pp. 1–10. doi: 10.1520/C0140.
- Ariffin, N. F. (2016) 'International Journal of Civil Engineering and PALM OIL CLINKER : A POTENTIAL PARTIAL SAND REPLACEMENT IN BRICK PRODUCTION'.
- Arunima, V. R. and Sreelekshmi, S. (2016a) 'Effects on Compressive Strength on Using Palm Oil Clinker as Partial Replacement of Fine Aggregate in Concrete', *International Journal of Science and Research (IJSR)*, 5(6), pp. 815–817. doi: 10.21275/v5i6.nov164304.
- Arunima, V. R. and Sreelekshmi, S. (2016b) 'Study on Fresh Concrete Properties Using Palm Oil Clinker as Fine Aggregate Replacement Material', 7(6), pp. 315–319. doi: 10.1021/JF070893F.

ASTM C 642-13 (2013) ‘Standard test method for density, absorption, and voids in hardened concrete’, *ASTM International, West Conshohocken, PA*, (4), pp. 1–3.

ASTM C67 - 14 (2014) ‘Standard Test Methods for Sampling and Testing Brick and Structural Clay Tile’, *ASTM International*, i, pp. 1–12. doi: 10.1520/C0067-14.2.

Dash, M. K., Patro, S. K. and Rath, A. K. (2016) ‘Sustainable use of industrial-waste as partial replacement of fine aggregate for preparation of concrete – A review’, *International Journal of Sustainable Built Environment*. The Gulf Organisation for Research and Development, 5(2), pp. 484–516. doi: 10.1016/j.ijsbe.2016.04.006.

Huda, M. N. *et al.* (2018) ‘Performance of High Strength Lightweight Concrete Using Palm Wastes’, *IJUM Engineering Journal*, 19(2), pp. 30–42. doi: 10.31436/ijumej.v19i2.919.

Hussin, M. W. and Abdullah, K. (2009) ‘Properties of Palm Oil Fuel Ash Cement Based Aggregate’, *Malaysian Journal of Civil Engineering*, 21(1), pp. 17–31.

JKR (2005) ‘E D E R a T I O N O F a L Y S I a’, 20800.

Kanadasan, J. *et al.* (2015) ‘Feasibility studies of palm oil mill waste aggregates for the construction industry’, *Materials*, 8(9), pp. 6508–6530. doi: 10.3390/ma8095319.

Kanadasan, J. and Razak, H. A. (2014) ‘Mix design for self-compacting palm oil clinker concrete based on particle packing’, *Materials and Design*. Elsevier Ltd, 56, pp. 9–19. doi: 10.1016/j.matdes.2013.10.086.

Kanadasan, J. and Razak, H. A. (2015) ‘Utilization of palm oil clinker as cement replacement material’, *Materials*, 8(12), pp. 8817–8838. doi: 10.3390/ma8125494.

Mat Aris, S. *et al.* (2018) ‘Properties of palm oil fuel ash cement sand brick containing pulverized cockle shell as partial sand replacement’, *IOP Conference Series: Earth and Environmental Science*, 140(1). doi: 10.1088/1755-1315/140/1/012145.

Shafigh, P. *et al.* (2014) ‘Structural lightweight aggregate concrete using two types of waste from the palm oil industry as aggregate’, *Journal of Cleaner Production*, 80, pp. 187–196. doi: 10.1016/j.jclepro.2014.05.051.

Subramaniam, V. *et al.* (2010) ‘LIFE CYCLE ASSESSMENT OF THE PRODUCTION OF CRUDE PALM OIL (Part 3)’, *Journal of Oil Palm Research*, 22(October), pp. 895–903. Available at: <https://pdfs.semanticscholar.org/6d8d/3a283086d5fb4dd8998d522f01a50aa0188e.pdf>.