



### SUPERVISOR'S DECLARATION

We hereby declare that we have checked this thesis and in our opinion, this thesis is adequate in terms of scope and quality for the award of the degree of Master of Science.



(Supervisor's Signature)

Full Name : IR TS DR. SITI ZUBAIDAH BINTI SULAIMAN  
Position : SENIOR LECTURER  
Date : 12/7/2021



(Co-supervisor's Signature)

Full Name : TS DR. AZIZAN BIN RAMLI  
Position : SENIOR LECTURER  
Date : 16/7/2021



## STUDENT'S DECLARATION

I hereby declare that the work in this thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at Universiti Malaysia Pahang or any other institutions.

A handwritten signature in black ink, appearing to be 'Nurul Syazwana Binti Noor Azmi', is written over a horizontal line.

(Student's Signature)

Full Name : NURUL SYAZWANA BINTI NOOR AZMI

ID Number : MKC16029

Date : 16/9/2021

SIMULATION AND EXPERIMENTAL STUDY OF BIOGAS EXPLOSION

NURUL SYAZWANA BINTI NOOR AZMI

Thesis submitted in fulfillment of the requirements  
for the award of the degree of  
Master of Science

College of Engineering  
UNIVERSITI MALAYSIA PAHANG

APRIL 2021

## ACKNOWLEDGEMENTS

In the name of Allah, the Most Merciful, the Most Compassionate, the Most Beneficent, the Most Gracious. All praises belong to Almighty Allah, the Lord of the worlds. Prayers and peace to Prophet Muhammad SAW (Peace Be Upon Him). His servant and messenger who has guided mankind towards human perfection, morality, justice and knowledge. Alhamdulillah, I am thankful to Allah, for His help, blessings and guidance by giving me the opportunity, courage, energy and love to complete this research.

First and foremost, I would like to extend my genuine gratitude and appreciation to my supervisor, Ir Ts Dr. Siti Zubaidah binti Sulaiman for her inspirational guidance, assistance, advice, motivations, supports and encouragements throughout the processes of researching and writing this thesis. I also would like to thank her for the time spared to review this thesis and for her valuable comments and insights to improve this thesis. This accomplishment would not have been possible without her tremendous help.

Besides, my grateful acknowledgements are given to Dr. Lau Woon Phui for her tremendous efforts in helping me to use CFD using Ansys Fluent. Furthermore, not to forget my thanks to Miss Nur Hazwani Fatimah bt Mohd Zaidi from UTM for also teaching me about CFD. Without their help, this thesis cannot be completed. Further acknowledgements go to Dr. Jolius Gimbut, for giving me the permission to use Ansys Fluent in computer simulation laboratory located in CARIFF, UMP Gambang.

Furthermore, my deepest appreciation to my family members especially my parents, Noor Azmi bin Said and Shakina bt A Rahman for their constant loves, supports, sacrifices, patience and encouragements throughout the course of this study. My hearty thanks to my siblings, Syazwani, Syazwan, Syazlee and Syazryqal for being there through my ups and downs moments.

In addition, my sincere thanks to all my friends, my roommates, and my research mates for their endless support and encouragements. Thank you for all the great times we have together and fun times we shared. Last but not least, my greatest sense of gratitude to one and all, who directly or indirectly, have lent their hand in this research.

## ABSTRAK

Biogas merupakan pengganti yang menarik kepada bahan api petroleum konvensional kerana mereka mempunyai kebaikan iaitu ianya sangat murah dan boleh diperbaharui semula secara natural. Beberapa teknik sudah dibangunkan untuk mengelak kemusnahan yang menghancurkan kepada loji-loji biogas dalam industri. Langkah mengelak letupan yang paling praktikal ialah pemasangan alat pelepasan gas. Kajian tentang letupan gas dan debu yang dilepaskan sudah menunjukkan evolusi kawasan pelepasan dengan tekanan bergantung kepada keadaan campuran bahan letupan (komposisi, tekanan dan suhu awal, pergolakan sebelum pencucuhan) dan kepada ciri-ciri bekas letupan (dimensi, bentuk, kehadiran halangan dan lain-lain). Kefahaman terhadap mekanisme bagaimana tekanan terbentuk dalam proses letupan yang dilepaskan adalah penting dalam mereka bentuk langkah pelepasan letupan dan kepada penyiasatan insiden. Pendekatan yang lain menggunakan alat pelepasan letupan ialah termasuk dengan kehadiran saluran pelepasan. Walaupun alat pelepasan letupan adalah penyelesaian yang biasa kepada langkah mengelak letupan tidak sengaja dalam alatan industri, jumlah kajian mengenai saluran pelepasan letupan adalah sangat kecil. Dalam kajian ini, penyiasatan terhadap ciri-ciri letupan biogas-udara dan metana-udara pra-campur dilakukan melalui analisis kepada tekanan letupan maksimum dan kelajuan nyalaan. Faktor-faktor yang menyumbang kepada ciri-ciri letupan pra-campuran bahan api-udara yang dinilai ialah panjang dan diameter saluran pelepasan letupan, kepekatan campuran dan juga kehadiran karbon dioksida. Selain daripada itu, penyebaran nyalaan daripada bahan api dan udara dalam letupan yang dilepaskan melalui saluran dan tanpa saluran turut disiasat. Keputusan numerik daripada kajian CFD dibandingkan dengan pemerhatian daripada kerja-kerja eksperimen. Pemerhatian kepada kontur tekanan 2D untuk kedua-dua letupan yang dilepaskan kepada saluran dan tanpa saluran didapati daripada program Fluent menunjukkan bacaan tekanan untuk letupan yang dilepaskan kepada saluran mempunyai nilai maksimum di dua kawasan di dalam paip letupan. Kehadiran saluran pelepasan mempengaruhi kawasan nyalaan dan seterusnya tekanan yang direkod sementara untuk letupan yang dilepaskan tanpa saluran, kontur tersebut menunjukkan reaksi letupan dan proses penyebaran nyalaan yang lebih mudah. Penilaian mendapati kesan panjang saluran yang berbeza membuktikan bahawa bacaan tekanan maksimum untuk kedua-dua jenis campuran gas ialah pada saluran dengan panjang 0.50 m. Bacaan tekanan yang direkodkan ialah 4.66 bar dan 5.99 bar sementara untuk kelajuan nyalaan masing-masing ialah 146.22 m/s serta 149.65 m/s untuk campuran biogas-udara dan metana-udara. Selain itu, untuk faktor diameter saluran yang berbeza, rekod bacaan tertinggi bagi tekanan dan kelajuan nyalaan ialah pada diameter 0.05 m (4.66 bar dan 146.22 m/s untuk campuran biogas-udara sementara 5.99 bar dan 149.65 m/s untuk campuran metana-udara). Siasatan terhadap kesan kepekatan campuran kepada tekanan maksimum dan kelajuan nyalaan menunjukkan nilai tertinggi direkod ketika  $ER=1$  iaitu pada keadaan stoikiometri. Semua kerja-kerja eksperimen bersandar kepada kerja-kerja numerik dan siasatan terhadap kesan nisbah keseimbangan  $ER$  yang berbeza dilakukan sepanjang paip. Selain itu, berdasarkan bacaan tekanan maksimum yang direkod melalui kerja-kerja eksperimen menunjukkan campuran metana menghasilkan letupan yang lebih teruk berbanding campuran biogas. Akhir sekali, graf tekanan maksimum melawan masa bagi kedua-dua kerja numerik dan eksperimen dikaji. Selain daripada beberapa perbezaan, kedua-dua graf adalah dalam persetujuan bersama. Perbezaan yang terjadi mungkin disebabkan oleh andaian yang dibuat dalam ANSYS Fluent dan hanya persamaan reaksi kimia mudah yang dipertimbangkan di dalam model simulasi.

## ABSTRACT

Biogas is an attractive substitute to conventional petroleum fuels because they have the advantages of being very cheap and are renewable in nature, and thereby not contributing to the net atmospheric concentration of the greenhouse gas, carbon dioxide. Several techniques have been developed to prevent the destructive damage to biogas plants in industries. Studies on vented gas and dust explosions have shown the evolution of venting area with pressure depending on the nature and state of the explosive mixture (composition, initial pressure and temperature, pre-ignition turbulence) and on the vessel characteristics (dimension, shape, presence of obstacles and others). An understanding of the mechanisms by which pressure is generated in vented explosions is important in the design of explosion reliefs and to the investigation of incidents. Another approach using venting system also included venting with a presence of venting duct. While venting devices are common solutions for the mitigation of accidental explosions in industrial equipment, study about duct venting are still very small. Researches on biogas explosion in cylindrical vessel are also very limited. In this study, the investigation of explosion characteristics of the premixed biogas-air and methane-air were analysed through the explosion maximum overpressure and flame speed. The factors that contributed to the premixed fuels-air explosions characteristics was evaluated which are the venting duct length and diameter, the mixture concentration as well as the presence of carbon dioxide by comparing biogas-air and methane-air explosions. Moreover, the flame propagation of fuels-air in duct vented and simply vented explosion were investigated by using numerical simulation. The numerical results were compared with the observation from experimental works. From the observation of 2D pressure contours for both duct vented and simply vented explosion obtained from Fluent, for duct vented explosion, the pressure readings were at maximum at two areas of the pipe. The presence of the duct affected the flame area and consecutively the overpressure recorded while for the simply vented (ductless) explosion, the contour gave observations of a simpler reaction and flame propagation. From the evaluation, the effect of different duct length proved that the highest maximum overpressure recorded for both gases were at duct length of 0.50 m. The overpressure recorded were 4.66 bar and 5.99 bar as well as 146.22 m/s and 149.65 m/s of flame speed for biogas-air mixture and methane-air mixture respectively. Apart from that, for factor of different duct diameters, the highest maximum overpressure and flame speed recorded for both mixtures are at 0.05 m (4.66 bar and 146.22 m/s for biogas-air while 5.99 bar and 149.65 m/s for methane-air mixtures). In the meantime, the investigation on effect of mixture concentration on maximum overpressure and flame speed shows the highest values for these two explosion characteristics were recorded at  $ER=1$  which is stoichiometric condition. All the experimental works validate the simulation works by carrying the experiment along the pipe for different ER. Apart from that, based on the recorded maximum overpressure in experimental works of biogas-air and methane-air mixtures explosions, it can be elucidated that methane produced higher explosion severity than biogas. This was due to the dilution effect of  $CO_2$ , which has a higher heat capacity than methane. Lastly, both graphs of maximum overpressure versus time from numerical and experimental works were presented and studied. Besides several differences mentioned previously, the graphs were in agreement with each other. The differences might be due to the assumption made in ANSYS Fluent and only a simple chemical reaction equation was considered in the model.

## TABLE OF CONTENTS

<b>DECLARATION</b>	
<b>TITLE PAGE</b>	
<b>ACKNOWLEDGEMENTS</b>	<b>ii</b>
<b>ABSTRAK</b>	<b>iii</b>
<b>ABSTRACT</b>	<b>iv</b>
<b>TABLE OF CONTENTS</b>	<b>v</b>
<b>LIST OF TABLES</b>	<b>viii</b>
<b>LIST OF FIGURES</b>	<b>ix</b>
<b>LIST OF SYMBOLS</b>	<b>xi</b>
<b>LIST OF ABBREVIATIONS</b>	<b>xii</b>
<b>CHAPTER 1 INTRODUCTION</b>	<b>1</b>
1.1 Research Background	1
1.2 Problem Statement	3
1.3 Research Objectives	7
1.4 Scope of Study	8
1.5 Overview of Thesis	9
<b>CHAPTER 2 LITERATURE REVIEW</b>	<b>10</b>
2.1 Introduction	10
2.2 Biogas	11
2.3 Biogas Plants in Malaysia	14
2.4 Gas Explosion	15
2.5 Gas Explosion Parameters	18
2.6 Gas Explosion Protection System	19
2.6.1 Venting	19

2.7	Influencing factors on flame propagation and pressure development	24
2.7.1	Effect of Duct Diameter	24
2.7.2	Effect of Duct Length	27
2.7.3	Effect of Mixture Concentration	29
2.7.4	Effect of presence of carbon dioxide	30
2.8	Numerical Simulation in Gas Explosion	30
2.9	Summary	33
<b>CHAPTER 3 METHODOLOGY</b>		<b>35</b>
3.1	Introduction	35
3.2	Computational Fluid Dynamics	36
3.2.1	Governing Equations in Ansys Fluent	36
3.2.2	Combustion Model	38
3.2.3	Detailed procedure for numerical simulation	39
3.3	Experimental Procedure	45
3.3.1	Test pipes rig	45
3.3.2	Ignition System	49
3.3.3	Gas handling and mixing preparations	50
3.3.4	Instrumentation and data collection	51
3.3.5	Detailed experimental procedure	53
3.3.6	Special safety procedure	55
3.3.7	Calculations of flame surface area, unburned gas velocity and Reynold's number	55
3.4	Summary	56
<b>CHAPTER 4 RESULTS AND DISCUSSION</b>		<b>58</b>
4.1	Introduction	58



4.2	Numerical Simulation Results	58
4.2.1	Mechanism of flame propagation	58
4.2.2	Effect of duct length	63
4.2.3	Effect of duct diameter	71
4.2.4	Effect of mixture concentration	76
4.3	Experimental Results	80
4.3.1	Effect of mixture concentration on gas explosion severity	81
4.3.2	Comparison between methane-air and biogas-air mixture reaction.	89
4.4	Comparison between numerical simulations and experimental works.	91
4.5	Summary	93
	<b>CHAPTER 5 CONCLUSION AND RECOMMENDATION</b>	<b>96</b>
5.1	Conclusion	96
5.2	Recommendations	98
	<b>REFERENCES</b>	<b>99</b>

## REFERENCES

- Anggono, W., Lawes, M., Hughes, K. J., & Wahyudi, S. (2012). Laminar Burning Characteristics Of Biogas-Air Mixtures In Spark Ignited Premix, 8(8), 4126–4132.
- Anggono, W., Wardana, I. N. G., Lawes, M., & Hughes, K. J. (2013a). Effect of inhibitors on biogas laminar burning velocity and flammability limits in spark ignited premix combustion. *International Journal of Engineering and Technology*, 5(6), 4980–4987. <https://doi.org/10.1088/1742-6596/423/1/012015>
- Anggono, W., Wardana, I. N. G., Lawes, M., & Hughes, K. J. (2013b). Effect of inhibitors on biogas laminar burning velocity and flammability limits in spark ignited premix combustion. *International Journal of Engineering and Technology*, 5(6), 4980–4987. <https://doi.org/10.1088/1742-6596/423/1/012015>
- Ayache, A. (2017). Experimental Measurement of Turbulent Burning Velocity of Premixed Biogas Flame by.
- Bao, Q., Fang, Q., Zhang, Y., Chen, L., Yang, S., & Li, Z. (2016). Effects of gas concentration and venting pressure on overpressure transients during vented explosion of methane-air mixtures. *Fuel*, 175, 40–48. <https://doi.org/10.1016/j.fuel.2016.01.084>
- Casson Moreno, V., Papisidero, S., Scarponi, G. E., Guglielmi, D., & Cozzani, V. (2016). Analysis of accidents in biogas production and upgrading. *Renewable Energy*, 96, 1127–1134. <https://doi.org/10.1016/j.renene.2015.10.017>
- Chan, Y. L., Zhu, M. M., Zhang, Z. Z., Liu, P. F., & Zhang, D. K. (2015). The Effect of CO<sub>2</sub> Dilution on the Laminar Burning Velocity of Premixed Methane/Air Flames. *Energy Procedia*, 75, 3048–3053. <https://doi.org/10.1016/j.egypro.2015.07.621>
- Chow, S. K., Cleaver, R. P., Fairweather, M., & Walker, D. G. (2000). an Experimental Study of Vented Explosions in. *Transactions Institute of Chemical Engineers*, 78(November), 425–433.
- Davazdah, S., Zubaidah, S., Diana, M., Rosmani, C., & Hassan, C. (2016). Journal of Loss Prevention in the Process Industries Effect of pipe configurations on flame propagation of hydrocarbons e air and hydrogen e air mixtures in a constant volume, 39, 141–151. <https://doi.org/10.1016/j.jlp.2015.11.005>
- Di Benedetto, A., Russo, P., & Salzano, E. (2007). Gas explosions mitigation by ducted venting. *Turkish Journal of Engineering and Environmental Sciences*, 31(6), 355–363.
- Dupont, L., & Accorsi, A. (2006). Explosion characteristics of synthesised biogas at various temperatures. *Journal of Hazardous Materials*, 136(3), 520–525. <https://doi.org/10.1016/j.jhazmat.2005.11.105>

- Farrell, T. M., Vingerhoets, J., Snoeys, J., & Going, J. (2013). Dust Flame Propagation in Industrial Scale Piping Part 1 : Empirical Study in a Conveying Vessel-Pipeline System, (May 2015), 1–23.
- Ferrara, G., Di Benedetto, A., Salzano, E., & Russo, G. (2006). CFD analysis of gas explosions vented through relief pipes. *Journal of Hazardous Materials*, *137*(2), 654–665. <https://doi.org/10.1016/j.jhazmat.2006.03.037>
- Ferrara, G., Willacy, S. K., Phylaktou, H. N., & Andrews, G. E. (2005). Duct-vented Propane / Air Explosions with Central and Rear Ignition, 1341–1352.
- Forsich, C., Lackner, M., Winter, F., Kopecek, H., & Wintner, E. (2004). Characterization of laser-induced ignition of biogas – air mixtures, *27*, 299–312. <https://doi.org/10.1016/j.biombioe.2004.02.002>
- Hong, Y., Lin, B., & Zhu, C. (2016). Premixed methane / air gas deflagration simulations in closed-end and open-end tubes, *8*(4), 271–284. <https://doi.org/10.1177/1756827716648640>
- Iida, N., Kawaguchi, O., & Sato, G. T. (1985). Premixed flame propagating into a narrow channel at a high speed, part 1: Flame behaviors in the channel. *Combustion and Flame*, *60*(3), 245–255. [https://doi.org/10.1016/0010-2180\(85\)90030-6](https://doi.org/10.1016/0010-2180(85)90030-6)
- Im, H. G., & Chen, J. H. (2002). Preferential Diffusion Effects on the Burning Rate of Interacting Turbulent Premixed Hydrogen-Air Flames, *258*, 246–258.
- Jin, K. (2018). Experimental study on a comparison of typical premixed combustible gas-air flame propagation in a horizontal rectangular closed duct, 1–13.
- Kasmani, R. M. (2008). Vented gas explosions. Retrieved from <http://theses.whiterose.ac.uk/1604/>
- Kundu, S. K., Zanganeh, J., Eschebach, D., Mahinpey, N., & Moghtaderi, B. (2017). Explosion characteristics of methane–air mixtures in a spherical vessel connected with a duct. *Process Safety and Environmental Protection*, *111*, 85–93. <https://doi.org/10.1016/j.psep.2017.06.014>
- Kyung, W., Mogi, T., & Dobashi, R. (2014). Effect of propagation behaviour of expanding spherical flames on the blast wave generated during unconfined gas explosions. *Fuel*, *128*, 396–403. <https://doi.org/10.1016/j.fuel.2014.02.062>
- Li, J., Lai, W. H., & Chung, K. (2006). Tube diameter effect on deflagration-to-detonation transition of propane-oxygen mixtures. *Shock Waves*, *16*(2), 109–117. <https://doi.org/10.1007/s00193-006-0056-8>
- Li, Q., Ciccarelli, G., Sun, X., Lu, S., Wang, X., Zhang, Z., ... Wang, C. (2018). Flame propagation across a flexible obstacle in a square cross-section channel. *International Journal of Hydrogen Energy*, *43*(36), 17480–17491. <https://doi.org/10.1016/j.ijhydene.2018.07.077>

- Li, Z., Zhang, X., & Chen, L. (2017). Vented Methane-air Explosion Overpressure Calculation — A simplified approach based on CFD. *Process Safety and Environmental Protection*, *109*, 489–508. <https://doi.org/10.1016/j.psep.2017.04.025>
- Luo, C., Zanganeh, J., & Moghtaderi, B. (2016). A 3D numerical study on the effects of obstacles on flame propagation in a cylindrical explosion vessel connected to a vented tube. *Journal of Loss Prevention in the Process Industries*, *44*, 53–61. <https://doi.org/10.1016/j.jlp.2016.08.016>
- McCann, D. P. J., Thomas, G. O., & Edwards, D. H. (1985). Gasdynamics of vented explosions part I: Experimental studies. *Combustion and Flame*, *59*(3), 233–250. [https://doi.org/10.1016/0010-2180\(85\)90128-2](https://doi.org/10.1016/0010-2180(85)90128-2)
- Molkov, V. V. (2001). Unified correlations for vent sizing of enclosures at atmospheric and elevated pressures. *Journal of Loss Prevention in the Process Industries*, *14*(6), 567–574. [https://doi.org/10.1016/S0950-4230\(01\)00037-7](https://doi.org/10.1016/S0950-4230(01)00037-7)
- Najafian Ashrafi, Z., & Ashjaee, M. (2014). Experimental study of a laminar premixed LFG/air flame in a slot burner using Mach-Zehnder interferometry. *Thermal Science*, *2014*(5), 1649–1660. <https://doi.org/10.2298/TSC141113147N>
- Nonaka, H. O. B., & Pereira, F. M. (2016). Experimental and numerical study of CO<sub>2</sub> content effects on the laminar burning velocity of biogas. *Fuel*, *182*, 382–390. <https://doi.org/10.1016/j.fuel.2016.05.098>
- Pizzuti, L., Torres, F. A., Ferreira, R. W., Santos, L. R., Lacava, P. T., & Martins, C. A. (2014). Laminar Burning Velocity and Flammability Limits in Biogas : a State of the Art. *10th International Conference on Heat Transfer, Fluid Mechanics and Thermodynamics*, (July), 98–107. Retrieved from [https://repository.up.ac.za/bitstream/handle/2263/44642/Pizzuti\\_Laminar\\_2014.pdf;sequence=1](https://repository.up.ac.za/bitstream/handle/2263/44642/Pizzuti_Laminar_2014.pdf;sequence=1)
- Ponizy. (1999). Flame dynamics in a vented vessel connected to a duct. Part 1 Mechanism of vessel-duct interaction. *Combustion and Flame*, *116*, 259–271.
- Ponizy, B., & Leyer, J. C. (1999). Flame dynamics in a vented vessel connected to a duct: 2. Influence of ignition site, membrane rupture, and turbulence. *Combustion and Flame*, *116*(1–2), 272–281. [https://doi.org/10.1016/S0010-2180\(98\)00039-X](https://doi.org/10.1016/S0010-2180(98)00039-X)
- Ponizy, Bogdan, Henneon, N., Claverie, A., & Veysiere, B. (2014). Detailed investigation of flame transmission from a vessel to a discharge duct, *161*, 1348–1364.
- Sinab, A. D. E. L., Bibliográficos, R., Amell, A., & Olmos, L. (2017). Ingeniería e Investigación, 2–7.
- Snoeys, J., Going, J. E., & Taveau, J. R. (2013). Dust Explosion Protection by Flameless Venting, *31*, 733–738

- Sulaiman<sup>1\*</sup>, S. Z., R.M. Kasmani<sup>2, 3</sup>, Mustafa<sup>2</sup>, A., Mudalip<sup>1</sup>, S. K. A., Che, R., Man<sup>1</sup>, Noo, N. S. (2017). Effect of pipe size on acetylene flame propagation in a closed straight pipe, *11*(4), 3095–3103. Retrieved from [http://jmes.ump.edu.my/images/Volume 11 Issue 4 December 2017/12\\_Sulaiman et al.pdf](http://jmes.ump.edu.my/images/Volume 11 Issue 4 December 2017/12_Sulaiman et al.pdf)
- Sun, S., Wang, M., Gao, K., Zhao, T., & Guo, Q. (2018). Effect of vent conditions on internal overpressure time-history during a vented explosion. *Journal of Loss Prevention in the Process Industries*, *54*(1), 85–92. <https://doi.org/10.1016/j.jlp.2018.03.002>
- Tang, P., & Jiang, J. (2011). Numerical simulation of duct-vented gas explosion. *Procedia Engineering*, *18*, 25–30. <https://doi.org/10.1016/j.proeng.2011.11.005>
- Tascón, A., & Aguado, P. J. (2015). CFD simulations to study parameters affecting dust explosion venting in silos. *Powder Technology*, *272*, 132–141. <https://doi.org/10.1016/j.powtec.2014.11.031>
- Zhang, K., Wang, Z., Yan, C., Cui, Y., Dou, Z., & Jiang, J. (2017). Effect of size on methane-air mixture explosions and explosion suppression in spherical vessels connected with pipes. *Journal of Loss Prevention in the Process Industries*, *49*, 785–790. <https://doi.org/10.1016/j.jlp.2017.02.013>
- Zhao, Z., Zhenyuan, J., & Haizhu, L. (2015). Characteristics of gas explosion flow fields in complex pipelines. *International Journal of Mining Science and Technology*, *25*(1), 157–164. <https://doi.org/10.1016/j.ijmst.2014.12.010>
- Zheng-yan, W., Shu-, J., Lan-, W., Kai, W., Wei-qing, Z., Hai-wei, W., & Wei-wei, L. (2009). *Procedia Earth and Planetary Science* Experimental study on explosion suppression of vacuum chambers with different scales, *1*, 396–401. <https://doi.org/10.1016/j.proeps.2009.07.063>
- Zheng, K., Yu, M., Liang, Y., & Zheng, L. (2018). ScienceDirect Large eddy simulation of premixed hydrogen / methane / air flame propagation in a closed duct, *3*.
- Zipf, R. K., Gamezo, V. N., Mohamed, K. M., Oran, E. S., & Kessler, D. A. (2014). Deflagration-to-detonation transition in natural gas-air mixtures. *Combustion and Flame*, *161*(8), 2165–2176. <https://doi.org/10.1016/j.combustflame.2014.02.002>