A narrative review on strengthening of reinforced concrete beams using carbon fibre reinforced polymer composite material through experimental investigation and numerical modelling

Solahuddin B.A.; Yahaya F.M

^a Faculty of Civil Engineering Technology, Level 1, Chancellery Building, Universiti Malaysia Pahang, Lebuh Persiaran Tun Khalil Yaakob, 26300 Kuantan, Pahang Darul Makmur, Malaysia

ABSTRACT

Carbon fibre reinforced polymer (CFRP) composite material has many benefits. The reinforced concrete beams (RCB) structural behaviour is improved due to the usage of CFRP composite material as external reinforcement. The effects of CFRP on various features are also essential to be summarised. This review paper concisely summarises the strengthening of RCB using CFRP. The flexure, stiffness, young modulus, load–deflection, ultimate load capacity, load-axial, fracture pattern, stress–strain distribution, and failure mechanism of RCB made with CFRP were significantly improved based on previous relevant experimental investigation and numerical modelling results. This CFRP composite material can be used as external reinforcement for RCB because of its overqualified strength capability, force, load, corrosion resistance, adhesive, and anchoring properties. Using CFRP composite material in civil and structural engineering can improve the RCB's structural behaviour and performance, particularly in the construction industry.

KEYWORDS

Carbon fibre reinforced polymer; Composite structure; Experimental investigation; Finite element analysis; Numerical modelling; Reinforced concrete beams; Structural behaviour; Structural performance

REFERENCES

[1] Uddin N, Farhat NS, Vaidya U, Serrano-Perez JC. Vulnerability Reduction for Bridge Piers. University Transportation Center for Alabama (UTCA) Report. 2005 Aug, 3229.

[2] Erki MA, Meier U. Impact loading of concrete beams externally strengthened with CFRP laminates. J Compos Constr 1999;3(3):117–24.

[3] Curtis PT. Crag Test Methods for the Measurement of the Engineering Properties of Fibre Reinforced Plastics, Royal Aerospace Establishment, Procurement Executive, Ministry of Defence, Farnborough, Hampshire; 1988.

[4] Huang Y, Jin KK, Ha SK. Effects of fiber arrangement on mechanical behavior of unidirectional composites. J Compos Mater 2008;42(18):1851e1871.

[5] Pineau P, Dau F. Subsampling and homogenisation to investigate variability of composite material mechanical properties. Comput Methods Appl Mech Eng 2012; 241e244:238e245.