



## Decanter cake as a feedstock for biodiesel production: A first report



Gaanty Pragas Maniam<sup>a,b,\*</sup>, Noor Hindryawati<sup>a,c</sup>, Irma Nurfitri<sup>a</sup>, Rajan Jose<sup>a</sup>, Mohd Hasbi Ab. Rahim<sup>a</sup>,  
Farrah Aini Dahalan<sup>d</sup>, Mashitah M. Yusoff<sup>a,b</sup>

<sup>a</sup> Faculty of Industrial Sciences and Technology, Universiti Malaysia Pahang, Lebuhraya Tun Razak, 26300 Gambang, Kuantan, Pahang, Malaysia

<sup>b</sup> Central Laboratory, Universiti Malaysia Pahang, Lebuhraya Tun Razak, 26300 Gambang, Kuantan, Pahang, Malaysia

<sup>c</sup> Faculty of Mathematics and Natural Sciences, Mulawarman University, Gunung Kelua, 75113 Samarinda, East Borneo, Indonesia

<sup>d</sup> School of Environmental Engineering, Universiti Malaysia Perlis, Kompleks Pengajian Kejuruteraan Jejawi 3, 02600 Arau, Perlis, Malaysia

### ARTICLE INFO

#### Article history:

Received 22 April 2013

Accepted 24 July 2013

#### Keywords:

Decanter cake

*In situ* transesterification

Ultrasound

Boiler ash

Biodiesel

### ABSTRACT

Decanter cake (DC), with an oil content of  $11.5 \pm 0.18$  wt.%, was subjected to ultrasound-aided transesterification using boiler ash as a base catalyst, petroleum ether and hexane as co-solvents. Optimization work revealed that at MeOH:oil mass ratio of 6:1 and 2.3 wt.% catalyst (based on DC weight) with 1:2 co-solvents:DC mass ratio as the optimal reaction conditions. Both decanter cake and boiler ash, waste materials from oil palm mill, were successfully utilized to produce methyl ester (biodiesel) with highest conversion of 85.9 wt.% in a 1 h reaction period at 55 °C.

© 2013 Elsevier Ltd. All rights reserved.

\* Corresponding author at: Faculty of Industrial Sciences and Technology, Universiti Malaysia Pahang, Lebuhraya Tun Razak, 26300 Gambang, Kuantan, Pahang, Malaysia. Tel.: +60 16 4110236; fax: +60 9 549 2766.

E-mail address: [gaanty@hotmail.com](mailto:gaanty@hotmail.com) (G.P. Maniam).