

Membrane technology for CO₂ removal from CO₂-rich natural gas

Shaik Muntasir Shovon¹, Faysal Ahamed Akash¹, Minhaj Uddin Monir^{1,2}, Mohammad Tofayal Ahmed^{1,2} and Azrina Abd Aziz³

¹Department of Petroleum and Mining Engineering, Jashore University of Science and Technology, Jashore, Bangladesh; ²Energy Conversion Laboratory, Department of Petroleum and Mining Engineering, Jashore University of Science and Technology, Jashore, Bangladesh; ³Faculty of Civil Engineering Technology, Universiti Malaysia Pahang Al-Sultan Abdullah, Kuantan, Pahang, Malaysia

1. Introduction

Gas separation is required to remove contaminants, hazardous gases, and CO₂ in order to produce gas that meets consumer demands. Membrane gas separation is a typical gas separation method. Membrane gas separation processes, such as absorption, distillation, and adsorption, provide various benefits, including minimal cost, simplicity of handling, higher selectivity, and the potential to connect with other operations [1]. Presently, the primary emphasis is on developing technology and polymer manufacturing for improved selectivity and permeability in order to meet demand. Numerous studies are being conducted to separate CO₂/CH₄ and O₂/N₂ from air and natural gases [2]. Membrane performance is determined by its manufacture and material structure, as well as separation mechanism [3].

Benchhold started the voyage of membrane gas separation in 1907 [4]. He was a pioneer in the development of nitrocellulose membranes with varying pore sizes. Collodion membranes with microparticle sizes first appeared on the market on a small scale in 1930s, when more refined membrane manufacturing procedures were devised [5,6]. Various polymers, such as cellulose acetate,