

REFERENCES

- [1] Abdel-Rahman E.M., Nayfeh A.H., Masoud Z.N., 2003, Dynamics and control of cranes: A review, *Journal of Vibration and Control*, 9, 863-908
- [2] Aschemann H., 2002, *Optimale Trajektrienplanung sowie modelgestützte Steuerung für einen Brückenkran*, Fortschritt-Berichte VDI, Reihe 8: Mess-, Steuerungs- und Regelungs-technik, Nr. 929, Düsseldorf
- [3] E. Kriikku, N. Singer, W.Singhose. *An Input Shaping Controller Enabling Crane Move Without Sway*. American Nuclear Society 7th Topical Meeting on Robotics and Remote Systems
- [4] Jones, S.D. and A.G. Ulsoy, "Control Input Shaping for Coordinate Measuring Machines," *American Control Conf.*, Baltimore, MD, Vol. 3, pp. 2899-2903, 1994.
- [5] Kim, Y. S.; Hong, K. S. & Sul, S.K., R., 2001, Anti-Sway Control of Container Cranes: Inclinometer, Observer and State Feedback. *International Journal of Control, Automation and Systems*, Vol. 2., No. 4, (December 2004) pp. 435-449
- [6] M. J. Robertson and W. E. Singhose, Closed-Form Deflection-Limiting Commands, American Control Conference, Portland, USA, 2005, pp.2104-2109
- [7] Pao, L. and W. Singhose, "Unity Magnitude Input Shapers and Their Relation to Time- Optimal Control," *IFAC World Congress*, San Francisco, CA, 1996.

- [8] Hu, H., Hu, Q., Lu, Z. and Xu, D., 2005, Optimal PID controller design in PMSM servo system via particle swarm optimization. Proc. IEEE Annual Conference of Industrial Electronics Society, pp.79-83.
- [9] Rosenfeld Y., Shapira A., 1998, Automation of existing tower cranes: economic and technological feasibility, *Automation in Construction*, 7, 285-298
- [10] Sawodny, O.; Aschemann, H.; Kumpel, J.; Tarin, C. & Schneider, K. (2002). Anti-sway control for boom cranes, *Proceedings of American Control Conference*, pp. 244-249 vol. 1, ISBN: 0-7803-7298-0, Alaska, May 2002, Anchorage
- [11] Singhose, W.E., Porter L.J. and Seering, W., "Input shaped of a planar gantry crane with hoisting," *Proc. of the American Control Conference*, 1997, pp. 97-100.
- [12] Sirri Sunay Gurleyuk, Ozgur Bahadir, Yunus Turkkan and Hakan Usenti, *Improved Three Step Input Shaping Control of Crane System*. Issue 6, Vol.7, June 2008.
- [13] Spong M.W., 1997, Underactuated mechanical systems, In: *Control Problems in Robotics and Automation*, B. Siciliano and K.P. Valavanis (edit.), Lecture Notes in Control and Information Sciences, Vol. 230, Springer-Verlag, London
- [14] Tuttle, T.D. and W.P. Seering, "A Zero-placement Technique for Designing Shaped Inputs to Suppress Multiple-mode Vibration," *American Control Conf.*, Baltimore, MD, Vol. 3, pp. 2533-2537, 1994.
- [15] M Araki: Control systems, Robotics and Automation-Vol II – PID Control –,Kyoto University ,Japan
- [16] King, S.S., (November, 2006)., Command Shaping Control of a Crane System. Universiti Teknologi Malaysia: Master Thesis

- [17] O. J. M. Smith, Posicast control of damped oscillatory systems, *Proceedings of the IRE*, 45 (1957) 1249-1255.
- [18] N. C. Singer and W. P. Seering, Preshaping command inputs to reduce system vibration, *J. of Dynamic Systems, Measurement and Control*, 112 (1990) 76-82.
- [19] K. L. Sorensen, W. E. Singhose and S. Dickerson, A controller enabling precise positioning and sway reduction in bridge and gantry cranes, *Control Engineering Practice*, 15 (2007) 825-837.
- [20] M. A. Ahmad, R. M. T. R. Ismail, M. S. Ramli, R. E. Samin and M. A. Zawawi, Robust input shaping for anti-sway control of rotary crane, *Proc. of TENCON 2009 - IEEE Region 10 Conference*, pp. 1039-1043, Nov. 23-26, 2009, Singapore.
- [21] W. E. Singhose, N. C. Singer and W. Seering, Time-optimal negative input shapers, *J. of Dynamic Systems, Measurement, and Control*, 119 (1997) 198-205.
- [22] D. Gorinevsky and G. Vukovich, Nonlinear input shaping control of flexible spacecraft reorientation maneuver, *AIAA J. of Guidance, Control, and Dynamics*, 21 (2) (1998) 264-270.
- [23] L. Y. Pao and W. E. Singhose, Verifying robust timeoptimal commands for multi-mode flexible spacecraft, *AIAA J. of Guidance, Control, and Dynamics*, 20 (4) (1997) 831-833.
- [24] J. Park, P. H. Chang, H. S. Park and E. Lee, Design of learning input shaping technique for residual vibration suppression in an industrial robot, *IEEE/ASME Trans. On Mechatronics*, 11 (1) (2006) 55-65.
- [25] C. G. Kang, K. S. Woo, J. W. Kim, D. J. Lee, K. H. Park and H. C. Kim, Suppression of residual vibrations with input shaping for a two-mode mechanical

- system, *Proc. of Int. Conf. on Service and Interactive Robotics*, Taipei, Taiwan (2009) 1-6.
- [26] S. Jones and A. Ulsoy, An approach to control input shaping with application to coordinate measuring machines, *J. of Dynamic Systems, Measurement, and Control*, 121 (1999)
- [27] S. Kapucu, G.. Alici and S. Baysec, Residual swing/vibration reduction using a hybrid input shaping method, *Mech. Mach. Theory*, 36 (2001) 311-326.
- [28] S. S. Gurleyuk and S. Cinal, Robust three-impulse sequence input shaper design, *Journal of Vibration and Control*, 13 (12) (2007) 1807-1818.
- [29] M.N.A. Zohari, 2010, Experimental investigation of input shaping techniques for double pendulum type overhead crane (DPTOC) system, November 2010, pp. 31-74.
- [30] H.M. Omar, 2003, Control of gantry and tower cranes. Ph.D. Thesis, M.S. Virginia Tech.